

A comparison between joint regression analysis and the AMMI model: A case study with barley

Joint regression analysis (JRA) and additive main effects and multiplicative interaction (AMMI) models are compared in order to (i) assess the ability of describing a genotype by environment interaction effects and (ii) evaluate the agreement between the winners of mega-environments obtained from the AMMI analysis and the genotypes in the upper contour of the JRA. An iterative algorithm is used to obtain the environmental indexes for JRA, and standard multiple comparison procedures are adapted for genotype comparison and selection. This study includes three data sets from a spring barley (*Hordeum vulgare* L.) breeding programme carried out between 2004 and 2006 in Czech Republic. The results from both techniques are integrated in order to advise plant breeders, farmers and agronomists for better genotype selection and prediction for new years and/or new environments.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Research Community on Data-to-Decision (D2D), Depto. de Matemática, NOVA University of Lisbon, Dept. of Mathematical and Statistical Methods

Contributors: Pereira, D. G., Rodrigues, P. C., Mejza, S., Mexia, J. T.

Number of pages: 15

Pages: 193-207

Publication date: Feb 2012

Peer-reviewed: Yes

Publication information

Journal: JOURNAL OF STATISTICAL COMPUTATION AND SIMULATION

Volume: 82

Issue number: 2

ISSN (Print): 0094-9655

Ratings:

Scopus rating (2012): CiteScore 1 SJR 0.604 SNIP 1.041

Original language: English

ASJC Scopus subject areas: Applied Mathematics, Statistics and Probability, Modelling and Simulation, Statistics, Probability and Uncertainty

Keywords: AMMI models, joint regression analysis, mega-environments, multiple comparisons, spring barley, zigzag algorithm

DOIs:

10.1080/00949655.2011.615839

URLs:

<http://www.scopus.com/inward/record.url?scp=84856990001&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84856990001

Research output: Contribution to journal › Article › Scientific › peer-review

Active scanner control on paper machines

The cross-directional (CD) basis weight control on paper machines is improved by optimizing the path of the scanning measurement. The optimal path results from an LQG problem and depends on how the uncertainty of the present estimate of the basis weight and the intensity of process noise vary in CD. These factors are assessed by how accurately the CD basis weight estimate predicts the measured optical transmittance with a linear adaptive model on synchronized basis weight and transmittance data. Simulations on optimized scanner path in disturbance scenarios are presented, and the practical implementation of scanner control is discussed.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Automation and Hydraulic Engineering

Contributors: Raunio, J., Ritala, R.

Number of pages: 17

Pages: 74-90

Publication date: 1 Dec 2018

Peer-reviewed: Yes

Publication information

Journal: Journal of Process Control

Volume: 72

ISSN (Print): 0959-1524

Ratings:

Scopus rating (2018): CiteScore 5.9 SJR 0.967 SNIP 2.027

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Computer Science Applications, Industrial and Manufacturing Engineering

Keywords: basis weight, linear-quadratic-Gaussian, optimal measurement, paper machine, scanner, transmittance, variance estimation, web-wide measurement

DOIs:

10.1016/j.jprocont.2018.09.012

Source: Scopus

Source ID: 85056176314

Research output: Contribution to journal › Article › Scientific › peer-review

Adaptive autoregressive model for reduction of noise in SPECT

This paper presents improved autoregressive modelling (AR) to reduce noise in SPECT images. An AR filter was applied to prefilter projection images and postfilter ordered subset expectation maximisation (OSEM) reconstruction images (AR-OSEM-AR method). The performance of this method was compared with filtered back projection (FBP) preceded by Butterworth filtering (BW-FBP method) and the OSEM reconstruction method followed by Butterworth filtering (OSEM-BW method). A mathematical cylinder phantom was used for the study. It consisted of hot and cold objects. The tests were performed using three simulated SPECT datasets. Image quality was assessed by means of the percentage contrast resolution (CR%) and the full width at half maximum (FWHM) of the line spread functions of the cylinders. The BW-FBP method showed the highest CR% values and the AR-OSEM-AR method gave the lowest CR% values for cold stacks. In the analysis of hot stacks, the BW-FBP method had higher CR% values than the OSEM-BW method. The BW-FBP method exhibited the lowest FWHM values for cold stacks and the AR-OSEM-AR method for hot stacks. In conclusion, the AR-OSEM-AR method is a feasible way to remove noise from SPECT images. It has good spatial resolution for hot objects.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Automation Science and Engineering, Division of Nuclear Medicine, Department of Diagnostic Radiology, Oulu University Hospital, Department of Clinical Physiology and Nuclear Medicine, Joint Authority for Päijät-Häme Social and Health Care

Contributors: Takalo, R., Hytti, H., Ihalainen, H., Sohlberg, A.

Publication date: 2015

Peer-reviewed: Yes

Publication information

Journal: Computational and Mathematical Methods in Medicine

Volume: 2015

Article number: 494691

ISSN (Print): 1748-670X

Ratings:

Scopus rating (2015): CiteScore 2.3 SJR 0.466 SNIP 0.726

Original language: English

ASJC Scopus subject areas: Applied Mathematics, Modelling and Simulation, Biochemistry, Genetics and Molecular Biology(all), Medicine(all), Immunology and Microbiology(all)

DOIs:

10.1155/2015/494691

URLs:

<http://www.scopus.com/inward/record.url?scp=84930684783&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84930684783

Research output: Contribution to journal › Article › Scientific › peer-review

Ageing first passage time density in continuous time random walks and quenched energy landscapes

We study the first passage dynamics of an ageing stochastic process in the continuous time random walk (CTRW) framework. In such CTRW processes the test particle performs a random walk, in which successive steps are separated by random waiting times distributed in terms of the waiting time probability density function $\varphi(t) \approx t^{-1-\alpha}$ ($0 \leq \alpha \leq 2$). An ageing stochastic process is defined by the explicit dependence of its dynamic quantities on the ageing time t_{inf} , the time elapsed between its preparation and the start of the observation. Subdiffusive ageing CTRWs with $0 < \alpha < 1$ describe systems such as charge carriers in amorphous semiconductors, tracer dispersion in geological and biological systems, or the dynamics of blinking quantum dots. We derive the exact forms of the first passage time density for an ageing subdiffusive CTRW in the semi-infinite, confined, and biased case, finding different scaling regimes for weakly, intermediately, and strongly aged systems: these regimes, with different scaling laws, are also found when the scaling exponent is in the range $1 < \alpha < 2$, for sufficiently long t_{inf} . We compare our results with the ageing motion of a test particle in a quenched energy landscape. We test our theoretical results in the quenched landscape

against simulations: only when the bias is strong enough, the correlations from returning to previously visited sites become insignificant and the results approach the ageing CTRW results. With small bias or without bias, the ageing effects disappear and a change in the exponent compared to the case of a completely annealed landscape can be found, reflecting the build-up of correlations in the quenched landscape.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Institute for Physics and Astronomy, University of Potsdam, National Institute of Chemistry Ljubljana

Contributors: Krüsemann, H., Godec, A., Metzler, R.

Publication date: 17 Jul 2015

Peer-reviewed: Yes

Publication information

Journal: Journal of Physics A: Mathematical and Theoretical

Volume: 48

Issue number: 28

Article number: 285001

ISSN (Print): 1751-8113

Ratings:

Scopus rating (2015): CiteScore 3.5 SJR 1.028 SNIP 1.04

Original language: English

ASJC Scopus subject areas: Mathematical Physics, Physics and Astronomy(all), Statistical and Nonlinear Physics, Modelling and Simulation, Statistics and Probability

Keywords: anomalous diffusion, first passage, random walks

DOIs:

10.1088/1751-8113/48/28/285001

URLs:

<http://www.scopus.com/inward/record.url?scp=84937118398&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84937118398

Research output: Contribution to journal > Article > Scientific > peer-review

A hybrid optimization grey model based on segmented gra and multi-strategy contest for short-term power load forecasting

In this paper, a hybrid grey model with both internal and external optimization is proposed to forecast the short-term power load which has the characteristics of nonlinear fluctuation and random growth. The internal optimization consists of modeling feasibility test and parameter a correction. The external optimization includes three aspects. First, the original series are selected from different viewpoints to construct different forecasting strategies. Second, the predicted day is divided into several smooth segments for separate forecasting. Finally, the different forecasting strategies are implemented respectively in the different segments through grey correlation contest. A practical application verifies that the proposed model has a higher forecasting accuracy and the independency on the choice of initial value.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Sensing Systems for Wireless Medicine (MediSense), Hunan University, Institute of Intelligence Engineering, Georgia Institute of Technology

Contributors: Min, J., Xiang, Z., Zhiming, Z., Tentzeris, M. M.

Number of pages: 14

Pages: 15-28

Publication date: 2012

Peer-reviewed: Yes

Publication information

Journal: JOURNAL OF GREY SYSTEM

Volume: 24

Issue number: 1

ISSN (Print): 0957-3720

Ratings:

Scopus rating (2012): CiteScore 0.9 SJR 0.374 SNIP 0.642

Original language: English

ASJC Scopus subject areas: Applied Mathematics, Control and Optimization, Modelling and Simulation, Statistics, Probability and Uncertainty

Keywords: External optimization, Hybrid grey model, Multi-strategy contest, Parameter a correction, Segmented grey correlation, Short-term power load forecasting

URLs:

<http://www.scopus.com/inward/record.url?scp=84858229525&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84858229525

Research output: Contribution to journal › Article › Scientific › peer-review

A Hybrid Task Graph Scheduler for High Performance Image Processing Workflows

Designing applications for scalability is key to improving their performance in hybrid and cluster computing. Scheduling code to utilize parallelism is difficult, particularly when dealing with data dependencies, memory management, data motion, and processor occupancy. The Hybrid Task Graph Scheduler (HTGS) improves programmer productivity when implementing hybrid workflows for multi-core and multi-GPU systems. The Hybrid Task Graph Scheduler (HTGS) is an abstract execution model, framework, and API that increases programmer productivity when implementing hybrid workflows for such systems. HTGS manages dependencies between tasks, represents CPU and GPU memories independently, overlaps computations with disk I/O and memory transfers, keeps multiple GPUs occupied, and uses all available compute resources. Through these abstractions, data motion and memory are explicit; this makes data locality decisions more accessible. To demonstrate the HTGS application program interface (API), we present implementations of two example algorithms: (1) a matrix multiplication that shows how easily task graphs can be used; and (2) a hybrid implementation of microscopy image stitching that reduces code size by $\approx 43\%$ compared to a manually coded hybrid workflow implementation and showcases the minimal overhead of task graphs in HTGS. Both of the HTGS-based implementations show good performance. In image stitching the HTGS implementation achieves similar performance to the hybrid workflow implementation. Matrix multiplication with HTGS achieves 1.3x and 1.8x speedup over the multi-threaded OpenBLAS library for $16k \times 16k$ and $32k \times 32k$ size matrices, respectively.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Pervasive Computing, Research area: Computer engineering, University of Maryland Baltimore County, National Institute of Standards and Technology, Department of Electrical and Computer Engineering, University of Maryland

Contributors: Blattner, T., Keyrouz, W., Bhattacharyya, S. S., Halem, M., Brady, M.

Number of pages: 11

Pages: 457–467

Publication date: 2017

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 89

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Dataflow, Heterogeneous architectures, Hybrid workflows, Image processing, Matrix multiplication, Task graph DOIs:

10.1007/s11265-017-1262-6

Source: Scopus

Source ID: 85025108758

Research output: Contribution to journal › Article › Scientific › peer-review

Algorithmic computation of knot polynomials of secondary structure elements of proteins

The classification of protein structures is an important and still outstanding problem. The purpose of this paper is threefold. First, we utilize a relation between the Tutte and homfly polynomial to show that the Alexander-Conway polynomial can be algorithmically computed for a given planar graph. Second, as special cases of planar graphs, we use polymer graphs of protein structures. More precisely, we use three building blocks of the three-dimensional protein structure - α -helix, antiparallel β -sheet, and parallel β -sheet - and calculate, for their corresponding polymer graphs, the Tutte polynomials analytically by providing recurrence equations for all three secondary structure elements. Third, we present numerical results comparing the results from our analytical calculations with the numerical results of our algorithm - not only to test consistency, but also to demonstrate that all assigned polynomials are unique labels of the secondary structure elements. This paves the way for an automatic classification of protein structures.

General information

Publication status: Published
MoE publication type: A1 Journal article-refereed
Organisations: Stowers Institute for Medical Research
Contributors: Emmert-Streib, F.
Number of pages: 10
Pages: 1503-1512
Publication date: 1 Oct 2006
Peer-reviewed: Yes

Publication information

Journal: Journal of Computational Biology
Volume: 13
Issue number: 8
ISSN (Print): 1066-5277
Ratings:
Scopus rating (2006): SJR 1.421 SNIP 1.155
Original language: English
ASJC Scopus subject areas: Molecular Biology, Genetics, Computational Mathematics, Modelling and Simulation, Computational Theory and Mathematics
Keywords: Knot polynomial, Planar graph, Protein structure, Topological invariant, Tutte polynomial
DOIs:
10.1089/cmb.2006.13.1503
URLs:
<http://www.scopus.com/inward/record.url?scp=34547671421&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 34547671421
Research output: Contribution to journal > Article > Scientific > peer-review

ALMARVI System Solution for Image and Video Processing in Healthcare, Surveillance and Mobile Applications

ALMARVI is a collaborative European research project funded by Artemis involving 16 industrial as well as academic partners across 4 countries, working together to address various computational challenges in image and video processing in 3 application domains: healthcare, surveillance and mobile. This paper is an editorial for a special issue discussing the integrated system created by the partners to serve as a cross-domain solution for the project. The paper also introduces the partner articles published in this special issue to discuss the various technological developments achieved within ALMARVI spanning all system layers, from hardware to applications. We illustrate the challenges faced within the project based on use cases from the three targeted application domains, and how these can address the 4 main project objectives addressing 4 challenges faced by high performance image and video processing systems: massive data rate, low power consumption, composability and robustness. We present a system stack composed of algorithms, design frameworks and platforms as a solution to these challenges. Finally, the use cases from the three different application domains are mapped on the system stack solution and are evaluated based on their performance for each of the 4 ALMARVI objectives.

General information

Publication status: Published
MoE publication type: A1 Journal article-refereed
Organisations: Pervasive Computing, Delft University of Technology, Philips Healthcare Nederland
Contributors: Al-Ars, Z., van der Vlugt, S., Jääskeläinen, P., van der Linden, F.
Pages: 1-7
Publication date: Jan 2019
Peer-reviewed: Yes
Early online date: 2018

Publication information

Journal: Journal of Signal Processing Systems
Volume: 91
Issue number: 1
ISSN (Print): 1939-8018
Ratings:
Scopus rating (2019): CiteScore 2.4 SJR 0.298 SNIP 0.833
Original language: English
ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture
DOIs:
10.1007/s11265-018-1423-2

Source: Scopus

Source ID: 85057058836

Research output: Contribution to journal › Article › Scientific › peer-review

Analysis of common rail pressure signal of dual-fuel large industrial engine for identification of injection duration of pilot diesel injectors

In this paper, we address the problem of identification of injection duration of common rail (CR) diesel pilot injectors of dual-fuel engines. In these pilot injectors, the injected volume is small and the repeatability of injections and identification of drifts of injectors are important factors, which need to be taken into account in order to achieve good repeatability (shot-to-shot with every cylinder) and therefore a well-balanced engine and furthermore reduced overall wear. This information can then be used for calibration and diagnostics purposes to guarantee engine longevity facilitated by consistent operating conditions throughout the life of the unit. A diagnostics method based on analysis of CR pressure with experimental results is presented in this paper. Using the developed method, the relative duration of injection events can be identified for multiple injectors. We use the phenomenon of drop in rail pressure due to an injection event as a feature of the injection process. The method is based on filtered CR pressure data during and after the injection event. First, the pressure signal during injection is extracted after control of each injection event. After that, the signal is normalized and filtered. Then a derivative of the filtered signal is calculated. Change in the derivative of the filtered signal larger than a predefined threshold indicates an injection event that can be detected and its relative duration can be identified. We present the experimental results and demonstrate the efficacy of the proposed methods using two different types of pressure sensors. We are able to properly identify a change of $\geq 10 \mu\text{s}$ (2%, 500 μs) in injection time. This shows that the developed method detects drifts in injection duration and the magnitude of drift. This information can be used for adaptive control of injection duration, so that finally the injected fuel volume is the same as the original.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Automation and Hydraulic Engineering

Contributors: Krogerus, T., Hyvönen, M., Huhtala, K.

Pages: 1-9

Publication date: Mar 2018

Peer-reviewed: Yes

Early online date: 6 Dec 2017

Publication information

Journal: Fuel

Volume: 216

ISSN (Print): 0016-2361

Ratings:

Scopus rating (2018): CiteScore 8.9 SJR 1.745 SNIP 2.041

Original language: English

ASJC Scopus subject areas: Mechanical Engineering, Signal Processing, Modelling and Simulation, Applied Mathematics

Keywords: Analysis , Dual-fuel engine , Diesel , Common rail , Injector , Rail pressure

Electronic versions:

Accepted author manuscript. Embargo ended: 6/12/19

DOIs:

10.1016/j.fuel.2017.11.152

URLs:

<http://urn.fi/URN:NBN:fi:tty-201712222489>. Embargo ended: 6/12/19

Research output: Contribution to journal › Article › Scientific › peer-review

Analysis of the damping characteristics of two power electronics-based devices using 'individual channel analysis and design'

A comparison of the capabilities of two quite distinct power electronics-based 'flexible AC transmission systems' devices is presented. In particular, the damping of low frequency electromechanical oscillations is investigated aiming at improving the performance of power systems. The comparison is made using frequency domain methods under the 'individual channel analysis and design' framework. A synchronous generator feeding into a system with large inertia is used for such a purpose. Two system configurations including compensation are analysed: (a) in series in the form of a thyristor-controlled series compensator, and (b) in shunt through a static VAR compensator featuring a damping controller. Analyses are carried out to elucidate the dynamic behaviour of the synchronous generator in the presence of the power electronics-based controllers and for the case when no controller is present. Performance and robustness assessments are given particular emphasis. The crux of the matter is the comparison between the abilities of the static VAR compensator and the thyristor-controlled series compensator to eliminate the problematic switch-back characteristic intrinsic to synchronous generator operation by using the physical insight afforded by 'individual channel analysis and design'.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Electrical Energy Engineering, Research group: Power systems, Cardiff University, Monterrey

Contributors: Ugalde-Loo, C. E., Acha, E., Licéaga-Castro, E.

Number of pages: 19

Pages: 527-545

Publication date: 1 Jul 2018

Peer-reviewed: Yes

Publication information

Journal: Applied Mathematical Modelling

Volume: 59

ISSN (Print): 0307-904X

Ratings:

Scopus rating (2018): CiteScore 5.3 SJR 0.873 SNIP 1.544

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Applied Mathematics

Keywords: Flexible AC transmission systems, Frequency domain analysis, Individual channel analysis and design, Multivariable control, Static VAR compensator, Thyristor-controlled series compensator

Electronic versions:

1-s2.0-S0307904X18300787-main

DOIs:

10.1016/j.apm.2018.02.008

URLs:

<http://urn.fi/URN:NBN:fi:tty-201804111480>

Source: Scopus

Source ID: 85044623804

Research output: Contribution to journal > Article > Scientific > peer-review

A prospect for computing in porous materials research: Very large fluid flow simulations

Properties of porous materials, abundant both in nature and industry, have broad influences on societies via, e.g. oil recovery, erosion, and propagation of pollutants. The internal structure of many porous materials involves multiple scales which hinders research on the relation between structure and transport properties: typically laboratory experiments cannot distinguish contributions from individual scales while computer simulations cannot capture multiple scales due to limited capabilities. Thus the question arises how large domain sizes can in fact be simulated with modern computers. This question is here addressed using a realistic test case; it is demonstrated that current computing capabilities allow the direct pore-scale simulation of fluid flow in porous materials using system sizes far beyond what has been previously reported. The achieved system sizes allow the closing of some particular scale gaps in, e.g. soil and petroleum rock research. Specifically, a full steady-state fluid flow simulation in a porous material, represented with an unprecedented resolution for the given sample size, is reported: the simulation is executed on a CPU-based supercomputer and the 3D geometry involves $16,384^3$ lattice cells (around 590 billion of them are pore sites). Using half of this sample in a benchmark simulation on a GPU-based system, a sustained computational performance of 1.77 PFLOPS is observed. These advances expose new opportunities in porous materials research. The implementation techniques here utilized are standard except for the tailored high-performance data layouts as well as the indirect addressing scheme with a low memory overhead and the truly asynchronous data communication scheme in the case of CPU and GPU code versions, respectively.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Physics, University of Jyväskylä, Natural Resources Institute Finland (Luke),

CENPES, Abo Akademi University

Contributors: Mattila, K., Puurtinen, T., Hyväluoma, J., Surmas, R., Myllys, M., Turpeinen, T., Robertsén, F., Westerholm, J., Timonen, J.

Number of pages: 15

Pages: 62-76

Publication date: 1 Jan 2016

Peer-reviewed: Yes

Publication information

Journal: Journal of Computational Science

Volume: 12

ISSN (Print): 1877-7503

Ratings:

Scopus rating (2016): CiteScore 3.4 SJR 0.476 SNIP 1.356

Original language: English

ASJC Scopus subject areas: Computer Science(all), Modelling and Simulation, Theoretical Computer Science

Keywords: Fluid flow simulation, GPU, Lattice Boltzmann method, Permeability, Petascale computing, Porous material
DOIs:

10.1016/j.jocs.2015.11.013

Bibliographical note

INT=fys,"Mattila, Keijo"

Source: Scopus

Source ID: 84954140861

Research output: Contribution to journal › Article › Scientific › peer-review

Assessment of mutation probabilities of KRAS G12 missense mutants and their long-timescale dynamics by atomistic molecular simulations and Markov state modeling

A mutated KRAS protein is frequently observed in human cancers. Traditionally, the oncogenic properties of KRAS missense mutants at position 12 (G12X) have been considered as equal. Here, by assessing the probabilities of occurrence of all KRAS G12X mutations and KRAS dynamics we show that this assumption does not hold true. Instead, our findings revealed an outstanding mutational bias. We conducted a thorough mutational analysis of KRAS G12X mutations and assessed to what extent the observed mutation frequencies follow a random distribution. Unique tissue-specific frequencies are displayed with specific mutations, especially with G12R, which cannot be explained by random probabilities. To clarify the underlying causes for the nonrandom probabilities, we conducted extensive atomistic molecular dynamics simulations (170 μ s) to study the differences of G12X mutations on a molecular level. The simulations revealed an allosteric hydrophobic signaling network in KRAS, and that protein dynamics is altered among the G12X mutants and as such differs from the wild-type and is mutation-specific. The shift in long-timescale conformational dynamics was confirmed with Markov state modeling. A G12X mutation was found to modify KRAS dynamics in an allosteric way, which is especially manifested in the switch regions that are responsible for the effector protein binding. The findings provide a basis to understand better the oncogenic properties of KRAS G12X mutants and the consequences of the observed nonrandom frequencies of specific G12X mutations.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Physics, Research group: Biological Physics and Soft Matter, University of Eastern Finland, University Hospital Tuebingen, Eberhard-Karls University Tuebingen, University of Helsinki, MEMPHYS-Center for Biomembrane Physics

Contributors: Pantsar, T., Rissanen, S., Dauch, D., Laitinen, T., Vattulainen, I., Poso, A.

Publication date: 10 Sep 2018

Peer-reviewed: Yes

Publication information

Journal: PLoS Computational Biology

Volume: 14

Issue number: 9

Article number: e1006458

ISSN (Print): 1553-734X

Ratings:

Scopus rating (2018): CiteScore 7.2 SJR 2.949 SNIP 1.408

Original language: English

ASJC Scopus subject areas: Ecology, Evolution, Behavior and Systematics, Modelling and Simulation, Ecology, Molecular Biology, Genetics, Cellular and Molecular Neuroscience, Computational Theory and Mathematics

Electronic versions:

journal.pcbi.1006458-1

DOIs:

10.1371/journal.pcbi.1006458

URLs:

<http://urn.fi/URN:NBN:fi:tty-201811012526>

Source: Scopus

Source ID: 85054571349

Research output: Contribution to journal › Article › Scientific › peer-review

Atomistic fingerprint of hyaluronan-CD44 binding

Hyaluronan is a polyanionic, megadalton-scale polysaccharide, which initiates cell signaling by interacting with several receptor proteins including CD44 involved in cell-cell interactions and cell adhesion. Previous studies of the CD44

hyaluronan binding domain have identified multiple widespread residues to be responsible for its recognition capacity. In contrast, the X-ray structural characterization of CD44 has revealed a single binding mode associated with interactions that involve just a fraction of these residues. In this study, we show through atomistic molecular dynamics simulations that hyaluronan can bind CD44 with three topographically different binding modes that in unison define an interaction fingerprint, thus providing a plausible explanation for the disagreement between the earlier studies. Our results confirm that the known crystallographic mode is the strongest of the three binding modes. The other two modes represent metastable configurations that are readily available in the initial stages of the binding, and they are also the most frequently observed modes in our unbiased simulations. We further discuss how CD44, fostered by the weaker binding modes, diffuses along HA when attached. This 1D diffusion combined with the constrained relative orientation of the diffusing proteins is likely to influence the aggregation kinetics of CD44. Importantly, CD44 aggregation has been suggested to be a possible mechanism in CD44-mediated signaling.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Physics, Research group: Biological Physics and Soft Matter, University of Helsinki, MEMPHYS - Centre for Biomembrane Physics, University of Southern Denmark, Institute of Organic Chemistry and Biochemistry, Academy of Sciences of the Czech Republic

Contributors: Vuorio, J., Vattulainen, I., Martinez-Seara, H.

Publication date: 1 Jul 2017

Peer-reviewed: Yes

Publication information

Journal: PLoS Computational Biology

Volume: 13

Issue number: 7

Article number: e1005663

ISSN (Print): 1553-734X

Ratings:

Scopus rating (2017): CiteScore 7.8 SJR 3.097 SNIP 1.374

Original language: English

ASJC Scopus subject areas: Ecology, Evolution, Behavior and Systematics, Modelling and Simulation, Ecology, Molecular Biology, Genetics, Cellular and Molecular Neuroscience, Computational Theory and Mathematics

Electronic versions:

Atomistic fingerprint of hyaluronan±CD44

DOIs:

[10.1371/journal.pcbi.1005663](https://doi.org/10.1371/journal.pcbi.1005663)

URLs:

<http://urn.fi/URN:NBN:fi:tty-201708291838>

Source: Scopus

Source ID: 85026671290

Research output: Contribution to journal › Article › Scientific › peer-review

Automatic hierarchical discovery of quasi-static schedules of RVC-CAL dataflow programs

RVC-CAL is an actor-based dataflow language that enables concurrent, modular and portable description of signal processing algorithms. RVC-CAL programs can be compiled to implementation languages such as C/C++ and VHDL for producing software or hardware implementations. This paper presents a methodology for automatic discovery of piecewise-deterministic (quasi-static) execution schedules for RVC-CAL program software implementations. Quasi-static scheduling moves computational burden from the implementable run-time system to design-time compilation and thus enables making signal processing systems more efficient. The presented methodology divides the RVC-CAL program into segments and hierarchically detects quasi-static behavior from each segment: first at the level of actors and later at the level of the whole segment. Finally, a code generator creates a quasi-statically scheduled version of the program. The impact of segment based quasi-static scheduling is demonstrated by applying the methodology to several RVC-CAL programs that execute up to 58 % faster after applying the presented methodology.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), Dept. of Computer Science and Engineering, Univ of Oulu, UBL

Contributors: Boutellier, J., Raulet, M., Silvén, O.

Number of pages: 6

Pages: 35-40

Publication date: 2013

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 71

Issue number: 1

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2013): CiteScore 2.1 SJR 0.254 SNIP 0.866

Original language: English

ASJC Scopus subject areas: Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science, Control and Systems Engineering, Modelling and Simulation

Keywords: Dataflow analysis, Scheduling, Signal processing

DOIs:

10.1007/s11265-012-0676-4

URLs:

<http://www.scopus.com/inward/record.url?scp=84873689972&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84873689972

Research output: Contribution to journal > Article > Scientific > peer-review

Automatic word count estimation from daylong child-centered recordings in various language environments using language-independent syllabification of speech

Automatic word count estimation (WCE) from audio recordings can be used to quantify the amount of verbal communication in a recording environment. One key application of WCE is to measure language input heard by infants and toddlers in their natural environments, as captured by daylong recordings from microphones worn by the infants. Although WCE is nearly trivial for high-quality signals in high-resource languages, daylong recordings are substantially more challenging due to the unconstrained acoustic environments and the presence of near- and far-field speech. Moreover, many use cases of interest involve languages for which reliable ASR systems or even well-defined lexicons are not available. A good WCE system should also perform similarly for low- and high-resource languages in order to enable unbiased comparisons across different cultures and environments. Unfortunately, the current state-of-the-art solution, the LENA system, is based on proprietary software and has only been optimized for American English, limiting its applicability. In this paper, we build on existing work on WCE and present the steps we have taken towards a freely available system for WCE that can be adapted to different languages or dialects with a limited amount of orthographically transcribed speech data. Our system is based on language-independent syllabification of speech, followed by a language-dependent mapping from syllable counts (and a number of other acoustic features) to the corresponding word count estimates. We evaluate our system on samples from daylong infant recordings from six different corpora consisting of several languages and socioeconomic environments, all manually annotated with the same protocol to allow direct comparison. We compare a number of alternative techniques for the two key components in our system: speech activity detection and automatic syllabification of speech. As a result, we show that our system can reach relatively consistent WCE accuracy across multiple corpora and languages (with some limitations). In addition, the system outperforms LENA on three of the four corpora consisting of different varieties of English. We also demonstrate how an automatic neural network-based syllabifier, when trained on multiple languages, generalizes well to novel languages beyond the training data, outperforming two previously proposed unsupervised syllabifiers as a feature extractor for WCE.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Computing Sciences, Aalto University, Laboratoire de Sciences Cognitives et Psycholinguistique, Carnegie Mellon University, University of Manitoba, Max Planck Institute for Psycholinguistics, CONICET, Duke University

Contributors: Räsänen, O., Seshadri, S., Karadayi, J., Riebling, E., Bunce, J., Cristia, A., Metze, F., Casillas, M., Rosemberg, C., Bergelson, E., Soderstrom, M.

Number of pages: 18

Pages: 63-80

Publication date: 1 Oct 2019

Peer-reviewed: Yes

Publication information

Journal: Speech Communication

Volume: 113

ISSN (Print): 0167-6393

Ratings:

Scopus rating (2019): CiteScore 4.2 SJR 0.554 SNIP 1.297

Original language: English

ASJC Scopus subject areas: Software, Modelling and Simulation, Communication, Language and Linguistics, Linguistics and Language, Computer Vision and Pattern Recognition, Computer Science Applications

Keywords: Automatic syllabification, Daylong recordings, Language acquisition, Noise robustness, Word count estimation

Electronic versions:

1-s2.0-S0167639318304205-main

DOIs:

10.1016/j.specom.2019.08.005

URLs:

<http://urn.fi/URN:NBN:fi:tuni-201909173346>

Source: Scopus

Source ID: 85070952723

Research output: Contribution to journal > Article > Scientific > peer-review

Comb Model with Slow and Ultraslow Diffusion

We consider a generalized diffusion equation in two dimensions for modeling diffusion on a comb-like structures. We analyze the probability distribution functions and we derive the mean squared displacement in x and y directions. Different forms of the memory kernels (Dirac delta, power-law, and distributed order) are considered. It is shown that anomalous diffusion may occur along both x and y directions. Ultraslow diffusion and some more general diffusive processes are observed as well. We give the corresponding continuous time random walk model for the considered two dimensional diffusion-like equation on a comb, and we derive the probability distribution functions which subordinate the process governed by this equation to the Wiener process.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Radiation Safety Directorate, Department of Physics, Max-Planck Institute for the Physics of Complex Systems, Institute for Physics and Astronomy, Universitat Potsdam, Universita degli Studi di Padova, Italy

Contributors: Sandev, T., Iomin, A., Kantz, H., Metzler, R., Checkin, A.

Number of pages: 16

Pages: 18-33

Publication date: 2016

Peer-reviewed: Yes

Publication information

Journal: Mathematical Modelling of Natural Phenomena

Volume: 11

Issue number: 3

ISSN (Print): 0973-5348

Ratings:

Scopus rating (2016): CiteScore 2.2 SJR 0.491 SNIP 0.685

Original language: English

ASJC Scopus subject areas: Modelling and Simulation

Keywords: Anomalous diffusion, Comb-like model, Mean squared displacement, Probability density function

DOIs:

10.1051/mmnp/201611302

Source: Scopus

Source ID: 84975677673

Research output: Contribution to journal > Article > Scientific > peer-review

Concerted regulation of npc2 binding to endosomal/lysosomal membranes by bis(monoacylglycero)phosphate and sphingomyelin

Niemann-Pick Protein C2 (npc2) is a small soluble protein critical for cholesterol transport within and from the lysosome and the late endosome. Intriguingly, npc2-mediated cholesterol transport has been shown to be modulated by lipids, yet the molecular mechanism of npc2-membrane interactions has remained elusive. Here, based on an extensive set of atomistic simulations and free energy calculations, we clarify the mechanism and energetics of npc2-membrane binding and characterize the roles of physiologically relevant key lipids associated with the binding process. Our results capture in atomistic detail two competitively favorable membrane binding orientations of npc2 with a low interconversion barrier. The first binding mode (Prone) places the cholesterol binding pocket in direct contact with the membrane and is characterized by membrane insertion of a loop (V59-M60-G61-I62-P63-V64-P65). This mode is associated with cholesterol uptake and release. On the other hand, the second mode (Supine) places the cholesterol binding pocket away from the membrane surface, but has overall higher membrane binding affinity. We determined that bis(monoacylglycero)phosphate (bmp) is specifically required for strong membrane binding in Prone mode, and that it cannot be substituted by other anionic lipids. Meanwhile, sphingomyelin counteracts bmp by hindering Prone mode without affecting Supine mode. Our results provide concrete evidence that lipids modulate npc2-mediated cholesterol transport either by favoring or disfavoring Prone mode and that they impose this by modulating the accessibility of bmp for interacting with npc2. Overall, we provide a mechanism by which npc2-mediated cholesterol transport is controlled by the membrane composition and how npc2-lipid interactions can regulate the transport rate.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Physics, Research group: Biological Physics and Soft Matter, University of Helsinki, FIN-00014 University of Helsinki, Minerva Foundation Institute for Medical Research Helsinki, Memphys—Center for Biomembrane Physics, Laboratory of Physics

Contributors: Enkavi, G., Mikkolainen, H., Gngr, B., Ikonen, E., Vattulainen, I.

Publication date: 1 Oct 2017

Peer-reviewed: Yes

Publication information

Journal: PLoS Computational Biology

Volume: 13

Issue number: 10

Article number: e1005831

ISSN (Print): 1553-734X

Ratings:

Scopus rating (2017): CiteScore 7.8 SJR 3.097 SNIP 1.374

Original language: English

ASJC Scopus subject areas: Ecology, Evolution, Behavior and Systematics, Modelling and Simulation, Ecology, Molecular Biology, Genetics, Cellular and Molecular Neuroscience, Computational Theory and Mathematics

Electronic versions:

full text

DOIs:

10.1371/journal.pcbi.1005831

URLs:

<http://urn.fi/URN:NBN:fi:tty-201711202175>

Bibliographical note

INT=fys,"Mikkolainen, Heikki"

Source: Scopus

Source ID: 85032730334

Research output: Contribution to journal > Article > Scientific > peer-review

Conformational properties of complex polymers: Rosette versus star-like structures

Multiple loop formation in polymer macromolecules is an important feature of the chromatin organization and DNA compactification in the nuclei. We analyse the size and shape characteristics of complex polymer structures, containing in general f_1 loops (petals) and f_2 linear chains (branches). Within the frames of continuous model of Gaussian macromolecule, we apply the path integration method and obtain the estimates for gyration radius R_g and asphericity A of typical conformation as functions of parameters f_1 , f_2 . In particular, our results qualitatively reveal the extent of anisotropy of star-like topologies as compared to the rosette structures of the same total molecular weight.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Institute for Physics and Astronomy, University of Potsdam, Institute for Condensed Matter Physics, National Academy of Sciences of Ukraine

Contributors: Blavatska, V., Metzler, R.

Publication date: 7 Apr 2015

Peer-reviewed: Yes

Publication information

Journal: Journal of Physics A: Mathematical and Theoretical

Volume: 48

Issue number: 13

Article number: 135001

ISSN (Print): 1751-8113

Ratings:

Scopus rating (2015): CiteScore 3.5 SJR 1.028 SNIP 1.04

Original language: English

ASJC Scopus subject areas: Mathematical Physics, Physics and Astronomy(all), Statistical and Nonlinear Physics, Modelling and Simulation, Statistics and Probability

Keywords: conformational properties, path integration, polymers

DOIs:

10.1088/1751-8113/48/13/135001

URLs:

<http://www.scopus.com/inward/record.url?scp=84930681628&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84930681628

Research output: Contribution to journal › Article › Scientific › peer-review

Continuum approach to high-cycle fatigue. The finite life-time case with stochastic stress history

In this paper, we consider continuum approach for high-cycle fatigue in the case where life-time is finite. The method is based on differential equations and all basic concepts are explained. A stress history is assumed to be a stochastic process and this leads us to the theory of stochastic differential equations. The life-time is a quantity, which tells us when the breakdown of the material happens. In this method, it is naturally a random variable. The basic assumption is, that the distribution of the life-time is log-normal or Weibull. We give a numerical basic example to demonstrate the method.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Computing Sciences

Contributors: Orelma, H.

Number of pages: 12

Pages: 452-463

Publication date: 2019

Peer-reviewed: Yes

Publication information

Journal: Vestnik Samarskogo Gosudarstvennogo Tekhnicheskogo Universiteta, Seriya Fiziko-Matematicheskie Nauki

Volume: 23

Issue number: 3

ISSN (Print): 1991-8615

Ratings:

Scopus rating (2019): CiteScore 0

Original language: English

ASJC Scopus subject areas: Mechanics of Materials, Condensed Matter Physics, Mathematical Physics, Modelling and Simulation, Analysis, Applied Mathematics, Software

Keywords: Evolution equation, High-cycle fatigue, Life-time

DOIs:

10.14498/vsgtu1705

Source: Scopus

Source ID: 85079143163

Research output: Contribution to journal › Article › Scientific › peer-review

Cuts for 3-D magnetic scalar potentials: Visualizing unintuitive surfaces arising from trivial knots

A wealth of literature exists on computing and visualizing cuts for the magnetic scalar potential of a current carrying conductor via Finite Element Methods (FEM) and harmonic maps to the circle. By a cut we refer to an orientable surface bounded by a given current carrying path (such that the flux through it may be computed) that restricts contour integrals on a curl-zero vector field to those that do not link the current-carrying path, analogous to branch cuts of complex analysis. This work is concerned with a study of a peculiar contour that illustrates topologically unintuitive aspects of cuts obtained from a trivial loop and raises questions about the notion of an optimal cut. Specifically, an unknotted curve that bounds only high genus surfaces in its convex hull is analyzed. The current work considers the geometric realization as a current-carrying wire in order to construct a magnetic scalar potential. Moreover, we consider the problem of choosing an energy functional on the space of maps, suggesting an algorithm for computing cuts via minimizing a conformally invariant functional utilizing Newton iteration.

General information

Publication status: Accepted/In press

MoE publication type: A1 Journal article-refereed

Organisations: Electrical Engineering, Boston University

Contributors: Stockrahm, A., Lahtinen, V., Kangas, J. J., Kotiuga, P. R.

Publication date: 2019

Peer-reviewed: Yes

Publication information

Journal: Computers and Mathematics with Applications

ISSN (Print): 0898-1221

Ratings:

Scopus rating (2019): CiteScore 4.8 SJR 1.214 SNIP 1.42

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Computational Theory and Mathematics, Computational Mathematics

Keywords: Homology, Magnetic fields, Visualization

DOIs:

10.1016/j.camwa.2019.05.023

Source: Scopus

Source ID: 85067239229

Research output: Contribution to journal › Article › Scientific › peer-review

Data augmentation approaches for improving animal audio classification

In this paper we present ensembles of classifiers for automated animal audio classification, exploiting different data augmentation techniques for training Convolutional Neural Networks (CNNs). The specific animal audio classification problems are i) birds and ii) cat sounds, whose datasets are freely available. We train five different CNNs on the original datasets and on their versions augmented by four augmentation protocols, working on the raw audio signals or their representations as spectrograms. We compared our best approaches with the state of the art, showing that we obtain the best recognition rate on the same datasets, without ad hoc parameter optimization. Our study shows that different CNNs can be trained for the purpose of animal audio classification and that their fusion works better than the stand-alone classifiers. To the best of our knowledge this is the largest study on data augmentation for CNNs in animal audio classification audio datasets using the same set of classifiers and parameters. Our MATLAB code is available at <https://github.com/LorisNanni>.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: BioMediTech, Research group: Computational Biophysics and Imaging Group, Universita degli Studi di Padova, Italy

Contributors: Nanni, L., Maguolo, G., Paci, M.

Number of pages: 8

Publication date: 2020

Peer-reviewed: Yes

Publication information

Journal: Ecological Informatics

Volume: 57

Article number: 101084

ISSN (Print): 1574-9541

Original language: English

ASJC Scopus subject areas: Ecology, Evolution, Behavior and Systematics, Ecology, Modelling and Simulation, Ecological Modelling, Computer Science Applications, Computational Theory and Mathematics, Applied Mathematics

Keywords: Acoustic features, Animal audio, Audio classification, Data augmentation, Ensemble of classifiers, Pattern recognition

DOIs:

10.1016/j.ecoinf.2020.101084

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202004163294>. Embargo ends: 19/03/22

Source: Scopus

Source ID: 85082116223

Research output: Contribution to journal › Article › Scientific › peer-review

Data Flow Algorithms for Processors with Vector Extensions: Handling Actors With Internal State

Full use of the parallel computation capabilities of present and expected CPUs and GPUs requires use of vector extensions. Yet many actors in data flow systems for digital signal processing have internal state (or, equivalently, an edge that loops from the actor back to itself) that impose serial dependencies between actor invocations that make vectorizing across actor invocations impossible. Ideally, issues of inter-thread coordination required by serial data dependencies should be handled by code written by parallel programming experts that is separate from code specifying signal processing operations. The purpose of this paper is to present one approach for so doing in the case of actors that maintain state. We propose a methodology for using the parallel scan (also known as prefix sum) pattern to create algorithms for multiple simultaneous invocations of such an actor that results in vectorizable code. Two examples of applying this methodology are given: (1) infinite impulse response filters and (2) finite state machines. The correctness and performance of the resulting IIR filters and one class of FSMs are studied.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Pervasive Computing, Research area: Computer engineering, Signal Processing Research Community (SPRC), Keysight Technologies, University of Maryland

Contributors: Barford, L., Bhattacharyya, S. S., Liu, Y.

Pages: 21-31

Publication date: 2017

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 87

Issue number: 1

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science

Keywords: Data flow computing, Digital signal processing, Graphics processing units, Parallel algorithms, Vector processors

DOIs:

10.1007/s11265-015-1045-x

Source: Scopus

Source ID: 84946115179

Research output: [Contribution to journal](#) › [Article](#) › [Scientific](#) › [peer-review](#)

Design Flow for GPU and Multicore Execution of Dynamic Dataflow Programs

Dataflow programming has received increasing attention in the age of multicore and heterogeneous computing. Modular and concurrent dataflow program descriptions enable highly automated approaches for design space exploration, optimization and deployment of applications. A great advance in dataflow programming has been the recent introduction of the RVC-CAL language. Having been standardized by the ISO, the RVC-CAL dataflow language provides a solid basis for the development of tools, design methodologies and design flows. This paper proposes a novel design flow for mapping RVC-CAL dataflow programs to parallel and heterogeneous execution platforms. Through the proposed design flow the programmer can describe an application in the RVC-CAL language and map it to multi- and many-core platforms, as well as GPUs, for efficient execution. The functionality and efficiency of the proposed approach is demonstrated by a parallel implementation of a video processing application and a run-time reconfigurable filter for telecommunications. Experiments are performed on GPU and multicore platforms with up to 16 cores, and the results show that for high-performance applications the proposed design flow provides up to 4 × higher throughput than the state-of-the-art approach in multicore execution of RVC-CAL programs.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Pervasive Computing, Research area: Computer engineering, Center for Machine Vision and Signal Analysis, Univ of Oulu

Contributors: Boutellier, J., Nyländen, T.

Number of pages: 10

Pages: 469–478

Publication date: 2017

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 89

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Dataflow computing, Design automation, Parallel processing, Signal processing

DOIs:

10.1007/s11265-017-1260-8

Source: Scopus

Source ID: 85021239311

Research output: Contribution to journal › Article › Scientific › peer-review

Development of an England-wide indoor overheating and air pollution model using artificial neural networks

With the UK climate projected to warm in future decades, there is an increased research focus on the risks of indoor overheating. Energy-efficient building adaptations may modify a buildings risk of overheating and the infiltration of air pollution from outdoor sources. This paper presents the development of a national model of indoor overheating and air pollution, capable of modelling the existing and future building stocks, along with changes to the climate, outdoor air pollution levels, and occupant behaviour. The model presented is based on a large number of EnergyPlus simulations run in parallel. A metamodeling approach is used to create a model that estimates the indoor overheating and air pollution risks for the English housing stock. The performance of neural networks (NNs) is compared to a support vector regression (SVR) algorithm when forming the metamodel. NNs are shown to give almost a 50% better overall performance than SVR.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: University College London, London School of Hygiene and Tropical Medicine, Public Health England

Contributors: Symonds, P., Taylor, J., Chalabi, Z., Mavrogianni, A., Davies, M., Hamilton, I., Vardoulakis, S., Heaviside, C., Macintyre, H.

Number of pages: 14

Pages: 606-619

Publication date: 1 Nov 2016

Peer-reviewed: Yes

Publication information

Journal: JOURNAL OF BUILDING PERFORMANCE SIMULATION

Volume: 9

Issue number: 6

ISSN (Print): 1940-1493

Ratings:

Scopus rating (2016): CiteScore 4.1 SJR 0.877 SNIP 1.399

Original language: English

ASJC Scopus subject areas: Architecture , Building and Construction, Modelling and Simulation, Computer Science Applications

Keywords: indoor air pollution, machine learning, metamodeling, neural networks, overheating, stock modelling

DOIs:

10.1080/19401493.2016.1166265

URLs:

<http://www.scopus.com/inward/record.url?scp=84963632445&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84963632445

Research output: Contribution to journal › Article › Scientific › peer-review

Digital Predistortion for 5G Small Cell: GPU Implementation and RF Measurements

In this paper, we present a high data rate implementation of a digital predistortion (DPD) algorithm on a modern mobile multicore CPU containing an on-chip GPU. The proposed implementation is capable of running in real-time, thanks to the execution of the predistortion stage inside the GPU, and the execution of the learning stage on a separate CPU core. This configuration, combined with the low complexity DPD design, allows for more than 400 Msamples/s sample rates. This is sufficient for satisfying 5G new radio (NR) base station radio transmission specifications in the sub-6 GHz bands, where signal bandwidths up to 100 MHz are specified. The linearization performance is validated with RF measurements on two base station power amplifiers at 3.7 GHz, showing that the 5G NR downlink emission requirements are satisfied.

General information

Publication status: E-pub ahead of print

MoE publication type: A1 Journal article-refereed

Organisations: Electrical Engineering, Computing Sciences, Research area: Computer engineering, Research group: Wireless Communications and Positioning, University of Vaasa (UVA), Tampere University

Contributors: Pascual Campo, P., Lampu, V., Meirhaeghe, A., Boutellier, J., Anttila, L., Valkama, M.

Number of pages: 12

Publication date: 2019

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2019): CiteScore 2.4 SJR 0.298 SNIP 0.833

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: 5G, Digital predistortion (DPD), GPU, High data rate, Real-time

Electronic versions:

PascualCampo2019_Article_DigitalPredistortionFor5GSmall

DOIs:

10.1007/s11265-019-01502-4

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202001171372>

Bibliographical note

INT=comp,"Meirhaeghe, Alexandre"

Source: Scopus

Source ID: 85077054281

Research output: [Contribution to journal](#) › [Article](#) › [Scientific](#) › [peer-review](#)

Distant speech separation using predicted time-frequency masks from spatial features

Speech separation algorithms are faced with a difficult task of producing high degree of separation without containing unwanted artifacts. The time-frequency (T-F) masking technique applies a real-valued (or binary) mask on top of the signal's spectrum to filter out unwanted components. The practical difficulty lies in the mask estimation. Often, using efficient masks engineered for separation performance leads to presence of unwanted musical noise artifacts in the separated signal. This lowers the perceptual quality and intelligibility of the output. Microphone arrays have been long studied for processing of distant speech. This work uses a feed-forward neural network for mapping microphone array's spatial features into a T-F mask. Wiener filter is used as a desired mask for training the neural network using speech examples in simulated setting. The T-F masks predicted by the neural network are combined to obtain an enhanced separation mask that exploits the information regarding interference between all sources. The final mask is applied to the delay-and-sum beamformer (DSB) output. The algorithm's objective separation capability in conjunction with the separated speech intelligibility is tested with recorded speech from distant talkers in two rooms from two distances. The results show improvement in instrumental measure for intelligibility and frequency-weighted SNR over complex-valued non-negative matrix factorization (CNMF) source separation approach, spatial sound source separation, and conventional beamforming methods such as the DSB and minimum variance distortionless response (MVDR).

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Signal Processing, Research group: Audio research group

Contributors: Pertilä, P., Nikunen, J.

Number of pages: 10

Pages: 97-106

Publication date: 2015

Peer-reviewed: Yes

Publication information

Journal: Speech Communication

Volume: 68

ISSN (Print): 0167-6393

Ratings:

Scopus rating (2015): CiteScore 4.1 SJR 0.49 SNIP 1.612

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Computer Science Applications, Computer Vision and Pattern Recognition, Software, Communication, Linguistics and Language, Language and Linguistics

Keywords: Beamforming, Microphone arrays, Neural networks, Speech separation, Time-frequency masking

DOIs:

10.1016/j.specom.2015.01.006

Source: Scopus

Source ID: 84923277715

Research output: [Contribution to journal](#) › [Article](#) › [Scientific](#) › [peer-review](#)

Effect of paint baking treatment on the properties of press hardened boron steels

This study comprehends the effect of a typical paint baking process on the properties of press hardened boron steels. Bake hardening response of four 22MnB5 steels with different production histories and two other boron steels of 30MnB5 and 34MnB5 type were analyzed. In particular, the effect of steel carbon content and prior austenite grain size on the strength of the bake hardening treated steels was investigated. Press hardened steels showed a relatively strong bake hardening effect, 80–160 MPa, in terms of yield strength. In addition, a clear decrease in ultimate tensile strength, 30–150 MPa, was observed due to baking. The changes in tensile strength showed a dependency on the carbon content of the steel: higher carbon content led to a larger decrease in tensile strength in general. Smaller prior austenite grain size resulted in a higher increase in yield strength despite the micro-alloyed 34MnB5. Transmission electron microscopy analysis carried out for the 34MnB5 revealed niobium rich mixture carbides of (Nb, Ti)C, which have most likely influenced the different bake hardening response. The present results indicate that the bake hardening response of press hardened steels depends on both prior austenite grain size and carbon content, but is also affected by other alloying elements. The observed correlation between prior austenite grain size and bake hardening response can be used to optimize the production of the standard grades of 22MnB5 and 30MnB5. In addition, our study suggests that baking process improves the post-uniform elongation and ductile fracture behavior of 34MnB5, but do not significantly influence the ductile fracture mechanisms of 22MnB5 and 30MnB5 representing lower strength levels.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Materials Science, Research group: Metals Technology, SSAB

Contributors: Järvinen, H., Honkanen, M., Järvenpää, M., Peura, P.

Number of pages: 15

Pages: 90-104

Publication date: 2018

Peer-reviewed: Yes

Early online date: 11 Sep 2017

Publication information

Journal: Journal of Materials Processing Technology

Volume: 252

ISSN (Print): 0924-0136

Ratings:

Scopus rating (2018): CiteScore 7.5 SJR 1.719 SNIP 2.888

Original language: English

ASJC Scopus subject areas: Ceramics and Composites, Modelling and Simulation, Computer Science Applications, Metals and Alloys, Industrial and Manufacturing Engineering

Keywords: Bake hardening, EBSD, Martensite, Paint baking, Press hardening, Prior austenite grain size

Electronic versions:

Effect of paint baking treatment 2017. Embargo ended: 11/09/19

DOIs:

10.1016/j.jmatprotec.2017.08.027

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202002182174>. Embargo ended: 11/09/19

Source: Scopus

Source ID: 85029389667

Research output: Contribution to journal › Article › Scientific › peer-review

Enhanced multiaxial fatigue criterion that considers stress gradient effects

Modification of a fatigue criterion valid for homogeneous multiaxial stress states to account for the beneficial effect of stress gradients is traditionally performed by modifying the stress terms in the fatigue criterion and thereby introducing new parameters that need to be calibrated. Here the stress terms are left unchanged and, instead, the parameters in the fatigue criterion are modified. This modification is performed, in principle, along the lines of Siebel and Stieler and it introduces Neuber's parameter as the only new parameter; however, as soon as the ultimate strength of the material is known, also Neuber's parameter is known. Therefore, the methodology introduced implies that no new calibration process is needed. Here a specific fatigue criterion valid for homogeneous multiaxial stress states is enhanced by this procedure and predictions of this simple approach are compared with a broad range of experimental data and good accuracy is achieved. Moreover, the approach adopted can be applied to other fatigue criteria than the one considered here.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Civil Engineering, Lund University

Contributors: Ottosen, N. S., Ristinmaa, M., Kouhia, R.
Number of pages: 12
Pages: 128-139
Publication date: 1 Nov 2018
Peer-reviewed: Yes

Publication information

Journal: International Journal of Fatigue

Volume: 116

ISSN (Print): 0142-1123

Ratings:

Scopus rating (2018): CiteScore 6.3 SJR 2.059 SNIP 2.486

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Materials Science(all), Mechanics of Materials, Mechanical Engineering, Industrial and Manufacturing Engineering

Keywords: Fatigue, Gradient effects, Multiaxial fatigue

DOIs:

10.1016/j.ijfatigue.2018.05.024

Source: Scopus

Source ID: 85048733879

Research output: Contribution to journal › Article › Scientific › peer-review

Entropy analysis of word-length series of natural language texts: Effects of text language and genre

We estimate the n-gram entropies of natural language texts in word-length representation and find that these are sensitive to text language and genre. We attribute this sensitivity to changes in the probability distribution of the lengths of single words and emphasize the crucial role of the uniformity of probabilities of having words with length between five and ten. Furthermore, comparison with the entropies of shuffled data reveals the impact of word length correlations on the estimated n-gram entropies.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Multi-scaled biodata analysis and modelling (MultiBAM), University of Athens, Institute of Microelectronics, Athens, Institute for Language and Speech Processing, Athena R.C.

Contributors: Kalimeri, M., Constantoudis, V., Papadimitriou, C., Karamanos, K., Diakonou, F. K., Papageorgiou, H.

Publication date: Sep 2012

Peer-reviewed: Yes

Publication information

Journal: INTERNATIONAL JOURNAL OF BIFURCATION AND CHAOS

Volume: 22

Issue number: 9

Article number: 1250223

ISSN (Print): 0218-1274

Ratings:

Scopus rating (2012): CiteScore 1.6 SJR 0.551 SNIP 0.79

Original language: English

ASJC Scopus subject areas: Applied Mathematics, General, Engineering(all), Modelling and Simulation

Keywords: N-gram entropies, Quantitative linguistics, Symbolic dynamics, Time series, Word-length representation

DOIs:

10.1142/S0218127412502239

URLs:

<http://www.scopus.com/inward/record.url?scp=84867518276&partnerID=8YFLogxK> (Link to publication in Scopus)

Bibliographical note

EXT="Kalimeri, Maria"

Source: Scopus

Source ID: 84867518276

Research output: Contribution to journal › Article › Scientific › peer-review

Exploiting statically schedulable regions in dataflow programs

Dataflow descriptions have been used in a wide range of Digital Signal Processing (DSP) applications, such as multimedia processing, and wireless communications. Among various forms of dataflow modeling, Synchronous Dataflow (SDF) is geared towards static scheduling of computational modules, which improves system performance and predictability. However, many DSP applications do not fully conform to the restrictions of SDF modeling. More general

dataflow models, such as CAL (Eker and Janneck 2003), have been developed to describe dynamically-structured DSP applications. Such generalized models can express dynamically changing functionality, but lose the powerful static scheduling capabilities provided by SDF. This paper focuses on the detection of SDF-like regions in dynamic dataflow descriptions-in particular, in the generalized specification framework of CAL. This is an important step for applying static scheduling techniques within a dynamic dataflow framework. Our techniques combine the advantages of different dataflow languages and tools, including CAL (Eker and Janneck 2003), DIF (Hsu et al. 2005) and CAL2C (Roquier et al. 2008). In addition to detecting SDF-like regions, we apply existing SDF scheduling techniques to exploit the static properties of these regions within enclosing dynamic dataflow models. Furthermore, we propose an optimized approach for mapping SDF-like regions onto parallel processing platforms such as multi-core processors.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), University of Maryland, Xilinx Research Labs, UBL, Department of Electrical and Computer Engineering

Contributors: Gu, R., Janneck, J. W., Raulet, M., Bhattacharyya, S. S.

Number of pages: 14

Pages: 129-142

Publication date: Apr 2011

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 63

Issue number: 1

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2011): CiteScore 1.8 SJR 0.248 SNIP 0.707

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Cal, Dataflow, DIF, Multicore processors, Quasi-static scheduling

DOIs:

10.1007/s11265-009-0445-1

URLs:

<http://www.scopus.com/inward/record.url?scp=79954601701&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 79954601701

Research output: Contribution to journal > Article > Scientific > peer-review

Harnessing the complexity of gene expression data from cancer: From single gene to structural pathway methods

: High-dimensional gene expression data provide a rich source of information because they capture the expression level of genes in dynamic states that reflect the biological functioning of a cell. For this reason, such data are suitable to reveal systems related properties inside a cell, e.g., in order to elucidate molecular mechanisms of complex diseases like breast or prostate cancer. However, this is not only strongly dependent on the sample size and the correlation structure of a data set, but also on the statistical hypotheses tested. Many different approaches have been developed over the years to analyze gene expression data to (I) identify changes in single genes, (II) identify changes in gene sets or pathways, and (III) identify changes in the correlation structure in pathways. In this paper, we review statistical methods for all three types of approaches, including subtypes, in the context of cancer data and provide links to software implementations and tools and address also the general problem of multiple hypotheses testing. Further, we provide recommendations for the selection of such analysis methods. Reviewers: This article was reviewed by Arcady Mushegian, Byung-Soo Kim and Joel Bader.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Prostate cancer research center (PCRC), Computational Biology and Machine Learning, Queen's University, Belfast, Northern Ireland

Contributors: Emmert-Streib, F., Tripathi, S., Matos Simoes, R. D.

Publication date: 10 Dec 2012

Peer-reviewed: Yes

Publication information

Journal: Biology Direct

Volume: 7

Article number: 44
ISSN (Print): 1745-6150
Ratings:

Scopus rating (2012): CiteScore 6.5 SJR 2.148 SNIP 0.742

Original language: English

ASJC Scopus subject areas: Agricultural and Biological Sciences(all), Biochemistry, Genetics and Molecular Biology(all), Immunology, Applied Mathematics, Modelling and Simulation, Ecology, Evolution, Behavior and Systematics

Keywords: Cancer data, Cancer genomics, Correlation structure, Gene expression data, Pathway methods, Statistical analysis methods

DOIs:

10.1186/1745-6150-7-44

URLs:

<http://www.scopus.com/inward/record.url?scp=84872650417&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84872650417

Research output: Contribution to journal > Article > Scientific > peer-review

Hermitian one-particle density matrix through a semiclassical gradient expansion

We carry out the semiclassical expansion of the one-particle density matrix up to the second order in \hbar . We use the method of Grammaticos and Voros based on the Wigner transform of operators. We show that the resulting density matrix is Hermitian and idempotent in contrast with the well-known result of the semiclassical Kirzhnits expansion. Our density matrix leads to the same particle density and kinetic energy density as in the literature, and it satisfies the consistency criterion of the Euler equation. The derived Hermitian density matrix clarifies the ambiguity in the usefulness of gradient expansion approximations and might reignite the development of density functionals with semiclassical methods.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Research group: Quantum Control and Dynamics, Research area: Computational Physics, Computational Science X (CompX), Université Ferhat

Contributors: Bencheikh, K., Räsänen, E.

Publication date: 9 Dec 2015

Peer-reviewed: Yes

Publication information

Journal: Journal of Physics A: Mathematical and Theoretical

Volume: 49

Issue number: 1

Article number: 015205

ISSN (Print): 1751-8113

Ratings:

Scopus rating (2015): CiteScore 3.5 SJR 1.028 SNIP 1.04

Original language: English

ASJC Scopus subject areas: Mathematical Physics, Physics and Astronomy(all), Statistical and Nonlinear Physics, Modelling and Simulation, Statistics and Probability

Keywords: density matrix, density-functional theory, Wigner transform

DOIs:

10.1088/1751-8113/49/1/015205

Source: Scopus

Source ID: 84961361098

Research output: Contribution to journal > Article > Scientific > peer-review

Hierarchical coordination of periodic genes in the cell cycle of *Saccharomyces cerevisiae*

Background: Gene networks are a representation of molecular interactions among genes or products thereof and, hence, are forming causal networks. Despite intense studies during the last years most investigations focus so far on inferential methods to reconstruct gene networks from experimental data or on their structural properties, e.g., degree distributions. Their structural analysis to gain functional insights into organizational principles of, e.g., pathways remains so far under appreciated. Results: In the present paper we analyze cell cycle regulated genes in *S. cerevisiae*. Our analysis is based on the transcriptional regulatory network, representing causal interactions and not just associations or correlations between genes, and a list of known periodic genes. No further data are used. Partitioning the transcriptional regulatory network according to a graph theoretical property leads to a hierarchy in the network and, hence, in the information flow allowing to identify two groups of periodic genes. This reveals a novel conceptual interpretation of the working mechanism of the cell cycle and the genes regulated by this pathway. Conclusion: Aside from the obtained results for the cell cycle of yeast our approach could be exemplary for the analysis of general pathways by exploiting the rich causal structure of inferred and/or curated gene networks including protein or signaling networks.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences, Queen's University, Belfast, Northern Ireland, Institute for Bioinformatics and Translational Research

Contributors: Emmert-Streib, F., Dehmer, M.

Publication date: 20 Jul 2009

Peer-reviewed: Yes

Publication information

Journal: BMC Systems Biology

Volume: 3

Article number: 76

ISSN (Print): 1752-0509

Ratings:

Scopus rating (2009): SJR 1.493 SNIP 0.974

Original language: English

ASJC Scopus subject areas: Molecular Biology, Structural Biology, Applied Mathematics, Modelling and Simulation, Computer Science Applications

DOIs:

10.1186/1752-0509-3-76

URLs:

<http://www.scopus.com/inward/record.url?scp=68949220295&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 68949220295

Research output: Contribution to journal > Article > Scientific > peer-review

Hysteresis and eddy-current losses in electrical steel utilising edge degradation due to cutting effects

Cutting of electrical steel sheets typically deteriorates the permeability and increases the iron loss close to the cutting edges. We estimated iron losses in the cross-section of electrical steel sheets by numerically solving the 1-D and 2-D eddy-current distributions while accounting for static magnetic behaviour with a hysteresis model. The magnetization curves in the cross-section are defined using a continuous local material model, making them dependent on the distance from the cut edge by a degradation profile. Damaged and undamaged hysteresis loops were identified by measurements of different wide strips of M400-50A steel sheets. The eddy-current distributions were solved when the strips of different widths were excited with sinusoidal average flux densities at different frequencies. It was found that the cutting degradation also affects the eddy-current loss particularly around 1.0 T. The exact shape of the degradation profile was found to be less significant while the increase of excess losses is significant for the overall loss estimation.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Electrical Engineering, Research group: Electromechanics, Research area: Power engineering, DENSO AUTOMOTIVE Deutschland GmbH, RWTH Aachen University

Contributors: Elfgen, S., Rasilo, P., Hameyer, K.

Number of pages: 10

Publication date: 2020

Peer-reviewed: Yes

Publication information

Journal: International Journal of Numerical Modelling: Electronic Networks, Devices and Fields

ISSN (Print): 0894-3370

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Computer Science Applications, Electrical and Electronic Engineering

Keywords: cut edges, edge degradation, hysteresis model, iron losses, thin sheet model

DOIs:

10.1002/jnm.2781

Source: Scopus

Source ID: 85088045733

Research output: Contribution to journal > Article > Scientific > peer-review

IEEE 802.11ac MIMO Transceiver Baseband Processing on a VLIW Processor

Wireless standards are evolving rapidly due to the exponential growth in the number of portable devices along with the applications with high data rate requirements. Adaptable software based signal processing implementations for these devices can make the deployment of the constantly evolving standards faster and less expensive. The flagship technology

from the IEEE WLAN family, the IEEE 802.11ac, aims at achieving very high throughputs in local area connectivity scenarios. This article presents a software based implementation for the Multiple Input and Multiple Output (MIMO) transmitter and receiver baseband processing conforming to the IEEE 802.11ac standard which can achieve transmission bit rates beyond 1Gbps. This work focuses on the Physical layer frequency domain processing. Various configurations, including 2x2 and 4x4 MIMO are considered for the implementation. To utilize the available data and instruction level parallelism, a DSP core with vector extensions is selected as the implementation platform. Then, the feasibility of the presented software-based solution is assessed by studying the number of clock cycles and power consumption of the different scenarios implemented on this core. Such Software Defined Radio based approaches can potentially offer more flexibility, high energy efficiency, reduced design efforts and thus shorter time-to-market cycles in comparison with the conventional fixed-function hardware methods.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Electronics and Communications Engineering, Research group: Wireless Communications and Positioning, Department of Pervasive Computing, Research area: Computer engineering

Contributors: Aghababaeetafreshi, M., Lehtonen, L. K., Levanen, T., Valkama, M., Takala, J.

Publication date: 2016

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2016): CiteScore 1.6 SJR 0.212 SNIP 0.677

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science

Keywords: MIMO, OFDM, Parallel processing, Software defined radio, VLIW, WLAN

DOIs:

10.1007/s11265-015-1032-2

URLs:

<http://www.scopus.com/inward/record.url?scp=84942023616&partnerID=8YFLogxK> (Link to publication in Scopus)

Bibliographical note

ORG=elt,0.5

ORG=tie,0.5

Source: Scopus

Source ID: 84942023616

Research output: Contribution to journal > Article > Scientific > peer-review

Implementation of a direct procedure for critical point computations using preconditioned iterative solvers

Computation of critical points on an equilibrium path requires the solution of a non-linear eigenvalue problem. These critical points could be either bifurcation or limit points. When the external load is parametrized by a single parameter, the non-linear stability eigenvalue problem consists of solving the equilibrium equations along the criticality condition. Several techniques exist for solution of such a system. Their algorithmic treatment is usually focused for direct linear solvers and thus use the block elimination strategy. In this paper special emphasis is given for a strategy which can be used also with iterative linear solvers. Comparison to the block elimination strategy with direct linear solvers is given. Due to the non-uniqueness of the critical eigenmode a normalizing condition is required. In addition, for bifurcation points, the Jacobian matrix of the augmented system is singular at the critical point and additional stabilization is required in order to maintain the quadratic convergence of the Newton's method. Depending on the normalizing condition, convergence to a critical point with negative load parameter value can happen. The form of the normalizing equation is critically discussed. Due to the slenderness of the buckling sensitive structures the resulting matrices are ill-conditioned and a good preconditioner is mandatory for efficient solution. © 2012 Civil-Comp Ltd. and Elsevier Ltd. All rights reserved.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Mechanics and Design, Department of Civil Engineering, Life Cycle Effectiveness of the Built Environment (LCE@BE), Academy of Sciences of the Czech Republic, Institute of Computer Science of the Academy of Sciences of the Czech Republic, Department of Civil and Structural Engineering, Aalto University

Contributors: Kouhia, R., Tůma, M., Mäkinen, J., Fedoroff, A., Marjamäki, H.

Number of pages: 8

Pages: 110-117

Publication date: Oct 2012

Peer-reviewed: Yes

Publication information

Journal: Computers & Structures

Volume: 108-109

ISSN (Print): 0045-7949

Ratings:

Scopus rating (2012): CiteScore 3.8 SJR 1.354 SNIP 2.226

Original language: English

ASJC Scopus subject areas: Computer Science Applications, Civil and Structural Engineering, Mechanical Engineering, Modelling and Simulation, Materials Science(all)

Keywords: Critical points, Equilibrium equations, Non-linear eigenvalue problem, Preconditioned iterations

DOIs:

10.1016/j.compstruc.2012.02.009

URLs:

<http://www.scopus.com/inward/record.url?scp=84865782578&partnerID=8YFLogxK> (Link to publication in Scopus)

Bibliographical note

/kir12
Contribution: organisation=mec,FACT1=1
Publisher name: Elsevier

Source: researchoutputwizard

Source ID: 4554

Research output: Contribution to journal > Article > Scientific > peer-review

Implementation of a Multirate Resampler for Multi-carrier Systems on GPUs

Efficient sample rate conversion is of widespread importance in modern communication and signal processing systems. Although many efficient kinds of polyphase filterbank structures exist for this purpose, they are mainly geared toward serial, custom, dedicated hardware implementation for a single task. There is, therefore, a need for more flexible sample rate conversion systems that are resource-efficient, and provide high performance. To address these challenges, we present in this paper an all-software-based, fully parallel, multirate resampling method based on graphics processing units (GPUs). The proposed approach is well-suited for wireless communication systems that have simultaneous requirements on high throughput and low latency. Utilizing the multidimensional architecture of GPUs, our design allows efficient parallel processing across multiple channels and frequency bands at baseband. The resulting architecture provides flexible sample rate conversion that is designed to address modern communication requirements, including real-time processing of multiple carriers simultaneously.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Pervasive Computing, University of Maryland

Contributors: Kim, S. C., Bhattacharyya, S. S.

Number of pages: 11

Pages: 445-455

Publication date: 2017

Peer-reviewed: Yes

Early online date: 30 Mar 2017

Publication information

Journal: Journal of Signal Processing Systems

Volume: 89

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Carrier aggregation, GPU-based radio, Multirate signal processing, Polyphase decimator, Polyphase interpolator, Polyphase resampler

DOIs:

10.1007/s11265-017-1239-5

Source: Scopus

Source ID: 85016560476

Research output: Contribution to journal > Article > Scientific > peer-review

Inferring the conservative causal core of gene regulatory networks

Background: Inferring gene regulatory networks from large-scale expression data is an important problem that received much attention in recent years. These networks have the potential to gain insights into causal molecular interactions of biological processes. Hence, from a methodological point of view, reliable estimation methods based on observational data are needed to approach this problem practically. **Results:** In this paper, we introduce a novel gene regulatory network inference (GRNI) algorithm, called C3NET. We compare C3NET with four well known methods, ARACNE, CLR, MRNET and RN, conducting in-depth numerical ensemble simulations and demonstrate also for biological expression data from *E. coli* that C3NET performs consistently better than the best known GRNI methods in the literature. In addition, it has also a low computational complexity. Since C3NET is based on estimates of mutual information values in conjunction with a maximization step, our numerical investigations demonstrate that our inference algorithm exploits causal structural information in the data efficiently. **Conclusions:** For systems biology to succeed in the long run, it is of crucial importance to establish methods that extract large-scale gene networks from high-throughput data that reflect the underlying causal interactions among genes or gene products. Our method can contribute to this endeavor by demonstrating that an inference algorithm with a neat design permits not only a more intuitive and possibly biological interpretation of its working mechanism but can also result in superior results.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Queen's University, Belfast, Northern Ireland, Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences

Contributors: Altay, G., Emmert-Streib, F.

Publication date: 28 Sep 2010

Peer-reviewed: Yes

Publication information

Journal: BMC Systems Biology

Volume: 4

Article number: 132

ISSN (Print): 1752-0509

Ratings:

Scopus rating (2010): SJR 1.832 SNIP 1.057

Original language: English

ASJC Scopus subject areas: Molecular Biology, Structural Biology, Applied Mathematics, Modelling and Simulation, Computer Science Applications

DOIs:

10.1186/1752-0509-4-132

URLs:

<http://www.scopus.com/inward/record.url?scp=77957141016&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 77957141016

Research output: Contribution to journal › Article › Scientific › peer-review

Influence of relative humidity and physical load during storage on dustiness of inorganic nanomaterials: implications for testing and risk assessment

Dustiness testing using a down-scaled EN15051 rotating drum was used to investigate the effects of storage conditions such as relative humidity and physical loading on the dustiness of five inorganic metal oxide nanostructured powder materials. The tests consisted of measurements of gravimetric respirable dustiness index and particle size distributions. Water uptake of the powders during 7 days of incubation was investigated as an explanatory factor of the changes. Consequences of these varying storage conditions in exposure modelling were tested using the control banding and risk management tool NanoSafer. Drastic material-specific effects on powder respirable dustiness index were observed with the change in TiO₂ from 30 % RH (639 mg/kg) to 50 % RH (1.5 mg/kg). All five tested materials indicate a decreasing dustiness index with relative humidity increasing from 30 to 70 % RH. Test of powder water uptake showed an apparent link with the decreasing dustiness index. Effects of powder compaction appeared more material specific with both increasing and decreasing dustiness indices observed as an effect of compaction. Tests of control banding exposure models using the measured dustiness indices in three different exposure scenarios showed that in two of the tested materials, one 20 % change in RH changed the exposure banding from the lowest level to the highest. The study shows the importance of powder storage conditions prior to tests for classification of material dustiness indices. It also highlights the importance of correct storage information and relative humidity and expansion of the dustiness test conditions specifically, when using dustiness indices as a primary parameter for source strength in exposure assessment.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Materials Science, Research group: Materials Characterization, Engineering materials science and solutions (EMASS), Department of Micro and Nanotechnology, Denmark Technical University DTU, Finnish Institute of Occupational Health, CIC biomaGUNE, National Research Centre for the Working Environment

Contributors: Levin, M., Rojas, E., Vanhala, E., Vippola, M., Liguori, B., Kling, K. I., Koponen, I. K., Mølhave, K., Tuomi, T., Gregurec, D., Moya, S., Jensen, K. A.

Publication date: 14 Aug 2015

Peer-reviewed: Yes

Publication information

Journal: Journal of Nanoparticle Research

Volume: 17

Issue number: 8

Article number: 337

ISSN (Print): 1388-0764

Ratings:

Scopus rating (2015): CiteScore 3.8 SJR 0.568 SNIP 0.725

Original language: English

ASJC Scopus subject areas: Atomic and Molecular Physics, and Optics, Condensed Matter Physics, Modelling and Simulation, Chemistry(all), Materials Science(all), Bioengineering

Keywords: Dustiness, Exposure assessment, Nanotechnology, Occupational health, Powder storage, Rotating drum

DOIs:

10.1007/s11051-015-3139-6

URLs:

<http://www.scopus.com/inward/record.url?scp=84939162642&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84939162642

Research output: Contribution to journal › Article › Scientific › peer-review

Influence of specimen type and reinforcement on measured tension-tension fatigue life of unidirectional GFRP laminates

It is well known that standardised tension-tension fatigue test specimens of unidirectional (UD) glass-fibre-reinforced plastics (GFRP) laminates tend to fail at end tabs. The true fatigue life is then underestimated. The first objective of this study was to find for UD GFRP laminates a test specimen that fails in the gauge section. The second objective was to compare fatigue performance of two laminates, one having a newly developed UD powder-bound fabric as a reinforcement and the other having a quasi-UD stitched non-crimp fabric as a reinforcement. In the first phase, a rectangular specimen in accordance with the ISO 527-5 standard and two slightly different dog-bone shaped specimens were evaluated by means of finite element modelling. Subsequent comparative fatigue tests were performed for the laminates with the three specimen types. The results showed that the test specimen type has a significant effect on the failure mode and measured fatigue life of the laminates. A significantly higher fatigue life was measured for the laminate with the powder-bound fabric reinforcement when compared to the laminate with the stitched reinforcement.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Materials Science, Research group: Plastics and Elastomer Technology, Aalto University, Risø Campus

Contributors: Korhikoski, S., Brøndsted, P., Sarlin, E., Saarela, O.

Number of pages: 16

Pages: 114-129

Publication date: 1 Apr 2016

Peer-reviewed: Yes

Publication information

Journal: International Journal of Fatigue

Volume: 85

ISSN (Print): 0142-1123

Ratings:

Scopus rating (2016): CiteScore 4.9 SJR 1.648 SNIP 2.612

Original language: English

ASJC Scopus subject areas: Industrial and Manufacturing Engineering, Mechanical Engineering, Mechanics of Materials, Materials Science(all), Modelling and Simulation

Keywords: Fatigue test methods, Polymer matrix composites, S-N curves, Specimen design, Unidirectional laminate

DOIs:

10.1016/j.ijfatigue.2015.12.008

Source: Scopus

Source ID: 84954185653

Research output: Contribution to journal › Article › Scientific › peer-review

Information processing in the transcriptional regulatory network of yeast: Functional robustness

Background: Gene networks are considered to represent various aspects of molecular biological systems meaningfully because they naturally provide a systems perspective of molecular interactions. In this respect, the functional understanding of the transcriptional regulatory network is considered as key to elucidate the functional organization of an organism. Results: In this paper we study the functional robustness of the transcriptional regulatory network of *S. cerevisiae*. We model the information processing in the network as a first order Markov chain and study the influence of single gene perturbations on the global, asymptotic communication among genes. Modification in the communication is measured by an information theoretic measure allowing to predict genes that are 'fragile' with respect to single gene knockouts. Our results demonstrate that the predicted set of fragile genes contains a statistically significant enrichment of so called essential genes that are experimentally found to be necessary to ensure vital yeast. Further, a structural analysis of the transcriptional regulatory network reveals that there are significant differences between fragile genes, hub genes and genes with a high betweenness centrality value. Conclusion: Our study does not only demonstrate that a combination of graph theoretical, information theoretical and statistical methods leads to meaningful biological results but also that such methods allow to study information processing in gene networks instead of just their structural properties.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Computational Biology and Machine Learning, Queen's University, Belfast, Northern Ireland, Center for Mathematics Probability and Statistics

Contributors: Emmert-Streib, F., Dehmer, M.

Publication date: 19 Mar 2009

Peer-reviewed: Yes

Publication information

Journal: BMC Systems Biology

Volume: 3

Article number: 35

ISSN (Print): 1752-0509

Ratings:

Scopus rating (2009): SJR 1.493 SNIP 0.974

Original language: English

ASJC Scopus subject areas: Molecular Biology, Structural Biology, Applied Mathematics, Modelling and Simulation, Computer Science Applications

DOIs:

10.1186/1752-0509-3-35

URLs:

<http://www.scopus.com/inward/record.url?scp=65649087188&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 65649087188

Research output: Contribution to journal › Article › Scientific › peer-review

Instrumentation-Driven Validation of Dataflow Applications

Dataflow modeling offers a myriad of tools for designing and optimizing signal processing systems. A designer is able to take advantage of dataflow properties to effectively tune the system in connection with functionality and different performance metrics. However, a disparity in the specification of dataflow properties and the final implementation can lead to incorrect behavior that is difficult to detect. This motivates the problem of ensuring consistency between dataflow properties that are declared or otherwise assumed as part of dataflow-based application models, and the dataflow behavior that is exhibited by implementations that are derived from the models. In this paper, we address this problem by introducing a novel dataflow validation framework (DVF) that is able to identify disparities between an application's formal dataflow representation and its implementation. DVF works by instrumenting the implementation of an application and monitoring the instrumentation data as the application executes. This monitoring process is streamlined so that DVF achieves validation without major overhead. We demonstrate the utility of our DVF through design and implementation case studies involving an automatic speech recognition application, a JPEG encoder, and an acoustic tracking application.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Pervasive Computing, Research area: Computer engineering, Signal Processing Research Community (SPRC), University of Maryland, Technische Universität München, Institute for Advanced Computer Studies

Contributors: Chukhman, I., Jiao, Y., Salem, H. B., Bhattacharyya, S. S.
Pages: 383–397
Publication date: 2016
Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 84

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2016): CiteScore 1.6 SJR 0.212 SNIP 0.677

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science

Keywords: Dataflow graphs, Design validation, Models of computation, Signal processing systems

DOIs:

10.1007/s11265-015-1073-6

Source: Scopus

Source ID: 84946128443

Research output: Contribution to journal › Article › Scientific › peer-review

Integration of dataflow-based heterogeneous multiprocessor scheduling techniques in GNU radio

As the variety of off-the-shelf processors expands, traditional implementation methods of systems for digital signal processing and communication are no longer adequate to achieve design objectives in a timely manner. There is a necessity for designers to easily track the changes in computing platforms, and apply them efficiently while reusing legacy code and optimized libraries that target specialized features in single processing units. In this context, we propose an integration workflow to schedule and implement Software Defined Radio (SDR) protocols that are developed using the GNU Radio environment on heterogeneous multiprocessor platforms. We show how to utilize Single Instruction Multiple Data (SIMD) units provided in Graphics Processing Units (GPUs) along with vector accelerators implemented in General Purpose Processors (GPPs). We augment a popular SDR framework (i.e. GNU Radio) with a library that seamlessly allows offloading of algorithm kernels mapped to the GPU without changing the original protocol description. Experimental results show how our approach can be used to efficiently explore design spaces for SDR system implementation, and examine the overhead of the integrated backend (software component) library.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), University of Maryland, Department of Electrical and Computer Engineering, Virginia Tech, Laboratory for Telecommunications Sciences

Contributors: Zaki, G. F., Plishker, W., Bhattacharyya, S. S., Clancy, C., Kuykendall, J.

Number of pages: 15

Pages: 177-191

Publication date: Feb 2013

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 70

Issue number: 2

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2013): CiteScore 2.1 SJR 0.254 SNIP 0.866

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Design methodology, GNU Radio, Graphic processor unit, Multiprocessor scheduling, Software defined radio

DOIs:

10.1007/s11265-012-0696-0

URLs:

<http://www.scopus.com/inward/record.url?scp=84892800816&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84892800816

Research output: Contribution to journal › Article › Scientific › peer-review

Iterative and Participative Axiomatic Design Process in complex mechanical assemblies: case study on fusion engineering

The present paper proposes a structured Product Development Lifecycle (PDL) model to deal with the concept design stage of complex assemblies. The proposed method provides a systematic approach to design, aimed to improve requirements management, project management and communication among stakeholders as well as to avoid project failures reducing project development time. This research also provides suggestions and recommendations for utilizing different analysis, synthesis and assessment methodologies along with the proposed approach. The process developed, named Iterative and Participative Axiomatic Design Process (IPADeP), is consistent with ISO/IEC 15288:2008 – “Systems and software engineering”, and INCOSE Systems engineering handbook. It is an iterative and incremental design process, participative and requirements driven, based on the theory of Axiomatic Product Development Lifecycle (APDL). IPADeP provides a systematic methodology in which, starting from a set of experts’ assumptions, a number of conceptual solutions are generated, analysed and evaluated. Based on the results obtained, new iterations can be performed for each level of decomposition while product requirements are refined. In this paper, we applied IPADeP to the initial phase of conceptual design activities for DEMO divertor-to-vacuum vessel locking system in order to propose new innovative solutions.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Intelligent Hydraulics and Automation, Research group: Fluid power automation in mobile machines, Dipartimento di Ingegneria, ENEA/CREATE/Università Degli Studi Napoli Federico II, VTT Technical Research Centre of Finland

Contributors: Di Gironimo, G., Lanzotti, A., Marzullo, D., Esposito, G., Carfora, D., Siuko, M.

Number of pages: 14

Pages: 325-338

Publication date: 22 Mar 2015

Peer-reviewed: Yes

Publication information

Journal: International Journal on Interactive Design and Manufacturing

Volume: 9

Issue number: 4

ISSN (Print): 1955-2513

Ratings:

Scopus rating (2015): CiteScore 1.7 SJR 0.349 SNIP 0.792

Original language: English

ASJC Scopus subject areas: Industrial and Manufacturing Engineering, Modelling and Simulation

Keywords: Axiomatic Design, Concept design, DEMO divertor locking system, Fuzzy-AHP, Systems engineering

DOIs:

10.1007/s12008-015-0270-7

URLs:

<http://www.scopus.com/inward/record.url?scp=84945463454&partnerID=8YFLogxK> (Link to publication in Scopus)

Bibliographical note

EXT="Siuko, M."

Source: Scopus

Source ID: 84945463454

Research output: Contribution to journal › Article › Scientific › peer-review

Local network-based measures to assess the inferability of different regulatory networks

The purpose of this study is to compare the inferability of various synthetic as well as real biological regulatory networks. In order to assess differences we apply local network-based measures. That means, instead of applying global measures, we investigate and assess an inference algorithm locally, on the level of individual edges and subnetworks. We demonstrate the behaviour of our local network-based measures with respect to different regulatory networks by conducting large-scale simulations. As inference algorithm we use exemplarily ARACNE. The results from our exploratory analysis allow us not only to gain new insights into the strength and weakness of an inference algorithm with respect to characteristics of different regulatory networks, but also to obtain information that could be used to design novel problem-specific statistical estimators. [Includes supplementary material]

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences, Queen's University, Belfast, Northern Ireland

Contributors: Emmert-Streib, F., Altay, G.

Number of pages: 12
Pages: 277-288
Publication date: Jul 2010
Peer-reviewed: Yes

Publication information

Journal: IET Systems Biology
Volume: 4

Issue number: 4

Article number: ISBEAT000004000004000277000001

ISSN (Print): 1751-8849

Ratings:

Scopus rating (2010): SJR 0.773 SNIP 0.791

Original language: English

ASJC Scopus subject areas: Biotechnology, Cell Biology, Genetics, Molecular Biology, Modelling and Simulation, Medicine(all)

DOIs:

10.1049/iet-syb.2010.0028

URLs:

<http://www.scopus.com/inward/record.url?scp=77954479475&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 77954479475

Research output: Contribution to journal > Article > Scientific > peer-review

Mapping parameterized cyclo-static dataflow graphs onto configurable hardware

In recent years, parameterized dataflow has evolved as a useful framework for modeling synchronous and cyclo-static graphs in which arbitrary parameters can be changed dynamically. Parameterized dataflow has proven to have significant expressive power for managing dynamics of DSP applications in important ways. However, efficient hardware synthesis techniques for parameterized dataflow representations are lacking. This paper addresses this void; specifically, the paper investigates efficient field programmable gate array (FPGA)-based implementation of parameterized cyclo-static dataflow (PCSDF) graphs. We develop a scheduling technique for throughput-constrained minimization of dataflow buffering requirements when mapping PCSDF representations of DSP applications onto FPGAs. The proposed scheduling technique is integrated with an existing formal schedule model, called the generalized schedule tree, to reduce schedule cost. To demonstrate our new, hardware-oriented PCSDF scheduling technique, we have designed a real-time base station emulator prototype based on a subset of long-term evolution (LTE), which is a key cellular standard.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), National Instruments, University of Maryland, Department of Electrical and Computer Engineering

Contributors: Kee, H., Shen, C. C., Bhattacharyya, S. S., Wong, I., Rao, Y., Kornerup, J.

Number of pages: 17

Pages: 285-301

Publication date: 2012

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 66

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2012): CiteScore 2.1 SJR 0.269 SNIP 0.879

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: 4G communication systems, Dataflow modeling, FPGA implementation, Parameterized dataflow, Scheduling

DOIs:

10.1007/s11265-011-0599-5

URLs:

<http://www.scopus.com/inward/record.url?scp=84888881360&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84888881360

Model-Based Dynamic Scheduling for Multicore Signal Processing

This paper presents a model-based design method and a corresponding new software tool, the HTGS Model-Based Engine (HMBE), for designing and implementing dataflow-based signal processing applications on multi-core architectures. HMBE provides complementary capabilities to HTGS (Hybrid Task Graph Scheduler), a recently-introduced software tool for implementing scalable workflows for high performance computing applications on compute nodes with high core counts and multiple GPUs. HMBE integrates model-based design approaches, founded on dataflow principles, with advanced design optimization techniques provided in HTGS. This integration contributes to (a) making the application of HTGS more systematic and less time consuming, (b) incorporating additional dataflow-based optimization capabilities with HTGS optimizations, and (c) automating significant parts of the HTGS-based design process using a principled approach. In this paper, we present HMBE with an emphasis on the model-based design approaches and the novel dynamic scheduling techniques that are developed as part of the tool. We demonstrate the utility of HMBE via two case studies: an image stitching application for large microscopy images and a background subtraction application for multispectral video streams.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Pervasive Computing, Research area: Computer engineering, University of Maryland, National Institute of Standards and Technology

Contributors: Wu, J., Blattner, T., Keyrouz, W., Bhattacharyya, S. S.

Number of pages: 14

Pages: 1-14

Publication date: 2018

Peer-reviewed: Yes

Early online date: 2018

Publication information

Journal: Journal of Signal Processing Systems

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2018): CiteScore 1.7 SJR 0.203 SNIP 0.61

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Dataflow, Memory management, Multicore platforms, Scheduling

DOIs:

10.1007/s11265-018-1412-5

Source: Scopus

Source ID: 85054798661

Research output: Contribution to journal › Article › Scientific › peer-review

Networks for systems biology: Conceptual connection of data and function

The purpose of this study is to survey the use of networks and network-based methods in systems biology. This study starts with an introduction to graph theory and basic measures allowing to quantify structural properties of networks. Then, the authors present important network classes and gene networks as well as methods for their analysis. In the last part of this study, the authors review approaches that aim at analysing the functional organisation of gene networks and the use of networks in medicine. In addition to this, the authors advocate networks as a systematic approach to general problems in systems biology, because networks are capable of assuming multiple roles that are very beneficial connecting experimental data with a functional interpretation in biological terms.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Research Community on Data-to-Decision (D2D), Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences, Queen's University, Belfast, Northern Ireland, Institute for Bioinformatics and Translational Research

Contributors: Emmert-Streib, F., Dehmer, M.

Number of pages: 23

Pages: 185-207

Publication date: May 2011

Peer-reviewed: Yes

Publication information

Journal: IET Systems Biology

Volume: 5

Issue number: 3

ISSN (Print): 1751-8849

Ratings:

Scopus rating (2011): CiteScore 3.2 SJR 0.745 SNIP 0.664

Original language: English

ASJC Scopus subject areas: Biotechnology, Cell Biology, Genetics, Molecular Biology, Modelling and Simulation

DOIs:

10.1049/iet-syb.2010.0025

URLs:

<http://www.scopus.com/inward/record.url?scp=79960325408&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 79960325408

Research output: Contribution to journal > Article > Scientific > peer-review

On the effect of deformation twinning and microstructure to strain hardening of high manganese austenitic steel 3D microstructure aggregates at large strains

The hardening and deformation characteristics of Hadfield microstructure are studied to investigate the effect of microstructure to the material behavior. A crystal plasticity model including dislocation slip and deformation twinning is employed. The role of deformation twinning to the overall strain hardening of the material is evaluated for two different grain structures. Large compressive strains are applied on 3D microstructural aggregates representing the uniform and non-uniform grain structures of Hadfield steels. The grain structure has an effect on the strain hardening rate as well as on the overall hardening capability of the microstructure. A major reason causing the difference in strain hardening arises from the different twin volume fraction evolution influenced by intra-grain and inter-grain interactions. A mixture of large and small grains was found to be more favorable for twinning and thus resulting in a greater hardening capability than uniform grain size.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Materials Science, Research group: Materials Characterization, VTT Lifecycle Solutions

Contributors: Lindroos, M., Laukkanen, A., Cailletaud, G., Kuokkala, V.

Pages: 68-76

Publication date: 2017

Peer-reviewed: Yes

Publication information

Journal: International Journal of Solids and Structures

Volume: 125

ISSN (Print): 0020-7683

Ratings:

Scopus rating (2017): CiteScore 4.8 SJR 1.295 SNIP 1.574

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Materials Science(all), Condensed Matter Physics, Mechanics of Materials, Mechanical Engineering, Applied Mathematics

Keywords: Austenitic manganese steel, Crystal plasticity, Deformation twinning, Microstructure based modeling

DOIs:

10.1016/j.ijsolstr.2017.07.015

Bibliographical note

EXT="Lindroos, Matti"

Source: Scopus

Source ID: 85025152227

Research output: Contribution to journal > Article > Scientific > peer-review

Optimization of Flexible Filter Banks Based on Fast Convolution

Multirate filter banks can be implemented efficiently using fast-convolution (FC) processing. The main advantage of the FC filter banks (FC-FB) compared with the conventional polyphase implementations is their increased flexibility, that is, the number of channels, their bandwidths, and the center frequencies can be independently selected. In this paper, an approach to optimize the FC-FBs is proposed. First, a subband representation of the FC-FB is derived. Then, the optimization problems are formulated with the aid of the subband model. Finally, these problems are conveniently solved with the aid of a general nonlinear optimization algorithm. Several examples are included to demonstrate the proposed overall design scheme as well as to illustrate the efficiency and the flexibility of the resulting FC-FB.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Electronics and Communications Engineering, Research group: Wireless Communications and Positioning

Contributors: Yli-Kaakinen, J., Renfors, M.

Pages: 101-111

Publication date: Aug 2016

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 85

Issue number: 1

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2016): CiteScore 1.6 SJR 0.212 SNIP 0.677

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science

Keywords: Digital filters, Filter banks, Multirate signal processing, Optimization, Sampling rate conversion

DOIs:

10.1007/s11265-015-1004-6

Source: Scopus

Source ID: 84929682954

Research output: [Contribution to journal](#) > [Article](#) > [Scientific](#) > [peer-review](#)

Organizational structure and the periphery of the gene regulatory network in B-cell lymphoma.

The physical periphery of a biological cell is mainly described by signaling pathways which are triggered by transmembrane proteins and receptors that are sentinels to control the whole gene regulatory network of a cell. However, our current knowledge about the gene regulatory mechanisms that are governed by extracellular signals is severely limited. The purpose of this paper is three fold. First, we infer a gene regulatory network from a large-scale B-cell lymphoma expression data set using the C3NET algorithm. Second, we provide a functional and structural analysis of the largest connected component of this network, revealing that this network component corresponds to the peripheral region of a cell. Third, we analyze the hierarchical organization of network components of the whole inferred B-cell gene regulatory network by introducing a new approach which exploits the variability within the data as well as the inferential characteristics of C3NET. As a result, we find a functional bisection of the network corresponding to different cellular components. Overall, our study allows to highlight the peripheral gene regulatory network of B-cells and shows that it is centered around hub transmembrane proteins located at the physical periphery of the cell. In addition, we identify a variety of novel pathological transmembrane proteins such as ion channel complexes and signaling receptors in B-cell lymphoma.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Research Community on Data-to-Decision (D2D), Prostate cancer research center (PCRC), Queen's University, Belfast, Northern Ireland, Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences

Contributors: de Matos Simoes, R., Tripathi, S., Emmert-Streib, F.

Publication date: 14 May 2012

Peer-reviewed: Yes

Publication information

Journal: BMC Systems Biology

Volume: 6

Article number: 38

ISSN (Print): 1752-0509

Ratings:

Scopus rating (2012): CiteScore 5.4 SJR 1.577 SNIP 1.009

Original language: English

ASJC Scopus subject areas: Molecular Biology, Structural Biology, Applied Mathematics, Modelling and Simulation, Computer Science Applications

Keywords: B-cell lymphoma, Gene expression data, Gene regulatory network, Statistical network inference

DOIs:

10.1186/1752-0509-6-38

URLs:

<http://www.scopus.com/inward/record.url?scp=84865119369&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84865119369

Research output: Contribution to journal › Article › Scientific › peer-review

Overview of the MPEG reconfigurable video coding framework

Video coding technology in the last 20 years has evolved producing a variety of different and complex algorithms and coding standards. So far the specification of such standards, and of the algorithms that build them, has been done case by case providing monolithic textual and reference software specifications in different forms and programming languages. However, very little attention has been given to provide a specification formalism that explicitly presents common components between standards, and the incremental modifications of such monolithic standards. The MPEG Reconfigurable Video Coding (RVC) framework is a new ISO standard currently under its final stage of standardization, aiming at providing video codec specifications at the level of library components instead of monolithic algorithms. The new concept is to be able to specify a decoder of an existing standard or a completely new configuration that may better satisfy application-specific constraints by selecting standard components from a library of standard coding algorithms. The possibility of dynamic configuration and reconfiguration of codecs also requires new methodologies and new tools for describing the new bitstream syntaxes and the parsers of such new codecs. The RVC framework is based on the usage of a new actor/ dataflow oriented language called CAL for the specification of the standard library and instantiation of the RVC decoder model. This language has been specifically designed for modeling complex signal processing systems. CAL dataflow models expose the intrinsic concurrency of the algorithms by employing the notions of actor programming and dataflow. The paper gives an overview of the concepts and technologies building the standard RVC framework and the non standard tools supporting the RVC model from the instantiation and simulation of the CAL model to software and/or hardware code synthesis.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), Department of Electrical and Computer Engineering, University of Maryland, Ericsson Research, Xilinx Research Labs, CRPP, UBL

Contributors: Bhattacharyya, S. S., Eker, J., Janneck, J. W., Lucarz, C., Mattavelli, M., Raulet, M.

Number of pages: 13

Pages: 251-263

Publication date: May 2011

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 63

Issue number: 2

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2011): CiteScore 1.8 SJR 0.248 SNIP 0.707

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: CAL actor language, Code synthesis, Dataflow programming, Reconfigurable Video Coding

DOIs:

10.1007/s11265-009-0399-3

URLs:

<http://www.scopus.com/inward/record.url?scp=79954574143&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 79954574143

Research output: Contribution to journal › Article › Scientific › peer-review

Parallel Digital Predistortion Design on Mobile GPU and Embedded Multicore CPU for Mobile Transmitters

Digital predistortion (DPD) is a widely adopted baseband processing technique in current radio transmitters. While DPD can effectively suppress unwanted spurious spectrum emissions stemming from imperfections of analog RF and baseband electronics, it also introduces extra processing complexity and poses challenges on efficient and flexible implementations, especially for mobile cellular transmitters, considering their limited computing power compared to basestations. In this paper, we present high data rate implementations of broadband DPD on modern embedded processors, such as mobile GPU and multicore CPU, by taking advantage of emerging parallel computing techniques for exploiting their computing resources. We further verify the suppression effect of DPD experimentally on real radio hardware platforms. Performance evaluation results of our DPD design demonstrate the high efficacy of modern general purpose mobile processors on accelerating DPD processing for a mobile transmitter.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Electronics and Communications Engineering, Research group: Wireless Communications and Positioning, Rice University, Univ of Oulu

Contributors: Li, K., Ghazi, A., Tarver, C., Boutellier, J., Abdelaziz, M., Anttila, L., Juntti, M., Valkama, M., Cavallaro, J. R.

Number of pages: 14

Pages: 417–430

Publication date: 2017

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 89

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: CUDA, Digital predistortion, Mobile SoC, NEON SIMD, Software-defined radio

Electronic versions:

Parallel Digital Predistortion Design on Mobile GPU 2017

DOIs:

10.1007/s11265-017-1233-y

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202002041822>

Source: Scopus

Source ID: 85013872658

Research output: [Contribution to journal](#) › [Article](#) › [Scientific](#) › [peer-review](#)

Parameterized scheduling of topological patterns in signal processing dataflow graphs

In recent work, a graphical modeling construct called "topological patterns" has been shown to enable concise representation and direct analysis of repetitive dataflow graph sub-structures in the context of design methods and tools for digital signal processing systems (Sane et al. 2010). In this paper, we present a formal design method for specifying topological patterns and deriving parameterized schedules from such patterns based on a novel schedule model called the scalable schedule tree. The approach represents an important class of parameterized schedule structures in a form that is intuitive for representation and efficient for code generation. Through application case studies involving image processing and wireless communications, we demonstrate our methods for topological pattern representation, scalable schedule tree derivation, and associated dataflow graph code generation.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), University of Maryland, Department of Electrical and Computer Engineering

Contributors: Wang, L. H., Shen, C. C., Wu, S., Bhattacharyya, S. S.

Number of pages: 12

Pages: 275-286

Publication date: 2013

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 71

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2013): CiteScore 2.1 SJR 0.254 SNIP 0.866

Original language: English

ASJC Scopus subject areas: Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science, Control and Systems Engineering, Modelling and Simulation

Keywords: Dataflow, Image registration, Scheduling, Software tools, Turbo decoder

DOIs:

10.1007/s11265-012-0719-x

URLs:

<http://www.scopus.com/inward/record.url?scp=84879696501&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84879696501

Research output: Contribution to journal > Article > Scientific > peer-review

Pathway analysis of expression data: Deciphering functional building blocks of complex diseases

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Prostate cancer research center (PCRC), Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences, Queen's University, Belfast, Northern Ireland, University of Arkansas for Medical Sciences

Contributors: Emmert-Streib, F., Glazko, G. V.

Publication date: May 2011

Peer-reviewed: Yes

Publication information

Journal: PLoS Computational Biology

Volume: 7

Issue number: 5

Article number: e1002053

ISSN (Print): 1553-734X

Ratings:

Scopus rating (2011): CiteScore 8.1 SJR 3.613 SNIP 1.636

Original language: English

ASJC Scopus subject areas: Cellular and Molecular Neuroscience, Ecology, Molecular Biology, Genetics, Ecology, Evolution, Behavior and Systematics, Modelling and Simulation, Computational Theory and Mathematics

DOIs:

[10.1371/journal.pcbi.1002053](https://doi.org/10.1371/journal.pcbi.1002053)

URLs:

<http://www.scopus.com/inward/record.url?scp=79958152651&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 79958152651

Research output: Contribution to journal > Article > Scientific > peer-review

Pneumatic unidirectional cell stretching device for mechanobiological studies of cardiomyocytes

In this paper, we present a transparent mechanical stimulation device capable of uniaxial stimulation, which is compatible with standard bioanalytical methods used in cellular mechanobiology. We validate the functionality of the uniaxial stimulation system using human-induced pluripotent stem cells-derived cardiomyocytes (hiPSC-CMs). The pneumatically controlled device is fabricated from polydimethylsiloxane (PDMS) and provides uniaxial strain and superior optical performance compatible with standard inverted microscopy techniques used for bioanalytics (e.g., fluorescence microscopy and calcium imaging). Therefore, it allows for a continuous investigation of the cell state during stretching experiments. The paper introduces design and fabrication of the device, characterizes the mechanical performance of the device and demonstrates the compatibility with standard bioanalytical analysis tools. Imaging modalities, such as high-resolution live cell phase contrast imaging and video recordings, fluorescent imaging and calcium imaging are possible to perform in the device. Utilizing the different imaging modalities and proposed stretching device, we demonstrate the capability of the device for extensive further studies of hiPSC-CMs. We also demonstrate that sarcomere structures of hiPSC-CMs organize and orient perpendicular to uniaxial strain axis and thus express more matured nature of cardiomyocytes.

General information

Publication status: E-pub ahead of print

MoE publication type: A1 Journal article-refereed

Organisations: Research group: Micro and Nanosystems Research Group, BioMediTech, Risø Campus, Tampere University of Applied Sciences, Eindhoven University of Technology, Tampere University Hospital

Contributors: Kreutzer, J., Viehrig, M., Pölonen, R. P., Zhao, F., Ojala, M., Aalto-Setälä, K., Kallio, P.

Publication date: 23 Aug 2019

Peer-reviewed: Yes

Publication information

Journal: BIOMECHANICS AND MODELING IN MECHANOBIOLOGY

ISSN (Print): 1617-7959

Ratings:

Scopus rating (2019): CiteScore 5.2 SJR 0.85 SNIP 1.159

Original language: English

ASJC Scopus subject areas: Biotechnology, Modelling and Simulation, Mechanical Engineering

Keywords: Cardiomyocytes, hiPSC, Mechanical stimulation, PDMS

Electronic versions:

Kreutzer2019_Article_PneumaticUnidirectionalCellStr

DOIs:

10.1007/s10237-019-01211-8

URLs:

<http://urn.fi/URN:NBN:fi:tuni-201909183380>

Bibliographical note

EXT="Zhao, Feihu"

Source: Scopus

Source ID: 85070939275

Research output: Contribution to journal › Article › Scientific › peer-review

Possible structures of nonstoichiometric tin oxide: The composition Sn₂O₃

Structural aspects of crystalline tin oxide and its interfaces with composition Sn₂O₃ are considered computationally based on first principles density functional calculations. The possibility of formation of different nonstoichiometric tin oxide crystals and SnO₂/SnO interfaces is shown. The lowest total energy per Sn₂O₃ unit was evaluated for a layered Sn₂O₃ crystal, where oxygen vacancies are arranged into the (101) plane in a rutile structure system. Interface structures with orientations SnO₂(101)/SnO(001) and SnO₂(100)/SnO(100), corresponding to composition Sn₂O₃ are only slightly less stable. Their estimated interface energies are 0.15 J m⁻² and 0.8 J m⁻², respectively. All geometries have components similar to well-known rutile structure SnO₂ and litharge structure SnO geometries. Most stable Sn₂O₃ crystals include SnO₆ octahedra similar to those found in rutile structure SnO₂.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Institute of Physics

Contributors: Mäki-Jaskari, M. A., Rantala, T. T.

Number of pages: 9

Pages: 33-41

Publication date: Jan 2004

Peer-reviewed: Yes

Publication information

Journal: Modelling and Simulation in Materials Science and Engineering

Volume: 12

Issue number: 1

ISSN (Print): 0965-0393

Ratings:

Scopus rating (2004): SJR 1.074 SNIP 1.286

Original language: English

ASJC Scopus subject areas: Materials Science(all), Physics and Astronomy (miscellaneous), Modelling and Simulation

DOIs:

10.1088/0965-0393/12/1/004

URLs:

<http://www.scopus.com/inward/record.url?scp=0942300309&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 0942300309

Research output: Contribution to journal › Article › Scientific › peer-review

Power Mitigation by Performance Equalization in a Heterogeneous Reconfigurable Multicore Architecture

This paper presents an integrated self-aware computing model mitigating the power dissipation of a heterogeneous reconfigurable multicore architecture by dynamically scaling the operating frequency of each core. The power mitigation is achieved by equalizing the performance of all the cores for an uninterrupted exchange of data. The multicore platform consists of heterogeneous Coarse-Grained Reconfigurable Arrays (CGRAs) of application-specific sizes and a Reduced Instruction-Set Computing (RISC) core. The CGRAs and the RISC core are integrated with each other over a Network-on-Chip (NoC) of six nodes arranged in a topology of two rows and three columns. The RISC core constantly monitors and controls the performance of each CGRA accelerator by adjusting the operating frequencies unless the performance of all

the CGRAs is optimally balanced over the platform. The CGRA cores on the platform are processing some of the most computationally-intensive signal processing algorithms while the RISC core establishes packet based synchronization between the cores for computation and communication. All the cores can access each other's computational and memory resources while processing the kernels simultaneously and independently of each other. Besides general-purpose processing and overall platform supervision, the RISC processor manages performance equalization among all the cores which mitigates the overall dynamic power dissipation by 20.7 % for a proof-of-concept test.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Electronics and Communications Engineering, Research group: System-on-Chip for GNSS, Wireless Communications and Cyber-Physical Embedded Computing

Contributors: Hussain, W., Hoffmann, H., Ahonen, T., Nurmi, J.

Number of pages: 11

Pages: 287–297

Publication date: Jun 2017

Peer-reviewed: Yes

Early online date: 5 May 2016

Publication information

Journal: Journal of Signal Processing Systems

Volume: 87

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science

Keywords: CGRA, Dark silicon, Heterogeneous, Multicore, Power dissipation, Reconfigurable

DOIs:

10.1007/s11265-016-1142-5

Source: Scopus

Source ID: 84965022070

Research output: [Contribution to journal](#) > [Article](#) > [Scientific](#) > [peer-review](#)

PRBS-based loop gain identification and output impedance shaping in DC microgrid power converters

Due to potential dynamic interactions among dc microgrid power converters, the performance of some of their control loops can vary from the designed behavior. Thus, online monitoring of different control loops within a dc microgrid power converter is highly desirable. This paper proposes the simultaneous identification of several control loops within dc microgrid power converters, by injecting orthogonal pseudo-random binary sequences (PRBSs), and measuring all the loop gains in one measurement cycle. The identification results can be used for different purposes such as controller autotuning, impedance shaping, etc. Herein, an example of output impedance estimation and shaping based on locally-measured loop gains is presented. The proposed identification technique and its application in output impedance shaping are validated on an experimental dc microgrid prototype, composed of three droop-controlled power converters.

General information

Publication status: E-pub ahead of print

MoE publication type: A1 Journal article-refereed

Organisations: Research group: Power electronics, Research area: Power engineering, Electrical Engineering, Università degli Studi di Padova, Italy

Contributors: Khodamoradi, A., Liu, G., Mattavelli, P., Messo, T., Abedini, H.

Number of pages: 13

Publication date: 2020

Peer-reviewed: Yes

Publication information

Journal: Mathematics and Computers in Simulation

ISSN (Print): 0378-4754

Original language: English

ASJC Scopus subject areas: Theoretical Computer Science, Computer Science(all), Numerical Analysis, Modelling and Simulation, Applied Mathematics

Keywords: DC microgrid, Impedance shaping, Loop gain identification

DOIs:

10.1016/j.matcom.2020.04.017

Source: Scopus

Source ID: 85084199897

Research output: Contribution to journal › Article › Scientific › peer-review

Preoperative simulation for the planning of microsurgical clipping of intracranial aneurysms

Introduction: The safety and success of intracranial aneurysm (IA) surgery could be improved through the dedicated application of simulation covering the procedure from the 3-dimensional (3D) description of the surgical scene to the visual representation of the clip application. We aimed in this study to validate the technical feasibility and clinical relevance of such a protocol. **Methods:** All patients preoperatively underwent 3D magnetic resonance imaging and 3D computed tomography angiography to build 3D reconstructions of the brain, cerebral arteries, and surrounding cranial bone. These 3D models were segmented and merged using Osirix, a DICOM image processing application. This provided the surgical scene that was subsequently imported into Blender, a modeling platform for 3D animation. Digitized clips and appliers could then be manipulated in the virtual operative environment, allowing the visual simulation of clipping. This simulation protocol was assessed in a series of 10 IAs by 2 neurosurgeons. **Results:** The protocol was feasible in all patients. The visual similarity between the surgical scene and the operative view was excellent in 100% of the cases, and the identification of the vascular structures was accurate in 90% of the cases. The neurosurgeons found the simulation helpful for planning the surgical approach (ie, the bone flap, cisternal opening, and arterial tree exposure) in 100% of the cases. The correct number of final clip(s) needed was predicted from the simulation in 90% of the cases. The preoperatively expected characteristics of the optimal clip(s) (ie, their number, shape, size, and orientation) were validated during surgery in 80% of the cases. **Conclusions:** This study confirmed that visual simulation of IA clipping based on the processing of high-resolution 3D imaging can be effective. This is a new and important step toward the development of a more sophisticated integrated simulation platform dedicated to cerebrovascular surgery.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Frontier Photonics, Lille University Hospital - CHRU, Division of Neurosurgery, Department of Neurosciences and Locomotive System, Univ Lille Nord de France, Clinique de Neurochirurgie

Contributors: Marinho, P., Vermandel, M., Bourgeois, P., Lejeune, J. P., Mordon, S., Thines, L.

Number of pages: 7

Pages: 370-376

Publication date: 20 Dec 2014

Peer-reviewed: Yes

Publication information

Journal: SIMULATION IN HEALTHCARE

Volume: 9

Issue number: 6

ISSN (Print): 1559-2332

Ratings:

Scopus rating (2014): CiteScore 3.7 SJR 0.986 SNIP 1.09

Original language: English

ASJC Scopus subject areas: Medicine (miscellaneous), Epidemiology, Education, Modelling and Simulation, Medicine(all)

Keywords: Cerebrovascular surgery, Image-guided surgery, Intracranial aneurysm, Minimally invasive surgery, Neurosurgical planning, Simulation

DOIs:

10.1097/SIH.0000000000000056

URLs:

<http://www.scopus.com/inward/record.url?scp=84919484527&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84919484527

Research output: Contribution to journal › Article › Scientific › peer-review

Properties of graph distance measures by means of discrete inequalities

In this paper, we investigate graph distance measures based on topological graph measures. Those measures can be used to measure the structural distance between graphs. When studying the scientific literature, one is aware that measuring distance/similarity between graphs meaningfully has been intricate. We demonstrate that our measures are well-defined and prove bounds for investigating their value domain. Also, we generate numerical results and demonstrate that the measures have useful properties.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Faculty of Biomedical Sciences and Engineering, Research group: Computational Medicine and Statistical Learning Laboratory (CMSL), Research group: Predictive Society and Data Analytics (PSDA), University of Applied

Sciences Upper Austria, Nankai University, Institute for Bioinformatics and Translational Research, Laboratory of Biosystem Dynamics, Institute of Biosciences and Medical Technology, Institute for Intelligent Production, The City College of New York (CUNY)

Contributors: Dehmer, M., Chen, Z., Emmert-Streib, F., Shi, Y., Tripathi, S., Musa, A., Mowshowitz, A.

Number of pages: 11

Pages: 739-749

Publication date: 1 Jul 2018

Peer-reviewed: Yes

Publication information

Journal: Applied Mathematical Modelling

Volume: 59

ISSN (Print): 0307-904X

Ratings:

Scopus rating (2018): CiteScore 5.3 SJR 0.873 SNIP 1.544

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Applied Mathematics

Keywords: Distance measures, Graphs, Inequalities, Networks, Similarity measures

DOIs:

10.1016/j.apm.2018.01.027

Bibliographical note

EXT="Tripathi, Shailesh"

Source: Scopus

Source ID: 85044481326

Research output: Contribution to journal > Article > Scientific > peer-review

Quantifying the non-ergodicity of scaled Brownian motion

We examine the non-ergodic properties of scaled Brownian motion (SBM), a non-stationary stochastic process with a time dependent diffusivity of the form $D(t) \propto t^{\alpha-1}$. We compute the ergodicity breaking parameter EB in the entire range of scaling exponents α , both analytically and via extensive computer simulations of the stochastic Langevin equation. We demonstrate that in the limit of long trajectory lengths T and short lag times Δ the EB parameter as function of the scaling exponent α has no divergence at $\alpha = 1/2$ and present the asymptotes for EB in different limits. We generalize the analytical and simulations results for the time averaged and ergodic properties of SBM in the presence of ageing, that is, when the observation of the system starts only a finite time span after its initiation. The approach developed here for the calculation of the higher time averaged moments of the particle displacement can be applied to derive the ergodic properties of other stochastic processes such as fractional Brownian motion.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Institute for Physics and Astronomy, University of Potsdam, Akhiezer Institute for Theoretical Physics, Kharkov Institute of Physics and Technology, Institute for Physics And Astronomy, Humboldt-Universität zu Berlin, Shahid Beheshti University

Contributors: Safdari, H., Cherstvy, A. G., Chechkin, A. V., Thiel, F., Sokolov, I. M., Metzler, R.

Publication date: 18 Sep 2015

Peer-reviewed: Yes

Publication information

Journal: Journal of Physics A: Mathematical and Theoretical

Volume: 48

Issue number: 37

Article number: 375002

ISSN (Print): 1751-8113

Ratings:

Scopus rating (2015): CiteScore 3.5 SJR 1.028 SNIP 1.04

Original language: English

ASJC Scopus subject areas: Mathematical Physics, Physics and Astronomy(all), Statistical and Nonlinear Physics, Modelling and Simulation, Statistics and Probability

Keywords: ageing, anomalous diffusion, scaled Brownian motion

DOIs:

10.1088/1751-8113/48/37/375002

URLs:

<http://www.scopus.com/inward/record.url?scp=84940069543&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84940069543

Research output: Contribution to journal › Article › Scientific › peer-review

Quasi-static scheduling of CAL actor networks for reconfigurable video coding

The upcoming Reconfigurable Video Coding (RVC) standard from MPEG (ISO / IEC SC29WG11) defines a library of coding tools to specify existing or new compressed video formats and decoders. The coding tool library has been written in a dataflow/actor-oriented language named CAL. Each coding tool (actor) can be represented with an extended finite state machine and the data communication between the tools are described as dataflow graphs. This paper proposes an approach to model the CAL actor network with Parameterized Synchronous Data Flow and to derive a quasi-static multiprocessor execution schedule for the system. In addition to proposing a scheduling approach for RVC, an extension to the well-known permutation flow shop scheduling problem that enables rapid run-time scheduling of RVC tasks, is introduced.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), Machine Vision Group, Univ of Oulu, CRPP, Abo Akad Univ, Abo Akademi University, Dept Phys

Contributors: Boutellier, J., Lucarz, C., Lafond, S., Gomez, V. M., Mattavelli, M.

Number of pages: 12

Pages: 191-202

Publication date: May 2011

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 63

Issue number: 2

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2011): CiteScore 1.8 SJR 0.248 SNIP 0.707

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Digital signal processors, Modeling, Parallel processing, Scheduling

DOIs:

10.1007/s11265-009-0389-5

URLs:

<http://www.scopus.com/inward/record.url?scp=79954614566&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 79954614566

Research output: Contribution to journal › Article › Scientific › peer-review

Reduced level of docosahexaenoic acid shifts GPCR neuroreceptors to less ordered membrane regions

G protein-coupled receptors (GPCRs) control cellular signaling and responses. Many of these GPCRs are modulated by cholesterol and polyunsaturated fatty acids (PUFAs) which have been shown to co-exist with saturated lipids in ordered membrane domains. However, the lipid compositions of such domains extracted from the brain cortex tissue of individuals suffering from GPCR-associated neurological disorders show drastically lowered levels of PUFAs. Here, using free energy techniques and multiscale simulations of numerous membrane proteins, we show that the presence of the PUFA DHA helps helical multi-pass proteins such as GPCRs partition into ordered membrane domains. The mechanism is based on hybrid lipids, whose PUFA chains coat the rough protein surface, while the saturated chains face the raft environment, thus minimizing perturbations therein. Our findings suggest that the reduction of GPCR partitioning to their native ordered environments due to PUFA depletion might affect the function of these receptors in numerous neurodegenerative diseases, where the membrane PUFA levels in the brain are decreased. We hope that this work inspires experimental studies on the connection between membrane PUFA levels and GPCR signaling.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Physics, University of Helsinki, Institute of Organic Chemistry and Biochemistry, Academy of Sciences of the Czech Republic, Universitat Autònoma de Barcelona, University of Texas Health Science Center at Houston, MEMPHYS

Contributors: Javanainen, M., Enkavi, G., Guixà-González, R., Kulig, W., Martinez-Seara, H., Levental, I., Vattulainen, I.

Publication date: 1 May 2019

Peer-reviewed: Yes

Publication information

Journal: PLoS Computational Biology

Volume: 15

Issue number: 5

Article number: e1007033

ISSN (Print): 1553-734X

Ratings:

Scopus rating (2019): CiteScore 7.3 SJR 2.91 SNIP 1.537

Original language: English

ASJC Scopus subject areas: Ecology, Evolution, Behavior and Systematics, Modelling and Simulation, Ecology, Molecular Biology, Genetics, Cellular and Molecular Neuroscience, Computational Theory and Mathematics

Electronic versions:

journal.pcbi.1007033

DOIs:

10.1371/journal.pcbi.1007033

URLs:

<http://urn.fi/URN:NBN:fi:tty-201906251906>

Bibliographical note

EXT="Martinez-Seara, Hector"

Source: Scopus

Source ID: 85066964975

Research output: Contribution to journal > Article > Scientific > peer-review

Search reliability and search efficiency of combined Lévy-Brownian motion: Long relocations mingled with thorough local exploration

A combined dynamics consisting of Brownian motion and Lévy flights is exhibited by a variety of biological systems performing search processes. Assessing the search reliability of ever locating the target and the search efficiency of doing so economically of such dynamics thus poses an important problem. Here we model this dynamics by a one-dimensional fractional Fokker-Planck equation combining unbiased Brownian motion and Lévy flights. By solving this equation both analytically and numerically we show that the superposition of recurrent Brownian motion and Lévy flights with stable exponent $\alpha < 1$, by itself implying zero probability of hitting a point on a line, leads to transient motion with finite probability of hitting any point on the line. We present results for the exact dependence of the values of both the search reliability and the search efficiency on the distance between the starting and target positions as well as the choice of the scaling exponent α of the Lévy flight component.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Research area: Computational Physics, Technische Universitat Munchen, Universita degli Studi di Padova, Italy, School of Mathematical Sciences, Institute for Physics and Astronomy, Universitat Potsdam

Contributors: Palyulin, V. V., Chechkin, A. V., Klages, R., Metzler, R.

Publication date: 8 Sep 2016

Peer-reviewed: Yes

Publication information

Journal: Journal of Physics A: Mathematical and Theoretical

Volume: 49

Issue number: 39

Article number: 394002

ISSN (Print): 1751-8113

Ratings:

Scopus rating (2016): CiteScore 3.7 SJR 0.935 SNIP 0.941

Original language: English

ASJC Scopus subject areas: Statistical and Nonlinear Physics, Statistics and Probability, Modelling and Simulation, Mathematical Physics, Physics and Astronomy(all)

Keywords: Brownian motion, first arrival, first passage, Lévy flights, random search process

DOIs:

10.1088/1751-8113/49/39/394002

URLs:

<https://arxiv.org/abs/1609.03822>

URLs:

<http://www.scopus.com/inward/record.url?scp=84989172145&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84989172145

Research output: Contribution to journal › Article › Scientific › peer-review

Spectral modeling of time series with missing data

Singular spectrum analysis is a natural generalization of principal component methods for time series data. In this paper we propose an imputation method to be used with singular spectrum-based techniques which is based on a weighted combination of the forecasts and hindcasts yield by the recurrent forecast method. Despite its ease of implementation, the obtained results suggest an overall good fit of our method, being able to yield a similar adjustment ability in comparison with the alternative method, according to some measures of predictive performance.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Research Community on Data-to-Decision (D2D), ISLA Campus Lisbon, Laureate International Universities, Pontificia Universidad Católica de Chile

Contributors: Rodrigues, P. C., de Carvalho, M.

Number of pages: 9

Pages: 4676-4684

Publication date: 1 Apr 2013

Peer-reviewed: Yes

Publication information

Journal: Applied Mathematical Modelling

Volume: 37

Issue number: 7

ISSN (Print): 0307-904X

Ratings:

Scopus rating (2013): CiteScore 3.8 SJR 1.074 SNIP 1.961

Original language: English

ASJC Scopus subject areas: Applied Mathematics, Modelling and Simulation

Keywords: Karhunen-Loève decomposition, Missing data, Singular spectrum analysis, Time series analysis

DOIs:

10.1016/j.apm.2012.09.040

URLs:

<http://www.scopus.com/inward/record.url?scp=84872620531&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84872620531

Research output: Contribution to journal › Article › Scientific › peer-review

Structural influence of gene networks on their inference: Analysis of C3NET

Background: The availability of large-scale high-throughput data possesses considerable challenges toward their functional analysis. For this reason gene network inference methods gained considerable interest. However, our current knowledge, especially about the influence of the structure of a gene network on its inference, is limited. **Results:** In this paper we present a comprehensive investigation of the structural influence of gene networks on the inferential characteristics of C3NET - a recently introduced gene network inference algorithm. We employ local as well as global performance metrics in combination with an ensemble approach. The results from our numerical study for various biological and synthetic network structures and simulation conditions, also comparing C3NET with other inference algorithms, lead a multitude of theoretical and practical insights into the working behavior of C3NET. In addition, in order to facilitate the practical usage of C3NET we provide an user-friendly R package, called *c3net*, and describe its functionality. It is available from <https://r-forge.r-project.org/projects/c3net> and from the CRAN package repository. **Conclusions:** The availability of gene network inference algorithms with known inferential properties opens a new era of large-scale screening experiments that could be equally beneficial for basic biological and biomedical research with auspicious prospects. The availability of our easy to use software package *c3net* may contribute to the popularization of such methods. **Reviewers:** This article was reviewed by Lev Klebanov, Joel Bader and Yuriy Gusev.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Research Community on Data-to-Decision (D2D), University of Cambridge, Computational Biology and Machine Learning Lab., Faculty of Medicine, Health and Life Sciences, Queen's University, Belfast, Northern Ireland, Cambridge Research Institute

Contributors: Altay, G., Emmert-Streib, F.
Publication date: 22 Jun 2011
Peer-reviewed: Yes

Publication information

Journal: Biology Direct

Volume: 6

Article number: 31

Ratings:

Scopus rating (2011): CiteScore 5.7 SJR 2.274 SNIP 0.857

Original language: English

ASJC Scopus subject areas: Agricultural and Biological Sciences(all), Biochemistry, Genetics and Molecular Biology(all), Immunology, Applied Mathematics, Modelling and Simulation, Ecology, Evolution, Behavior and Systematics

DOIs:

10.1186/1745-6150-6-31

URLs:

<http://www.scopus.com/inward/record.url?scp=79959327654&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 79959327654

Research output: Contribution to journal > Article > Scientific > peer-review

Target tracking via combination of particle filter and optimisation techniques

Particle filters (PFs) have been used for the nonlinear estimation for a number of years. However, they suffer from the impoverishment phenomenon. It is brought by resampling which intends to prevent particle degradation, and therefore becomes the inherent weakness of this technique. To solve the problem of sample impoverishment and to improve the performance of the standard particle filter we propose a modification to this method by adding a sampling mechanism inspired by optimisation techniques, namely, the pattern search, particle swarm optimisation, differential evolution and Nelder-Mead algorithms. In the proposed methods, the true state of the target can be better expressed by the optimised particle set and the number of meaningful particles can be grown significantly. The efficiency of the proposed particle filters is supported by a truck-trailer problem. Simulations show that the hybridised particle filter with Nelder-Mead search is better than other optimisation approaches in terms of particle diversity.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Signal Processing, University of Toledo, Bowling Green State University

Contributors: Hosseini, S. S. S., Jamali, M. M., Astola, J., Gorsevski, P. V.

Number of pages: 18

Pages: 212-229

Publication date: 2016

Peer-reviewed: Yes

Publication information

Journal: International Journal of Mathematical Modelling and Numerical Optimization

Volume: 7

Issue number: 2

ISSN (Print): 2040-3607

Ratings:

Scopus rating (2016): CiteScore 2.6 SJR 0.351 SNIP 0.935

Original language: English

ASJC Scopus subject areas: Numerical Analysis, Modelling and Simulation, Applied Mathematics

Keywords: Differential evolution, Nelder-Mead, Particle filter, Particle swarm optimisation, Pattern search, PSO, Target tracking

DOIs:

10.1504/IJMMNO.2016.077068

Source: Scopus

Source ID: 84990239582

Research output: Contribution to journal > Article > Scientific > peer-review

The Fisher-Snedecor F Distribution: A Simple and Accurate Composite Fading Model

We consider the use of the Fisher-Snedecor F distribution, which is defined as the ratio of two chi-squared variates, to model composite fading channels. In this context, the root-mean-square power of a Nakagami- m signal is assumed to be subject to variations induced by an inverse Nakagami- m random variable. Comparisons with physical channel data demonstrate that the proposed composite fading model provides as good, and in most cases better, fit to the data compared to the generalized- K composite fading model. Motivated by this result, simple novel expressions are derived for

the key statistical metrics and performance measures of interest.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Electronics and Communications Engineering, Research group: Wireless Communications and Positioning , Queen's University, Belfast, Northern Ireland, Aristotle University of Thessaloniki

Contributors: Yoo, S. K., Cotton, S. L., Sofotasios, P. C., Matthaiou, M., Valkama, M., Karagiannidis, G. K.

Number of pages: 4

Pages: 1661-1664

Publication date: 1 Jul 2017

Peer-reviewed: Yes

Publication information

Journal: IEEE Communications Letters

Volume: 21

Issue number: 7

ISSN (Print): 1089-7798

Ratings:

Scopus rating (2017): CiteScore 4.4 SJR 0.589 SNIP 1.38

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Computer Science Applications, Electrical and Electronic Engineering

Keywords: Composite fading, inverse Nakagami-m distribution, Nakagami-m fading, shadowing.

DOIs:

10.1109/LCOMM.2017.2687438

Source: Scopus

Source ID: 85029841155

Research output: Contribution to journal > Article > Scientific > peer-review

Topological patterns for scalable representation and analysis of dataflow graphs

Tools for designing signal processing systems with their semantic foundation in dataflow modeling often use high-level graphical user interfaces (GUIs) or text based languages that allow specifying applications as directed graphs. Such graphical representations serve as an initial reference point for further analysis and optimizations that lead to platform-specific implementations. For large-scale applications, the underlying graphs often consist of smaller substructures that repeat multiple times. To enable more concise representation and direct analysis of such substructures in the context of high level DSP specification languages and design tools, we develop the modeling concept of topological patterns, and propose ways for supporting this concept in a high-level language. We augment the dataflow interchange format (DIF) language-a language for specifying DSP-oriented dataflow graphs-with constructs for supporting topological patterns, and we show how topological patterns can be effective in various aspects of embedded signal processing design flows using specific application examples.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), University of Maryland, National Instruments, Air Force Research Laboratory Information Directorate, Department of Electrical and Computer Engineering

Contributors: Sane, N., Kee, H., Seetharaman, G., Bhattacharyya, S. S.

Number of pages: 16

Pages: 229-244

Publication date: 2011

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 65

Issue number: 2

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2011): CiteScore 1.8 SJR 0.248 SNIP 0.707

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Dataflow graphs, High-level languages, Model-based design, Signal processing systems, Topological patterns

DOIs:

10.1007/s11265-011-0610-1

URLs:

<http://www.scopus.com/inward/record.url?scp=84905269801&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84905269801

Research output: Contribution to journal > Article > Scientific > peer-review

Toward Efficient Execution of RVC-CAL Dataflow Programs on Multicore Platforms

The increasing number of cores in System on Chips (SoC) has introduced challenges in software parallelization. As an answer to this, the dataflow programming model offers a concurrent and reusability promoting approach for describing applications. In this work, a runtime for executing Dataflow Process Networks (DPN) on multicore platforms is proposed. The main difference between this work and existing methods is letting the operating system perform Central processing unit (CPU) load-balancing freely, instead of limiting thread migration between processing cores through CPU affinity. The proposed runtime is benchmarked on desktop and server multicore platforms using five different applications from video coding and telecommunication domains. The results show that the proposed method offers significant improvements over the state-of-art, in terms of performance and reliability.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Pervasive Computing, Research area: Computer engineering, Univ of Oulu

Contributors: Hautala, I., Boutellier, J., Nyländén, T., Silvén, O.

Number of pages: 11

Pages: 1507-1517

Publication date: Nov 2018

Peer-reviewed: Yes

Early online date: 9 Feb 2018

Publication information

Journal: Journal of Signal Processing Systems

Volume: 90

Issue number: 11

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2018): CiteScore 1.7 SJR 0.203 SNIP 0.61

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Dataflow Process Networks, Multicore, Orcc, RVC-CAL

DOIs:

10.1007/s11265-018-1339-x

Source: Scopus

Source ID: 85041532591

Research output: Contribution to journal > Article > Scientific > peer-review

Towards generic embedded multiprocessing for RVC-CAL dataflow programs

Dataflow languages enable describing signal processing applications in a platform independent fashion, which makes them attractive in today's multiprocessing era. RVC-CAL is a dynamic dataflow language that enables describing complex data-dependent programs such as video decoders. To this date, design automation toolchains for RVC-CAL have enabled creating workstation software, dedicated hardware and embedded application specific multiprocessor implementations out of RVC-CAL programs. However, no solution has been presented for executing RVC-CAL applications on generic embedded multiprocessing platforms. This paper presents a dataflow-based multiprocessor communication model, an architecture prototype that uses it and an automated toolchain for instantiating such a platform and the software for it. The complexity of the platform increases linearly as the number of processors is increased. The experiments in this paper use several instances of the proposed platform, with different numbers of processors. An MPEG-4 video decoder is mapped to the platform and executed on it. Benchmarks are performed on an FPGA board.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Signal Processing Research Community (SPRC), Dept. of Computer Science and Engineering, Univ of Oulu

Contributors: Boutellier, J., Silvén, O.

Number of pages: 6

Pages: 137-142
Publication date: Nov 2013
Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

Volume: 73

Issue number: 2

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2013): CiteScore 2.1 SJR 0.254 SNIP 0.866

Original language: English

ASJC Scopus subject areas: Hardware and Architecture, Information Systems, Signal Processing, Theoretical Computer Science, Control and Systems Engineering, Modelling and Simulation

Keywords: Data flow computing, Design automation, Multiprocessor interconnection

DOIs:

10.1007/s11265-013-0737-3

URLs:

<http://www.scopus.com/inward/record.url?scp=84881476500&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84881476500

Research output: Contribution to journal > Article > Scientific > peer-review

Urothelial cancer gene regulatory networks inferred from large-scale RNAseq, Bead and Oligo gene expression data

Background: Urothelial pathogenesis is a complex process driven by an underlying network of interconnected genes. The identification of novel genomic target regions and gene targets that drive urothelial carcinogenesis is crucial in order to improve our current limited understanding of urothelial cancer (UC) on the molecular level. The inference of genome-wide gene regulatory networks (GRN) from large-scale gene expression data provides a promising approach for a detailed investigation of the underlying network structure associated to urothelial carcinogenesis. **Methods:** In our study we inferred and compared three GRNs by the application of the BC3Net inference algorithm to large-scale transitional cell carcinoma gene expression data sets from Illumina RNAseq (179 samples), Illumina Bead arrays (165 samples) and Affymetrix Oligo microarrays (188 samples). We investigated the structural and functional properties of GRNs for the identification of molecular targets associated to urothelial cancer. **Results:** We found that the urothelial cancer (UC) GRNs show a significant enrichment of subnetworks that are associated with known cancer hallmarks including cell cycle, immune response, signaling, differentiation and translation. Interestingly, the most prominent subnetworks of co-located genes were found on chromosome regions 5q31.3 (RNAseq), 8q24.3 (Oligo) and 1q23.3 (Bead), which all represent known genomic regions frequently deregulated or aberrated in urothelial cancer and other cancer types. Furthermore, the identified hub genes of the individual GRNs, e.g., *HID1/DMC1* (tumor development), *RNF17/TDRD4* (cancer antigen) and *CYP4A11* (angiogenesis/ metastasis) are known cancer associated markers. The GRNs were highly dataset specific on the interaction level between individual genes, but showed large similarities on the biological function level represented by subnetworks. Remarkably, the RNAseq UC GRN showed twice the proportion of significant functional subnetworks. Based on our analysis of inferential and experimental networks the Bead UC GRN showed the lowest performance compared to the RNAseq and Oligo UC GRNs. **Conclusion:** To our knowledge, this is the first study investigating genome-scale UC GRNs. RNAseq based gene expression data is the data platform of choice for a GRN inference. Our study offers new avenues for the identification of novel putative diagnostic targets for subsequent studies in bladder tumors.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Signal Processing, BioMediTech, Research Community on Data-to-Decision (D2D), BioMediTech - Institute of Biosciences and Medical Technology, Queen's University, Belfast, Northern Ireland

Contributors: Matos Simoes, R. D., Dalleau, S., Williamson, K. E., Emmert-Streib, F.

Publication date: 14 May 2015

Peer-reviewed: Yes

Publication information

Journal: BMC Systems Biology

Volume: 9

Article number: 21

ISSN (Print): 1752-0509

Ratings:

Scopus rating (2015): CiteScore 5.4 SJR 1.549 SNIP 0.89

Original language: English

ASJC Scopus subject areas: Molecular Biology, Structural Biology, Applied Mathematics, Modelling and Simulation, Computer Science Applications

Keywords: BC3Net, Computational genomics, Gene regulatory network, Urothelial cancer

DOIs:

10.1186/s12918-015-0165-z

Source: Scopus

Source ID: 84931068065

Research output: Contribution to journal › Article › Scientific › peer-review

Using building simulation to model the drying of flooded building archetypes

With a changing climate, London is expected to experience more frequent periods of intense rainfall and tidal surges, leading to an increase in the risk of flooding. This paper describes the simulation of the drying of flooded building archetypes representative of the London building stock using the EnergyPlus-based hygrothermal tool 'University College London-Heat and Moisture Transfer (UCL-HAMT)' in order to determine the relative drying rates of different built forms and envelope designs. Three different internal drying scenarios, representative of conditions where no professional remediation equipment is used, are simulated. A mould model is used to predict the duration of mould growth risk following a flood on the internal surfaces of the different building types. Heating properties while keeping windows open dried dwellings fastest, while purpose built flats and buildings with insulated cavity walls were found to dry slowest.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: University College London

Contributors: Taylor, J., Biddulph, P., Davies, M., Ridley, I., Mavrogianni, A., Oikonomou, E., Lai, K. M.

Number of pages: 22

Pages: 119-140

Publication date: 1 Mar 2013

Peer-reviewed: Yes

Publication information

Journal: JOURNAL OF BUILDING PERFORMANCE SIMULATION

Volume: 6

Issue number: 2

ISSN (Print): 1940-1493

Ratings:

Scopus rating (2013): CiteScore 4 SJR 1.006 SNIP 1.246

Original language: English

ASJC Scopus subject areas: Architecture , Building and Construction, Modelling and Simulation, Computer Science Applications

Keywords: flood, hygrothermal, mould

DOIs:

10.1080/19401493.2012.703243

URLs:

<http://www.scopus.com/inward/record.url?scp=84871083708&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84871083708

Research output: Contribution to journal › Article › Scientific › peer-review

Vehicle Attribute Recognition by Appearance: Computer Vision Methods for Vehicle Type, Make and Model Classification

This paper studies vehicle attribute recognition by appearance. In the literature, image-based target recognition has been extensively investigated in many use cases, such as facial recognition, but less so in the field of vehicle attribute recognition. We survey a number of algorithms that identify vehicle properties ranging from coarse-grained level (vehicle type) to fine-grained level (vehicle make and model). Moreover, we discuss two alternative approaches for these tasks, including straightforward classification and a more flexible metric learning method. Furthermore, we design a simulated real-world scenario for vehicle attribute recognition and present an experimental comparison of the two approaches.

General information

Publication status: E-pub ahead of print

MoE publication type: A1 Journal article-refereed

Organisations: Computing Sciences, Research group: Multimedia Research Group - MRG

Contributors: Ni, X., Huttunen, H.

Publication date: 2020

Peer-reviewed: Yes

Publication information

Journal: Journal of Signal Processing Systems

ISSN (Print): 1939-8018

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Keywords: Image classification, Metric learning, Vehicle attribute recognition

Electronic versions:

Ni-Huttunen2020_Article_VehicleAttributeRecognitionByA

DOIs:

10.1007/s11265-020-01567-6

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202007076341>

Source: Scopus

Source ID: 85086837300

Research output: Contribution to journal > Article > Scientific > peer-review

Very sharp diffraction peak in nonglass-forming liquid with the formation of distorted tetraclusters

Understanding the liquid structure provides information that is crucial to uncovering the nature of the glass-liquid transition. We apply an aerodynamic levitation technique and high-energy X-rays to liquid (l)-Er₂O₃ to discover its structure. The sample densities are measured by electrostatic levitation at the International Space Station. Liquid Er₂O₃ displays a very sharp diffraction peak (principal peak). Applying a combined reverse Monte Carlo – molecular dynamics approach, the simulations produce an Er–O coordination number of 6.1, which is comparable to that of another nonglass-forming liquid, l-ZrO₂. The atomic structure of l-Er₂O₃ comprises distorted OEr₄ tetraclusters in nearly linear arrangements, as manifested by a prominent peak observed at ~180° in the Er–O–Er bond angle distribution. This structural feature gives rise to long periodicity corresponding to the sharp principal peak in the X-ray diffraction data. A persistent homology analysis suggests that l-Er₂O₃ is homologically similar to the crystalline phase. Moreover, electronic structure calculations show that l-Er₂O₃ has a modest band gap of 0.6 eV that is significantly reduced from the crystalline phase due to the tetracluster distortions. The estimated viscosity is very low above the melting point for l-ZrO₂, and the material can be described as an extremely fragile liquid.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Physics, Research group: Materials and Molecular Modeling, Japan Aerospace Exploration Agency, University of the Ryukyus, National Institute for Materials Science (NIMS), NIMS, Japan Science and Technology Agency, Japan Synchrotron Radiation Research Institute, Institute for Integrated Radiation and Nuclear Science, Kyoto University, Norwegian Univ. of Sci. and Technol., JAXA Institute of Space and Astronautical Science, SOKEN-DAI (The Graduate University for Advanced Studies), Hiroasaki University, Hakodate College, Tohoku University, Advanced Engineering Services Co., Ltd., RIKEN Center for Integrative Medical Sciences, Kyoto University Institute for Advanced Study

Contributors: Koyama, C., Tahara, S., Kohara, S., Onodera, Y., Småbråten, D. R., Selbach, S. M., Akola, J., Ishikawa, T., Masuno, A., Mizuno, A., Okada, J. T., Watanabe, Y., Nakata, Y., Ohara, K., Tamaru, H., Oda, H., Obayashi, I., Hiraoka, Y., Sakata, O.

Number of pages: 11

Publication date: 2020

Peer-reviewed: Yes

Publication information

Journal: NPG ASIA MATERIALS

Volume: 12

Issue number: 1

Article number: 43

ISSN (Print): 1884-4049

Original language: English

ASJC Scopus subject areas: Modelling and Simulation, Materials Science(all), Condensed Matter Physics

Electronic versions:

Very sharp diffraction peak 2020

DOIs:

10.1038/s41427-020-0220-0

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202007026305>

Source: Scopus

Source ID: 85085865321

Research output: Contribution to journal > Article > Scientific > peer-review

Workplace performance of a loose-fitting powered air purifying respirator during nanoparticle synthesis

Nanoparticle (particles with diameter ≤ 100 nm) exposure is recognized as a potentially harmful size fraction for pulmonary particle exposure. During nanoparticle synthesis, the number concentrations in the process room may exceed $10 \times 10^6 \text{ cm}^{-3}$. During such conditions, it is essential that the occupants in the room wear highly reliable high-performance respirators to prevent inhalation exposure. Here we have studied the in-use program protection factor (PPF) of loose-fitting powered air purifying respirators, while workers were coating components with TiO_2 or Cu_xO_y nanoparticles under a hood using a liquid flame spray process. The PPF was measured using condensation particle counters, an electrical low pressure impactor, and diffusion chargers. The room particle concentrations varied from 4×10^6 to $40 \times 10^6 \text{ cm}^{-3}$, and the count median aerodynamic diameter ranged from 32 to 180 nm. Concentrations inside the respirator varied from 0.7 to 7.2 cm^{-3} . However, on average, tidal breathing was assumed to increase the respirator concentration by 2.3 cm^{-3} . The derived PPF exceeded 1.1×10^6 , which is more than 40×10^3 times the respirator assigned protection factor. We were unable to measure clear differences in the PPF of respirators with old and new filters, among two male and one female user, or assess most penetrating particle size. This study shows that the loose-fitting powered air purifying respirator provides very efficient protection against nanoparticle inhalation exposure if used properly.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Department of Physics, Research group: Aerosol Synthesis, National Research Centre for the Working Environment, Finnish Institute of Occupational Health, Helsinki University, TNO

Contributors: Koivisto, A. J., Aromaa, M., Koponen, I. K., Fransman, W., Jensen, K. A., Mäkelä, J. M., Hämeri, K. J.

Publication date: 9 Apr 2015

Peer-reviewed: Yes

Publication information

Journal: Journal of Nanoparticle Research

Volume: 17

Issue number: 4

ISSN (Print): 1388-0764

Ratings:

Scopus rating (2015): CiteScore 3.8 SJR 0.568 SNIP 0.725

Original language: English

ASJC Scopus subject areas: Atomic and Molecular Physics, and Optics, Condensed Matter Physics, Modelling and Simulation, Chemistry(all), Materials Science(all), Bioengineering

Keywords: Aerosol, Air purifying respirator, Filtration, Occupational safety, Protection factor, Respirator performance

DOIs:

10.1007/s11051-015-2990-9

URLs:

<http://www.scopus.com/inward/record.url?scp=84927730047&partnerID=8YFLogxK> (Link to publication in Scopus)

Bibliographical note

EXT="Koivisto, Antti J."

Source: Scopus

Source ID: 84927730047

Research output: Contribution to journal › Article › Scientific › peer-review

A simulation case study of production planning and control in printed wiring board manufacturing

Production planning and control in printed wiring board (PWB) manufacturing is becoming more difficult as PWB's technology is developing and the production routings become more complex. Simultaneously, the strategic importance of delivery accuracy, short delivery times, and production flexibility is increasing with the highly fluctuating demand and short product life cycles of end products. New principles, that minimize throughput time while guaranteeing excellent customer service and adequate capacity utilization, are needed for production planning and control. Simulation is needed in order to develop the new principles and test their superiority. This paper presents an ongoing simulation product that aims at developing the production planning and control of a PWB manufacturer. In the project, a discrete event simulation model is built of a pilot case factory. The model is used for comparing the effect of scheduling, queuing rules, buffer policies, and lot sizes on customer service and cost efficiency.

General information

Publication status: Published

MoE publication type: Not Eligible

Organisations: Industrial Engineering and Management, Aalto University, TAI Research Centre

Contributors: Korhonen, H. M. E., Heikkilä, J., Törnwall, J. M.

Number of pages: 4

Pages: 844-847
Publication date: 1 Dec 2001
Peer-reviewed: Yes

Publication information

Journal: Winter Simulation Conference Proceedings

Volume: 2

ISSN (Print): 0275-0708

Ratings:

Scopus rating (2001): SJR 0.377

Original language: English

ASJC Scopus subject areas: Chemical Health and Safety, Software, Safety, Risk, Reliability and Quality, Applied Mathematics, Modelling and Simulation

URLs:

<http://www.scopus.com/inward/record.url?scp=0035708229&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 0035708229

Research output: Contribution to journal › Conference article › Scientific › peer-review

Model for evaluating additive manufacturing feasibility in end-use production

In practical design work, a designer needs to consider the feasibility of a part for a manufacturing using additive manufacturing (AM) instead of conventional manufacturing (CM) technology. Traditionally and by default parts are assumed to be manufactured using CM and using AM as an alternative need to be justified. AM is currently often a more expensive manufacturing method than CM, but its employment can be justified due to number of reasons: improved part features, faster manufacturing time and lower cost. Improved part features means usually reduced mass or complex shape. However, in low volume production lower manufacturing time and lower part cost may rise to the most important characteristics. In this paper, we present a practical feasibility model, which analyses the added value of using AM for manufacturing. The approach is demonstrated in the paper on four specific parts. They represent real industrial design tasks that are ordered from an engineering office company. These parts were manufactured by Selective Laser Mating (SLM) technology and the original design done for conventional manufacturing is also presented and used for comparison purpose.

General information

Publication status: Published

MoE publication type: A1 Journal article-refereed

Organisations: Automation Technology and Mechanical Engineering, Research area: Design, Development and LCM,

Research area: Manufacturing and Automation, Enmac Ltd

Contributors: Ahtiluoto, M., Ellman, A., Coatanea, E.

Number of pages: 10

Pages: 799-808

Publication date: 2019

Peer-reviewed: Yes

Publication information

Journal: Proceedings of the International Conference on Engineering Design, ICED

Volume: 1

Issue number: 1

ISSN (Print): 2220-4334

Original language: English

ASJC Scopus subject areas: Engineering (miscellaneous), Industrial and Manufacturing Engineering, Modelling and Simulation

Keywords: 3D printing, Additive Manufacturing, Decision making, Design for Additive Manufacturing (DfAM)

DOIs:

10.1017/dsi.2019.84

Source: Scopus

Source ID: 85079820268

Research output: Contribution to journal › Conference article › Scientific › peer-review

Guest Editorial: Implementation Issues in System-on-Chip

General information

Publication status: Published

MoE publication type: B1 Article in a scientific magazine

Organisations: Electronics and Communications Engineering, Research group: System-on-Chip for GNSS, Wireless Communications and Cyber-Physical Embedded Computing, Tallinn University of Technology

Contributors: Ellervee, P., Nurmi, J.
Number of pages: 2
Pages: 269-270
Publication date: 1 Jun 2017
Peer-reviewed: No

Publication information

Journal: Journal of Signal Processing Systems

Volume: 87

Issue number: 3

ISSN (Print): 1939-8018

Ratings:

Scopus rating (2017): CiteScore 1.7 SJR 0.216 SNIP 0.632

Original language: English

ASJC Scopus subject areas: Control and Systems Engineering, Theoretical Computer Science, Signal Processing, Information Systems, Modelling and Simulation, Hardware and Architecture

Electronic versions:

Guest Editorial SOC2014_v1. Embargo ended: 6/04/18

DOIs:

10.1007/s11265-017-1242-x

URLs:

<http://urn.fi/URN:NBN:fi:tty-201802141232>. Embargo ended: 6/04/18

Source: Scopus

Source ID: 85017177298

Research output: Contribution to journal > Editorial > Scientific

Acoustic Modelling

Let us examine the behaviour of sound in a gas or in a liquid medium. From a physical point of view, the sound we hear is created by the pressure change in the medium surrounding us that is sensed by our ears. The equations describing the behaviour of a liquid or a gas are based on well-known equations of fluid mechanics. Therefore in acoustics, they are often referred to as fluids. In the following sections we present a simple wave equation, which is the simplest of (linear) equations used to model acoustical phenomena. Even though the wave equation is quite a simplified model, it has proven to be extremely useful for describing the behaviour of sound in the most common fluid we face every day, namely air.

General information

Publication status: Published

MoE publication type: A3 Part of a book or another research book

Organisations: Department of Mathematics, Research group: MAT Intelligent Information Systems Laboratory, Research group: MAT Mathematical and semantic modelling, Tampere Univ Technol, Tampere University of Technology

Contributors: Pohjolainen, S., Suutala, A.

Number of pages: 21

Pages: 185-205

Publication date: 30 Jun 2016

Host publication information

Title of host publication: Mathematical Modelling

Place of publication: Switzerland

Publisher: Springer

Editor: Pohjolainen, S.

ISBN (Print): 978-3-319-27834-6

ISBN (Electronic): 978-3-319-27836-0

ASJC Scopus subject areas: Applied Mathematics, Modelling and Simulation, Acoustics and Ultrasonics

DOIs:

10.1007/978-3-319-27836-0_11

Bibliographical note

INT=mat,"Suutala, Antti"

Research output: Chapter in Book/Report/Conference proceeding > Chapter > Scientific > peer-review

Two models for hydraulic cylinders in flexible multibody simulations

In modelling hydraulic cylinders interaction between the structural response and the hydraulic system needs to be taken into account. In this chapter two approaches for modelling flexible multibody systems coupled with hydraulic actuators i.e. cylinders are presented and compared. These models are the truss-elementlike cylinder and bending flexible cylinder models. The bending flexible cylinder element is a super-element combining the geometrically exact Reissner-beam element, the C^1 -continuous slide-spring element needed for the telescopic movement and the hydraulic fluid field. Both

models are embedded with a friction model based on a bristle approach. The models are implemented in a finite element environment. In time the coupled stiff differential equation system is integrated using the L-stable Rosenbrock method.

General information

Publication status: Published

MoE publication type: A3 Part of a book or another research book

Organisations: Department of Civil Engineering, Research group: Structural Mechanics, Department of Mechanical Engineering and Industrial Systems, Research area: Applied Mechanics, FS Dynamics Finland Oy Ab

Contributors: Ylinen, A., Mäkinen, J., Kouhia, R.

Number of pages: 31

Pages: 463-493

Publication date: 2016

Host publication information

Title of host publication: Computational Methods for Solids and Fluids : Multiscale Analysis, Probability Aspects and Model Reduction

Publisher: Springer

ISBN (Print): 978-3-319-27994-7

ISBN (Electronic): 978-3-319-27996-1

Publication series

Name: Computational Methods in Applied Sciences

Volume: 41

ISSN (Print): 1871-3033

ASJC Scopus subject areas: Computational Mathematics, Modelling and Simulation, Fluid Flow and Transfer Processes, Computer Science Applications, Civil and Structural Engineering, Electrical and Electronic Engineering, Biomedical Engineering

DOIs:

10.1007/978-3-319-27996-1_17

Bibliographical note

JUFOID=79940

EXT="Ylinen, Antti"

Source: Scopus

Source ID: 84964233721

Research output: Chapter in Book/Report/Conference proceeding › Chapter › Scientific › peer-review

Action and power efficiency in self-organization: The case for growth efficiency as a cellular objective in *Escherichia coli*

Complex systems of different nature self-organize using common mechanisms. One of those is increase of their efficiency. The level of organization of complex systems of different nature can be measured as increased efficiency of the product of time and energy for an event, which is the amount of physical action consumed by it. Here we apply a method developed in physics to study the efficiency of biological systems. The identification of cellular objectives is one of the central topics in the research of microbial metabolic networks. In particular, the information about a cellular objective is needed in flux balance analysis which is a commonly used constrained-based metabolic network analysis method for the prediction of cellular phenotypes. The cellular objective may vary depending on the organism and its growth conditions. It is probable that nutritionally scarce conditions are very common in the nature, and, in order to survive in those conditions, cells exhibit various highly efficient nutrient-processing systems like enzymes. In this study, we explore the efficiency of a metabolic network in transformation of substrates to new biomass, and we introduce a new objective function simulating growth efficiency. We are searching for general principles of self-organization across systems of different nature. The objective of increasing efficiency of physical action has been identified previously as driving systems toward higher levels of self-organization. The flow agents in those networks are driven toward their natural state of motion, which is governed by the principle of least action in physics. We connect this to a power efficiency principle. Systems structure themselves in a way to decrease the average amount of action or power per one event in the system. In this particular example, action efficiency is examined in the case of growth efficiency of *E. coli*. We derive the expression for growth efficiency as a special case of action (power) efficiency to justify it through first principles in physics. Growth efficiency as a cellular objective of *E. coli* coincides with previous research on complex systems and is justified by first principles in physics. It is expected and confirmed outcome of this work. We examined the properties of growth efficiency using a metabolic model for *Escherichia coli*. We found that the maximal growth efficiency is obtained at a finite nutrient uptake rate. The rate is substrate dependent and it typically does not exceed 20 mmol/h/gDW. We further examined whether the maximal growth efficiency could serve as a cellular objective function in metabolic network analysis and found that cellular growth in batch cultivation can be predicted reasonably well under this assumption. The fit to experimental data was found slightly better than with the commonly used objective function of maximal growth rate. Based on our results, we suggest that the maximal growth efficiency can be considered a plausible optimization criterion in metabolic modeling for *E. coli*. In the future, it would be interesting to study growth efficiency as an objective also in other cellular systems and under different cultivation conditions.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: BioMediTech, Wireless Innovation Laboratory at Worcester Polytechnic Institute, Assumption College, Tufts University, Complex Systems Center, University of Vermont

Contributors: Georgiev, G. Y., Aho, T., Kesseli, J., Yli-Harja, O., Kauffman, S. A.

Number of pages: 16

Pages: 229-244

Publication date: 2019

Host publication information

Title of host publication: Evolution, Development and Complexity - Multiscale Evolutionary Models of Complex Adaptive Systems

Publisher: Springer

Editors: Flores Martinez, C. L., Georgiev, G. Y., Smart, J. M., Price, M. E.

ISBN (Print): 9783030000745

Publication series

Name: Springer Proceedings in Complexity

ISSN (Print): 2213-8684

ISSN (Electronic): 2213-8692

ASJC Scopus subject areas: Applied Mathematics, Modelling and Simulation, Computer Science Applications

Keywords: Action efficiency, Constraint-based modeling, Metabolism, Microorganism, Principle of least action

DOIs:

10.1007/978-3-030-00075-2_8

Bibliographical note

jufoid=84878

Source: Scopus

Source ID: 85071889407

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

A framework for building behavioral models for design-stage failure identification using dimensional analysis

In this paper, a design-stage failure identification framework is proposed using a modeling and simulation approach based on Dimensional Analysis and qualitative physics. The proposed framework is intended to provide a new approach to model the behavior in the Functional-Failure Identification and Propagation (FFIP) framework, which estimates potential faults and their propagation paths under critical event scenarios. The initial FFIP framework is based on combining hierarchical system models of functionality and configuration, with behavioral simulation and qualitative reasoning. This paper proposes to develop a behavioral model derived from information available at the configuration level. Specifically, the new behavioral model uses design variables, which are associated with units and quantities (i.e., Mass, Length, Time, etc...). The proposed framework continues the work to allow the analysis of functional failures and fault propagation at a highly abstract system concept level before any potentially high-cost design commitments are made. The main contribution in this paper consists of developing component behavioral models based on the combination of fundamental design variables used to describe components and their units or quantities, more precisely describing components' behavior. Copyright © 2010 by ASME.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Oregon State University, Helsinki University of Technology, Aalto University

Contributors: Coatanéa, E., Ritola, T., Tumer, I. Y., Jensen, D.

Number of pages: 11

Pages: 591-601

Publication date: 2010

Host publication information

Title of host publication: Proceedings of the ASME Design Engineering Technical Conference

Volume: 5

Publisher: AMER SOC MECHANICAL ENGINEERS

ISBN (Print): 978-0-7918-4413-7

ASJC Scopus subject areas: Mechanical Engineering, Computer Graphics and Computer-Aided Design, Computer Science Applications, Modelling and Simulation

DOIs:

10.1115/DETC2010-28864

URLs:

<http://www.scopus.com/inward/record.url?scp=80055023958&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: WOS

Source ID: 000320567700053

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

An image generator platform to improve cell tracking algorithms simulation of objects of various morphologies, kinetics and clustering

Several major advances in Cell and Molecular Biology have been made possible by recent advances in livecell microscopy imaging. To support these efforts, automated image analysis methods such as cell segmentation and tracking during a time-series analysis are needed. To this aim, one important step is the validation of such image processing methods. Ideally, the "ground truth" should be known, which is possible only by manually labelling images or in artificially produced images. To simulate artificial images, we have developed a platform for simulating biologically inspired objects, which generates bodies with various morphologies and kinetics and, that can aggregate to form clusters. Using this platform, we tested and compared four tracking algorithms: Simple Nearest-Neighbour (NN), NN with Morphology and two DBSCAN-based methods. We show that Simple NN works well for small object velocities, while the others perform better on higher velocities and when clustering occurs. Our new platform for generating new benchmark images to test image analysis algorithms is openly available at (<http://griduni.uninova.pt/ClusterGen/ClusterGen-v1.0.zip>).

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Department of Signal Processing, Research group: Laboratory of Biosystem Dynamics-LBD, Campus FCT-UNL

Contributors: Canelas, P., Martins, L., Mora, A., S. Ribeiro, A., Fonseca, J.

Number of pages: 12

Pages: 44-55

Publication date: 2016

Host publication information

Title of host publication: SIMULTECH 2016 - Proceedings of the 6th International Conference on Simulation and Modeling Methodologies, Technologies and Applications

Publisher: SCITEPRESS

ISBN (Electronic): 9789897581991

ASJC Scopus subject areas: Modelling and Simulation, Computational Theory and Mathematics, Computer Science Applications, Information Systems

Keywords: Cell Tracking, Cluster Tracking, Microscopy, Synthetic Time-lapse Image Simulation

Source: Scopus

Source ID: 84991211006

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

An origami inspired reconfigurable spiral antenna

Modern day systems often require reconfigurability in the operating parameters of the transmit and receive antennas, such as the resonant frequency, radiation pattern, impedance, or polarization. In this work a novel approach to antenna reconfigurability is presented by integrating antennas with the ancient art of origami. The proposed antenna consists of an inkjet printed center-fed spiral antenna, which is designed to resonate at 1.0GHz and have a reconfigurable radiation pattern while maintaining the 1.0GHz resonance with little variation in input impedance. When flat, the antenna is a planar spiral exhibiting a bidirectional radiation pattern. By a telescoping action, the antenna can be reconfigured into a conical spiral with a directional pattern and higher gain, which gives the antenna a large front-to-back ratio. Construction of the antenna in this manner allows for a simple, lightweight, transportable antenna that can expand to specifications in the field.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Sensing Systems for Wireless Medicine (MediSense), Georgia Institute of Technology

Contributors: Saintsing, C. D., Cook, B. S., Tentzeris, M. M.

Publication date: 2014

Host publication information

Title of host publication: 38th Mechanisms and Robotics Conference

Volume: 5B

Publisher: The American Society of Mechanical Engineers ASME

ISBN (Electronic): 9780791846377

ASJC Scopus subject areas: Modelling and Simulation, Mechanical Engineering, Computer Science Applications, Computer Graphics and Computer-Aided Design

DOIs:

10.1115/DETC201435353

URLs:

<http://www.scopus.com/inward/record.url?scp=84926029890&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84926029890

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Applying SCRUM in an OSS development process: An empirical evaluation

Open Source Software development often resembles Agile models. In this paper, we report about our experience in using SCRUM for the development of an Open Source Software Java tool. With this work, we aim at answering the following research questions: 1) is it possible to switch successfully to the SCRUM methodology in an ongoing Open Source Software development process? 2) is it possible to apply SCRUM when the developers are geographically distributed? 3) does SCRUM help improve the quality of the product and the productivity of the process? We answer to these questions by identifying a set of measures and by comparing the data we collected before and after the introduction of SCRUM. The results seem to show that SCRUM can be introduced and used in an ongoing geographically distributed Open Source Software process and that it helps control the development process better.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Università degli Studi Dell'Insubria, Former organisation of the author

Contributors: Lavazza, L., Morasca, S., Taibi, D., Tosi, D.

Number of pages: 13

Pages: 147-159

Publication date: 2010

Host publication information

Title of host publication: Agile Processes in Software Engineering and Extreme Programming - 11th International Conference, XP 2010, Proceedings

Volume: 48 LNBIP

Publisher: Springer Verlag

ISBN (Print): 9783642130533

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 48 LNBIP

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management

Keywords: Agile methods, Open-source software, OSS, Process improvement evaluation, SCRUM

DOIs:

10.1007/978-3-642-13054-0_11

URLs:

<http://www.scopus.com/inward/record.url?scp=84876211466&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84876211466

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Bringing stimulated ideation in a web environment: Students' evaluations of a basic software release

Previous studies have demonstrated that creative design activities benefit from stimuli and that textual prompts might extend the exploration of the design space. However, the number of stimuli to conduct a wide exploration is large and the support of an ICT platform results necessary to manage a creative task effectively because of the presumably large number of generated ideas. Within a project named Startled, a very simple first release of a web application has been developed that supports ideation activities by means of stimuli. Dozens of students enrolled in different courses and Universities have tested the platform and answered a questionnaire, which aimed to elucidate their self-efficacy, perceived workload, ease of use and utility of the present version of the web application. The outcomes show, beyond few differences between students with diverse backgrounds, a majority of neutral and slightly positive answers. The results are not fully satisfying and the authors intend to make the ICT-supported creative tool more guided, user-friendly and intuitive.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Computing Sciences, Free University of Bolzano-Bozen, CNR-INO

Contributors: Borgianni, Y., Lenarduzzi, V., Rotini, F., Taibi, D.

Publication date: 2018

Host publication information

Title of host publication: ICDC 2018 - 5th International Conference on Design Creativity, Conference Proceedings
Publisher: DESIGN SOCIETY
Editors: Dekoninck, E., Wodehouse, A., Snider, C., Georgiev, G., Cascini, G.
ISBN (Electronic): 9781904670834

Publication series

Name: Proceedings of the International Conference on Engineering Design, ICED
ISSN (Print): 2220-4334
ISSN (Electronic): 2220-4342
ASJC Scopus subject areas: Engineering (miscellaneous), Industrial and Manufacturing Engineering, Modelling and Simulation
Keywords: New product benefits, Questionnaires, Stimulated ideation, Web application
Source: Scopus
Source ID: 85072785974
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Business Model Innovation of Startups Developing Multisided Digital Platforms

Platforms are defined as multisided marketplaces with business models that enable producers and users to create value together by interacting with each other. In recent years, platforms have benefited from the advances of digitalization. Hence, digital platforms continue to triumph, and continue to be attractive for companies, also for startups. In this paper, we first explore the research of platforms compared to digital platforms. We then proceed to analyze digital platforms as business models, in the context of startups looking for business model innovation. Based on interviews conducted at a technology startup event in Finland, we analyzed how 34 startups viewed their business model innovations. Using the 10 sub-constructs from the business model innovation scale by Clauss in 2016, we found out that the idea of business model innovation resonated with startups, as all of them were able to identify the source of their business model innovation. Furthermore, the results indicated the complexity of business model innovation as 79 percent of the respondents explained it with more than one sub-construct. New technology/equipment, new processes and new customers and markets got the most mentions as sources of business model innovation. Overall, the emphasis at startups is on the value creation innovation, with new proposition innovation getting less, and value capture innovation even less emphasis as the source of business model innovation.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Research group: Business Ecosystems, Networks and Innovations, Industrial and Information Management , VTT Technical Research Centre of Finland
Contributors: Still, K., Seppänen, M., Korhonen, H., Valkokari, K., Suominen, A., Kumpulainen, M.
Number of pages: 6
Pages: 70-75
Publication date: 17 Aug 2017

Host publication information

Title of host publication: Proceedings - 2017 IEEE 19th Conference on Business Informatics, CBI 2017
Publisher: IEEE
ISBN (Electronic): 9781538630341
ASJC Scopus subject areas: Strategy and Management, Computer Networks and Communications, Information Systems and Management, Management Science and Operations Research, Modelling and Simulation, Management Information Systems, Organizational Behavior and Human Resource Management
Keywords: Business model, Business model innovation, Digital platforms, Platform, Startups
DOIs:
10.1109/CBI.2017.86
Source: Scopus
Source ID: 85029454278
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Characterizing trustworthy digital rights exporting

Digital Rights Management (DRM) is an important business enabler for digital content industry. Rights exporting is one of the crucial tasks in providing the interoperability of DRM. Trustworthy rights exporting is required by both the end users and the DRM systems. We propose a set of principles for trustworthy rights exporting by analysing the characteristic of rights exporting. Based on the principles, we provide some suggestions on how trustworthy rights exporting should be performed.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Research Community on Data-to-Decision (D2D)
Contributors: Lu, W., Zhang, Z., Nummenmaa, J.
Number of pages: 11
Pages: 85-95
Publication date: 2012

Host publication information

Title of host publication: Perspectives in Business Informatics Research - 11th International Conference, BIR 2012, Proceedings
Volume: 128 LNBIP
Publisher: Springer Verlag
ISBN (Print): 9783642332807

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 128 LNBIP
ISSN (Print): 18651348
ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
Keywords: Digital Rights Management (DRM), DRM interoperability, rights exporting
DOIs:
10.1007/978-3-642-33281-4_7
URLs:
<http://www.scopus.com/inward/record.url?scp=84867732410&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 84867732410
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Client-Side Cornucopia: Comparing the Built-In Application Architecture Models in the Web Browser

The programming capabilities of the Web can be viewed as an afterthought, designed originally by non-programmers for relatively simple scripting tasks. This has resulted in cornucopia of partially overlapping options for building applications. Depending on one's viewpoint, a generic standards-compatible web browser supports three, four or five built-in application rendering and programming models. In this paper, we give an overview and comparison of these built-in client-side web application architectures in light of the established software engineering principles. We also reflect on our earlier work in this area, and provide an expanded discussion of the current situation. In conclusion, while the dominance of the base HTML/CSS/JS technologies cannot be ignored, we expect Web Components and WebGL to gain more popularity as the world moves towards increasingly complex web applications, including systems supporting virtual and augmented reality.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Computing Sciences, Bell Labs, University of Helsinki, Università della Svizzera Italiana
Contributors: Taivalsaari, A., Mikkonen, T., Pautasso, C., Systä, K.
Number of pages: 24
Pages: 1-24
Publication date: 2019

Host publication information

Title of host publication: Web Information Systems and Technologies - 14th International Conference, WEBIST 2018, Revised Selected Papers
Publisher: Springer
Editors: Escalona, M. J., Domínguez Mayo, F., Majchrzak, T. A., Monfort, V.
ISBN (Print): 9783030353292

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 372
ISSN (Print): 1865-1348
ISSN (Electronic): 1865-1356
ASJC Scopus subject areas: Management Information Systems, Control and Systems Engineering, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
Keywords: Rendering engines, Single page web applications, Web application architectures, Web browser, Web Components, Web programming, Web rendering

DOIs:

10.1007/978-3-030-35330-8_1

Bibliographical note

EXT="Taivalsaari, Antero"

EXT="Mikkonen, Tommi"

jufoid=71106

Source: Scopus

Source ID: 85079096366

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Color Constancy Convolutional Autoencoder

In this paper, we study the importance of pretraining for the generalization capability in the color constancy problem. We propose two novel approaches based on convolutional autoencoders: an unsupervised pre-training algorithm using a fine-tuned encoder and a semi-supervised pre-training algorithm using a novel composite-loss function. This enables us to solve the data scarcity problem and achieve competitive, to the state-of-the-art, results while requiring much fewer parameters on ColorChecker RECommended dataset. We further study the over-fitting phenomenon on the recently introduced version of INTEL-TUT Dataset for Camera Invariant Color Constancy Research, which has both field and non-field scenes acquired by three different camera models.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Computing Sciences, Research group: Multimedia Research Group - MRG, Aarhus University, Intel Finland

Contributors: Laakom, F., Raitoharju, J., Iosifidis, A., Nikkanen, J., Gabbouj, M.

Number of pages: 6

Pages: 1085-1090

Publication date: 2019

Host publication information

Title of host publication: 2019 IEEE Symposium Series on Computational Intelligence, SSCI 2019

Publisher: IEEE

Article number: 9002684

ISBN (Print): 978-1-7281-2486-5

ISBN (Electronic): 9781728124858

ASJC Scopus subject areas: Artificial Intelligence, Computer Science Applications, Modelling and Simulation

Keywords: color constancy, convolutional autoencoders, illumination, pre-training

DOIs:

10.1109/SSCI44817.2019.9002684

Bibliographical note

EXT="Iosifidis, Alexandros"

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Comparing requirements decomposition within the Scrum, Scrum with Kanban, XP, and Banana development processes

Context: Eliciting requirements from customers is a complex task. In Agile processes, the customer talks directly with the development team and often reports requirements in an unstructured way. The requirements elicitation process is up to the developers, who split it into user stories by means of different techniques. Objective: We aim to compare the requirements decomposition process of an unstructured process and three Agile processes, namely XP, Scrum, and Scrum with Kanban. Method: We conducted a multiple case study with a replication design, based on the project idea of an entrepreneur, a designer with no experience in software development. Four teams developed the project independently, using four different development processes. The requirements were elicited by the teams from the entrepreneur, who acted as product owner and was available to talk with the four groups during the project. Results: The teams decomposed the requirements using different techniques, based on the selected development process. Conclusion: Scrum with Kanban and XP resulted in the most effective processes from different points of view. Unexpectedly, decomposition techniques commonly adopted in traditional processes are still used in Agile processes, which may reduce project agility and performance. Therefore, we believe that decomposition techniques need to be addressed to a greater extent, both from the practitioners' and the research points of view.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Free University of Bolzano-Bozen, University of Oulu, Former organisation of the author

Contributors: Taibi, D., Lenarduzzi, V., Janes, A., Liukkunen, K., Ahmad, M. O.

Number of pages: 16
Pages: 68-83
Publication date: 2017

Host publication information

Title of host publication: Agile Processes in Software Engineering and Extreme Programming - 18th International Conference, XP 2017, Proceedings
Publisher: Springer Verlag
ISBN (Print): 9783319576329

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 283
ISSN (Print): 1865-1348
ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
DOIs:
10.1007/978-3-319-57633-6_5

Bibliographical note

jufoid=71106
Source: Scopus
Source ID: 85018722175
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Computationally efficient optimization algorithms for model predictive control of linear systems with integer inputs

The model predictive control problem of linear systems with integer inputs results in an integer optimization problem. In case of a quadratic objective function, the optimization problem can be cast as an integer least-squares (ILS) problem. Three algorithms to solve this problem are proposed in this paper. Optimality can be traded in to reduce the computation time. An industrial case study-an inverter-driven electrical drive system-is considered to demonstrate the effectiveness of the presented techniques.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Institute for Electrical Drive Systems and Power Electronics, Technische Universität München, ABB Corporate Research Center - Switzerland
Contributors: Karamanakos, P., Geyer, T., Kennel, R.
Number of pages: 6
Pages: 3663-3668
Publication date: 16 Dec 2015

Host publication information

Title of host publication: 2015 54th IEEE Conference on Decision and Control, CDC 2015
ISBN (Electronic): 9781479978861
ASJC Scopus subject areas: Control and Systems Engineering, Modelling and Simulation, Control and Optimization
Electronic versions:
Computationally efficient optimization algorithms 2015
DOIs:
10.1109/CDC.2015.7402787
URLs:
<http://urn.fi/URN:NBN:fi:tuni-202004083147>
Source: Scopus
Source ID: 84961990645
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Constrained Long-Horizon Direct Model Predictive Control for Synchronous Reluctance Motor Drives

A finite control set model predictive control strategy for the control of the stator currents of a synchronous reluctance motor driven by a three-level neutral point clamped inverter is presented in this paper. The presented algorithm minimizes the stator current distortions while operating the drive system at switching frequencies of a few hundred Hertz. Moreover, the power electronic converter is protected by overcurrents and/or overvoltages owing to a hard constraint imposed on the stator currents. To efficiently solve the underlying integer nonlinear optimization problem a sphere decoding algorithm serves as optimizer. To this end, a numerical calculation of the unconstrained solution of the optimization problem is proposed, along with modifications in the algorithm proposed in [1] so as to meet the above-mentioned control objectives. Simulation results show the effectiveness of the proposed control algorithm.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Electrical Energy Engineering, Research group: Power electronics, Universita degli Studi di Padova, Italy, Technische Universitat Munchen

Contributors: Ortombina, L., Liegmann, E., Karamanakos, P., Tinazzi, F., Zigliotto, M., Kennel, R.

Number of pages: 8

Publication date: 10 Sep 2018

Host publication information

Title of host publication: 2018 IEEE 19th Workshop on Control and Modeling for Power Electronics, COMPEL 2018

Publisher: IEEE

Article number: 8460173

ISBN (Print): 9781538655412

ASJC Scopus subject areas: Modelling and Simulation, Energy Engineering and Power Technology, Electrical and Electronic Engineering, Control and Optimization

DOIs:

10.1109/COMPEL.2018.8460173

Bibliographical note

JUFOID=79370

Source: Scopus

Source ID: 85054503298

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Data Vault Mappings to Dimensional Model Using Schema Matching

In data warehousing, business driven development defines data requirements to fulfill reporting needs. A data warehouse stores current and historical data in one single place. Data warehouse architecture consists of several layers and each has its own purpose. A staging layer is a data storage area to assist data loadings, a data vault modelled layer is the persistent storage that integrates data and stores the history, whereas publish layer presents data using a vocabulary that is familiar to the information users. By following the process which is driven by business requirements and starts with publish layer structure, this creates a situation where manual work requires a specialist, who knows the data vault model. Our goal is to reduce the number of entities that can be selected in a transformation so that the individual developer does not need to know the whole solution, but can focus on a subset of entities (partial schema). In this paper, we present two different schema matchers, one based on attribute names, and another based on data flow mapping information. Schema matching based on data flow mappings is a novel addition to current schema matching literature. Through the example of Northwind, we show how these two different matchers affect the formation of a partial schema for transformation source entities. Based on our experiment with Northwind we conclude that combining schema matching algorithms produces correct entities in the partial schema.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Computing Sciences, Solita Ltd., Tampere University of Applied Sciences

Contributors: Puonti, M., Raitalaakso, T.

Number of pages: 10

Pages: 55-64

Publication date: 1 Jan 2019

Host publication information

Title of host publication: Research and Practical Issues of Enterprise Information Systems - 13th IFIP WG 8.9 International Conference, CONFENIS 2019, Proceedings

Publisher: Springer

Editors: Doucek, P., Basl, J., Pavlicek, A., Tjoa, A. M., Detter, K., Raffai, M.

ISBN (Print): 9783030376314

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 375

ISSN (Print): 1865-1348

ISSN (Electronic): 1865-1356

ASJC Scopus subject areas: Management Information Systems, Control and Systems Engineering, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management

Keywords: Data flow, Data vault, Data warehouse, Dimensional model, Schema matching

DOIs:

10.1007/978-3-030-37632-1_5

Bibliographical note

jufoid=71106

Source: Scopus

Source ID: 85077495040

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Dimension reduction and decomposition using causal graph and qualitative analysis for aircraft concept design optimization

With the increasing design dimensionality, it is more difficult to solve Multidisciplinary design optimization (MDO) problems. To reduce the dimensionality of MDO problems, many MDO decomposition strategies have been developed. However, those strategies consider the design problem as a black-box function. In practice, the designers usually have certain knowledge of their problem. In this paper, a method leveraging causal graph and qualitative analysis is developed to reduce the dimensionality of the MDO problem by systematically modeling and incorporating knowledge of the design problem. Causal graph is employed to show the input-output relationships between variables. Qualitative analysis using design structure matrix (DSM) is carried out to automatically find the variables that can be determined without optimization. According to the weight of variables, the MDO problem is divided into two sub-problems, the optimization problem with respect to important variables, and the one with less important variables. The novel method is performed to solve an aircraft concept design problem and the results show that the new dimension reduction and decomposition method can significantly improve optimization efficiency.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Mechanical Engineering and Industrial Systems, Simon Fraser University

Contributors: Wu, D., Coatanea, E., Wang, G. G.

Publication date: 2017

Host publication information

Title of host publication: 43rd Design Automation Conference

Publisher: The American Society of Mechanical Engineers ASME

ISBN (Electronic): 9780791858134

ASJC Scopus subject areas: Mechanical Engineering, Computer Graphics and Computer-Aided Design, Computer Science Applications, Modelling and Simulation

Keywords: Aircraft concept design, Causal graph, Dimension reduction, Dimensional analysis, Multidisciplinary design optimization

DOIs:

10.1115/DETC201767601

Source: Scopus

Source ID: 85034658662

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Dynamics of a buck converter with a constant power load

The dynamic properties of the buck converter with a constant power load are studied in this paper. The line-to-output and control-to-output transfer functions are derived, for voltage mode control and current mode control, in continuous conduction mode and discontinuous conduction mode. A comparison with the case of a resistive load is made in each case.

General information

Publication status: Published

MoE publication type: Not Eligible

Organisations: University Politehnica of Bucharest, Aalto University, Efore Oy

Contributors: Grigore, V., Hatonen, J., Kyyra, J., Suntio, T.

Number of pages: 7

Pages: 72-78

Publication date: 1 Jan 1998

Host publication information

Title of host publication: PESC 1998 - 29th Annual IEEE Power Electronics Specialists Conference

Publisher: Institute of Electrical and Electronics Engineers Inc.

Article number: 701881

ISBN (Print): 0780344898, 9780780344891

Publication series

Name: PESC Record - IEEE Annual Power Electronics Specialists Conference

Volume: 1

ISSN (Print): 0275-9306

ASJC Scopus subject areas: Modelling and Simulation, Condensed Matter Physics, Energy Engineering and Power Technology, Electrical and Electronic Engineering

DOIs:

10.1109/PESC.1998.701881

Source: Scopus

Source ID: 84880085186

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Ecosystems Here, There, and Everywhere — A Barometrical Analysis of the Roots of ‘Software Ecosystem’

This study structures the ecosystem literature by using a bibliometrical approach in analysing theoretical roots of ecosystem studies. Several disciplines, such as innovation, management and software studies have established own streams in the ecosystem research. This paper reports the results of analysing 601 articles from the Thomson Reuters Web of Science database, and identifies ten separate research communities which have established their own thematic ecosystem disciplines. We show that five sub-communities have emerged inside the field of software ecosystems. The software ecosystem literature draws its theoretical background from (1) technical, (2) research methodology, (3) business, (4) management, and (5) strategy oriented disciplines. The results pave the way for future research by illustrating the existing and missing links and directions in the field of the software ecosystem.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Pori Department, Research group: Business Ecosystems, Networks and Innovations, VTT Technical Research Centre of Finland, University of Turku

Contributors: Suominen, A., Hyrynsalmi, S., Seppänen, M.

Number of pages: 15

Pages: 32-46

Publication date: 2016

Host publication information

Title of host publication: Software Business : 7th International Conference, ICSOB 2016, Ljubljana, Slovenia, June 13-14, 2016, Proceedings

Publisher: Springer Verlag

ISBN (Print): 9783319405148

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 240

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering

Keywords: Bibliometric, Business ecosystem, Software ecosystem

DOIs:

10.1007/978-3-319-40515-5_3

Bibliographical note

JUFOID=711106

EXT="Hyrynsalmi, Sami"

Source: Scopus

Source ID: 84976639801

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Eeny, Meeny, Miny, Mo...: A multiple case study on selecting a technique for user-interaction data collecting

Today, software teams can deploy new software versions to users at an increasing speed – even continuously. Although this has enabled faster responding to changing customer needs than ever before, the speed of automated customer feedback gathering has not yet blossomed out at the same level. For these purposes, the automated collecting of quantitative data about how users interact with systems can provide software teams with an interesting alternative. When starting such a process, however, teams are faced immediately with difficult decision making: What kind of technique should be used for collecting user-interaction data? In this paper, we describe the reasons for choosing specific collecting techniques in three cases and refine a previously designed selection framework based on their data. The study is a part of on-going design science research and was conducted using case study methods. A few distinct criteria which practitioners valued the most arose from the results.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Pervasive Computing
Contributors: Suonsyrjä, S.
Number of pages: 16
Pages: 52-67
Publication date: 2017

Host publication information

Title of host publication: Agile Processes in Software Engineering and Extreme Programming - 18th International Conference, XP 2017, Proceedings
Publisher: Springer Verlag
ISBN (Print): 9783319576329

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 283
ISSN (Print): 1865-1348
ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
Keywords: Agile software development, Multiple case study, Software data collecting, User-interaction data
Electronic versions:
suonsyrjä 2017
DOIs:
10.1007/978-3-319-57633-6_4
URLs:
<http://urn.fi/URN:NBN:fi:tty-201706051581>

Bibliographical note

JUFOID=71106
Source: Scopus
Source ID: 85018700923
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Employing a multi-Objective robust optimisation method for healthy and low-energy dwelling design in Delhi, India

Dwelling design needs to consider multiple objectives and uncertainties to achieve effective and robust performance. A multi-objective robust optimisation method is outlined and then applied with the aim to optimise a one-story archetype in Delhi to achieve a healthy low-energy design. EnergyPlus is used to model a sample of selected design and uncertainty inputs. Sensitivity analysis identifies significant parameters and a meta-model is constructed to replicate input-output relationships. The meta-model is employed in a hybrid multi-objective optimisation algorithm that accounts for uncertainty. Results demonstrate the complexities of achieving a low energy consumption and healthy indoor environmental quality.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: University College London, University of Oxford
Contributors: Nix, E., Das, P., Taylor, J., Davies, M.
Number of pages: 8
Pages: 2093-2100
Publication date: 1 Jan 2015

Host publication information

Title of host publication: Proceedings of the 2014 Building Simulation and Optimization Conference
ASJC Scopus subject areas: Computer Science Applications, Architecture , Modelling and Simulation, Building and Construction
URLs:
<http://www.scopus.com/inward/record.url?scp=84976351471&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 84976351471
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Energy Detection-Based Spectrum Sensing over Fisher-Snedecor F Fading Channels

This paper investigates the performance of energy detection-based spectrum sensing over Fisher-Snedecor F fading channels. To this end, an analytical expression for the corresponding average detection probability is firstly derived and

then this is extended to account for collaborative spectrum sensing. The complementary receiver operating characteristics (ROC) are analyzed for different conditions of the average signal-to-noise ratio (SNR), time-bandwidth product, multipath fading, shadowing and number of collaborating users. It is shown that the energy detection performance is strongly linked to the severity of the multipath fading and amount of shadowing, whereby even small variations in either of these physical phenomena significantly impact the detection probability. Also, the versatile modeling capability of the Fisher-Snedecor F distribution is verified in the context of energy detection based spectrum sensing as it provides considerably more accurate characterization than the conventional Rayleigh fading model. To confirm the validity of the analytical results presented in this paper, we compare them with the results of some simulations.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Research group: Wireless Communications and Positioning, Electrical Engineering, Queen's University, Belfast, Northern Ireland, Centre for Wireless Innovation, Khalifa University, Department of Chemistry and Bioengineering, University of Surrey, German Jordanian University, Aristotle University of Thessaloniki

Contributors: Yoo, S. K., Cotton, S. L., Sofotasios, P. C., Muhaidat, S., Badarneh, O. S., Karagiannidis, G. K.

Publication date: 20 Feb 2019

Host publication information

Title of host publication: 2018 IEEE Global Communications Conference

Publisher: IEEE

Article number: 8647778

ISBN (Electronic): 9781538647271

ASJC Scopus subject areas: Information Systems and Management, Renewable Energy, Sustainability and the Environment, Safety, Risk, Reliability and Quality, Signal Processing, Modelling and Simulation, Instrumentation, Computer Networks and Communications

DOIs:

10.1109/GLOCOM.2018.8647778

Source: Scopus

Source ID: 85063500863

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Functional size measures and effort estimation in agile development: A replicated study

To help developers during the Scrum planning poker, in our previous work we ran a case study on a Moonlight Scrum process to understand if it is possible to introduce functional size metrics to improve estimation accuracy and to measure the accuracy of expert-based estimation. The results of this original study showed that expert-based estimations are more accurate than those obtained by means of models, calculated with functional size measures. To validate the results and to extend them to plain Scrum processes, we replicated the original study twice, applying an exact replication to two plain Scrum development processes. The results of this replicated study show that the accuracy of the effort estimated by the developers is very accurate and higher than that obtained through functional size measures. In particular, SiFP and IFPUG Function Points, have low predictive power and are thus not help to improve the estimation accuracy in Scrum.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Pervasive Computing, University of Cagliari

Contributors: Lenarduzzi, V., Lunesu, I., Matta, M., Taibi, D.

Number of pages: 12

Pages: 105-116

Publication date: 2015

Host publication information

Title of host publication: Agile Processes, in Software Engineering, and Extreme Programming - 16th International Conference, XP 2015, Proceedings

Volume: 212

Publisher: Springer-Verlag Berlin Heidelberg

ISBN (Print): 9783319186115

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 212

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Management Information Systems, Control and Systems Engineering, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management

DOIs:

10.1007/978-3-319-18612-2_9

URLs:

<http://www.scopus.com/inward/record.url?scp=84942790957&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84942790957

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Graph based representation and analyses for conceptual stages

What is the fundamental similarity between investing in stock of a company, because you like the products of this company, and selecting a design concept, because you have been impressed by the esthetic quality of the presentation made by the team developing the concept? Except that both decisions are based on a surface analysis of the situations, they both reflect a fundamental human's cognitive feature. Human brain is profoundly trying to minimize the efforts required to solve a cognitive task and is using when possible an automatic mode relying on recognition, memory, and causality. This mode is even used in some occasion without the engineer being conscious of it. Such type of tendencies are naturally pushing engineers to rush into known solutions, to avoid analyzing the context of a design problem, to avoid modelling design problems and to take decision based on isolated evidences. Those behaviors are familiar to experience teachers and engineers. This tendency is magnified by the time pressure imposed to the engineering design process. Early phases in particular have to be kept short despite the large impact of decisions taken at this stage. Few support tools are capable of supporting a deep analysis of the early design conditions and problems regarding the fuzziness and complexity of the early stage. The present article is hypothesizing that the natural ability of humans to deal with cause-effects relations push toward the massive usage of causal graphs analysis during the design process and specifically during the early phases. A global framework based on graphs is presented in this paper to efficiently support the early stages. The approach used to generate graphs, to analyze them and to support creativity based on the analysis is forming the central contribution of this paper.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Intelligent dexterity for secure networked infrastructure and applications (IDSNIA), Aalto University

Contributors: Coatanéa, E., Nonsiri, S., Christophe, F., Mokammel, F.

Publication date: 2014

Host publication information

Title of host publication: 34th Computers and Information in Engineering Conference

Volume: 1A

Publisher: The American Society of Mechanical Engineers ASME

ISBN (Electronic): 9780791846285

ASJC Scopus subject areas: Mechanical Engineering, Computer Graphics and Computer-Aided Design, Computer Science Applications, Modelling and Simulation

DOIs:

10.1115/DETC201435652

URLs:

<http://www.scopus.com/inward/record.url?scp=84961306932&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84961306932

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Improved Session Continuity in 5G NR with Joint Use of Multi-Connectivity and Guard Bandwidth

The intermittent millimeter-wave radio links as a result of human-body blockage are an inherent feature of the 5G New Radio (NR) technology by 3GPP. To improve session continuity in these emerging systems, two mechanisms have recently been proposed, namely, multi-connectivity and guard bandwidth. The former allows to establish multiple spatially-diverse connections and switch between them dynamically, while the latter reserves a fraction of system bandwidth for sessions changing their state from non-blocked to blocked, which ensures that the ongoing sessions have priority over the new ones. In this paper, we assess the joint performance of these two schemes for the user- and system-centric metrics of interest. Our numerical results reveal that the multi-connectivity operation alone may not suffice to increase the ongoing session drop probability considerably. On the other hand, the use of guard bandwidth significantly improves session continuity by somewhat compromising new session drop probability and system resource utilization. Surprisingly, the 5G NR system implementing both these techniques inherits their drawbacks. However, complementing it with an initial AP selection procedure effectively alleviates these limitations by maximizing the system resource utilization, while still providing sufficient flexibility to enable the desired trade-off between new and ongoing session drop probabilities.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Electrical Engineering, Department of Chemistry and Bioengineering, Peoples' Friendship University of Russia
Contributors: Kovalchukov, R., Moltchanov, D., Begishev, V., Samuylov, A., Andreev, S., Koucheryavy, Y., Samouylov, K.
Publication date: 20 Feb 2019

Host publication information

Title of host publication: 2018 IEEE Global Communications Conference, GLOBECOM 2018

Publisher: IEEE

ISBN (Electronic): 9781538647271

ASJC Scopus subject areas: Information Systems and Management, Renewable Energy, Sustainability and the Environment, Safety, Risk, Reliability and Quality, Signal Processing, Modelling and Simulation, Instrumentation, Computer Networks and Communications

Electronic versions:

Improved Session Continuity in 5G NR 2019

DOIs:

10.1109/GLOCOM.2018.8647608

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202001281600>

Source: Scopus

Source ID: 85063532495

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Independent Loops Search in Flow Networks Aiming for Well-Conditioned System of Equations

We approach the problem of choosing linearly independent loops in a pipeflow network as choosing the best-conditioned submatrix of a given larger matrix. We present some existing results of graph theory and submatrix selection problems, based on which we construct three heuristic algorithms for choosing the loops. The heuristics are tested on two pipeflow networks that differ significantly on the distribution of pipes and nodes in the network.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Mathematics, Research group: Computer Science and Applied Logics, Research group: Positioning, Research group: MAT Intelligent Information Systems Laboratory, Tekes

Contributors: Humaloja, J., Ali-Löytty, S., Pohjolainen, S., Hämäläinen, T.

Publication date: 2017

Host publication information

Title of host publication: Progress in Industrial Mathematics at ECMI 2016

Publisher: Springer International Publishing

Editors: Quintela, P., Barral, P., Gómez, D., Pena, F. J., Rodríguez, J., Salgado, P., Vázquez-Mendéz, M. E.

ISBN (Print): 978-3-319-63081-6

ISBN (Electronic): 978-3-319-63082-3

Publication series

Name: Mathematics in industry

Publisher: Springer

Volume: 26

ISSN (Print): 1612-3956

ISSN (Electronic): 2198-3283

ASJC Scopus subject areas: Applied Mathematics, Modelling and Simulation

Keywords: pipeflow analysis, independent loops

Electronic versions:

ecmi16. Embargo ended: 4/12/18

DOIs:

10.1007/978-3-319-63082-3

URLs:

<http://urn.fi/URN:NBN:fi:tty-201710182012>. Embargo ended: 4/12/18

<https://www.springer.com/gp/book/9783319630816>

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Knowledge-based artificial neural network (KB-ANN) in engineering: Associating functional architecture modeling, dimensional analysis and causal graphs to produce optimized topologies for KB-ANNs

This article documents a study on artificial neural networks (ANNs) applied to the field of engineering and more specifically a study taking advantage of prior domain knowledge of engineering systems to improve the learning capabilities of ANNs

by reducing the dimensionality of the ANNs. The proposed approach ultimately leads to training a smaller ANN, offering advantage in training performances such as lower Mean Squared Error, lower cost and faster convergence. The article proposes to associate functional architecture, Pi numbers, and causal graphs and presents a design process to generate optimized knowledge-based ANN (KB-ANN) topologies. The article starts with a literature survey related to ANN and their topologies. Then, an important distinction is made between system behavior centered topologies and ANN centered topologies. The Dimensional Analysis Conceptual Modeling (DACM) framework is introduced as a way of implementing the system behavior centered topology. One case study is analyzed with the goal of defining an optimized KB-ANN topology. The study shows that the KB-ANN topology performed significantly better in term of the size of the required training set than a conventional fully-connected ANN topology. Future work will investigate the application of KB-ANNs to additive manufacturing.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Mechanical Engineering and Industrial Systems, Research area: Manufacturing and Automation, Simon Fraser University

Contributors: Coatanéa, E., Wu, D., Tsarkov, V., Gary Wang, G., Modi, S., Jafarian, H.

Number of pages: 12

Publication date: 2018

Host publication information

Title of host publication: 38th Computers and Information in Engineering Conference

Volume: 1B-2018

Publisher: The American Society of Mechanical Engineers ASME

ISBN (Electronic): 9780791851739

ASJC Scopus subject areas: Mechanical Engineering, Computer Graphics and Computer-Aided Design, Computer Science Applications, Modelling and Simulation

Keywords: Additive Manufacturing, Artificial Neural Networks, Classifiers, Dimensional Analysis, Empirical learning, Knowledge Based Artificial Neural Network

DOIs:

10.1115/DETC201885895

Bibliographical note

INT=mei,"Jafarian, Hesam"

Source: Scopus

Source ID: 85056903740

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Lean manufacturing methods in simulation literature: Review and association analysis

The lean manufacturing philosophy includes several methods that aim to remove waste from production. This paper studies lean manufacturing methods and how simulation is used to consider them. In order to do this, it reviews papers that study simulation together with lean methods. The papers that are reviewed are categorized according to the lean methods used and result types obtained. Analysis is performed in order to gain knowledge about the volumes of occurrence of different methods and result types. Typical methods in the papers are different types of value stream mapping and work-in-process models. An exploratory analysis is performed to reveal the relationships between the methods and result types. This is done using association analysis. It reveals the methods that are commonly studied together in the literature. The paper also lists research areas that are not considered in the literature. These areas are often related to the analysis of variation.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Department of Mechanical Engineering and Industrial Systems, Research area: Manufacturing and Automation, Aalto University, Department of Engineering Design and Production

Contributors: Tokola, H., Niemi, E., Väistö, V.

Number of pages: 10

Pages: 2239-2248

Publication date: 16 Feb 2016

Host publication information

Title of host publication: 2015 Winter Simulation Conference (WSC)

ISBN (Print): 978-1-4673-9743-8

ASJC Scopus subject areas: Software, Modelling and Simulation, Computer Science Applications

DOIs:

10.1109/WSC.2015.7408336

Bibliographical note

EXT="Niemi, Esko"

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Lean software startup – an experience report from an entrepreneurial software business course

This paper offers blueprints for and reports upon three years experience from teaching the university course "Lean Software Startup" for information technology and economics students. The course aims to give a learning experience on ideation/innovation and subsequent product and business development using the lean startup method. The course educates the students in software business, entrepreneurship, teamwork and the lean startup method. The paper describes the pedagogical design and practical implementation of the course in sufficient detail to serve as an example of how entrepreneurship and business issues can be integrated into a software engineering curriculum. The course is evaluated through learning diaries and a questionnaire, as well as the primary teacher's learnings in the three course instances. We also examine the course in the context of CDIO and show its connection points to this broader engineering education framework. Finally we discuss the challenges and opportunities of engaging students with different backgrounds in a hands-on entrepreneurial software business course.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Managing digital industrial transformation (mDIT), University of Turku, Department of Information Technology

Contributors: Järvi, A., Taajamaa, V., Hyrynsalmi, S.

Number of pages: 15

Pages: 230-244

Publication date: 2015

Host publication information

Title of host publication: Software Business - 6th International Conference, ICSOB 2015, Proceedings

Volume: 210

Publisher: Springer Verlag

ISBN (Electronic): 9783319195926

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 210

ISSN (Print): 18651348

ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering

Keywords: CDIO, Education, Lean startup, Software business, Software entrepreneurship

DOIs:

10.1007/978-3-319-19593-3_21

Source: Scopus

Source ID: 84937425636

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Measurement theory and dimensional analysis: Methodological impact on the comparison and evaluation process

Comparison and ranking of solutions are central tasks of the design process. Designers have to deal with decisions simultaneously involving multiple criteria. Those criteria are often inconsistent in the sense that they are expressed according to different types of metrics. This means that usual engineering performance indicators are expressed according to physical quantities (i.e. SI system) and indicators such as preference functions can be "measured" by using other type of qualitative metrics. This aspect limits the scientific consistency of design because a coherent scientific framework will at first require the creation of a unified list of fundamental properties. A combined analysis of the measurement theory, the General Design Theory (GDT) and the dimensional analysis theory give an interesting insight in order to create guidelines for establishing a coherent measurement system. This article establishes a list of fundamental requirements. We expect that these guidelines can help engineers and designers to be more aware of the drawbacks linked with the use of wrong comparison procedures and limitations associated with the use of weak measurement scales. This article makes an analysis of the fundamental aspects available in major scientific publications related to comparison, provides a synthesis of these basic concepts and unifies those concepts together from a designing perspective. A practical design methodology using the fundamental results of this article as prerequisites has been implemented by the authors.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: LGI, LGI Laboratory, Helsinki University of Technology, Aalto University

Contributors: Coatanéa, E., Yannou, B., Honkala, S., Lajunen, A., Saarelainen, T., Makkonen, P.

Number of pages: 10
Pages: 173-182
Publication date: 2008

Host publication information

Title of host publication: 19th International Conference on Design Theory and Methodology and 1st International Conference on Micro and Nano Systems, presented at - 2007 ASME International Design Engineering Technical Conferences and Computers and Information in Engineering Conference, IDETC/CIE2007

Publisher: AMER SOC MECHANICAL ENGINEERS

ISBN (Print): 978-0-7918-4804-3

ASJC Scopus subject areas: Computer Graphics and Computer-Aided Design, Computer Science Applications, Mechanical Engineering, Modelling and Simulation

Keywords: ENGINEERING DESIGN

DOIs:

10.1115/DETC2007-34364

URLs:

<http://www.scopus.com/inward/record.url?scp=44849093457&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: WOS

Source ID: 000254167700017

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Minimum viable user experience: A framework for supporting product design in startups

Startups operate with small resources in time pressure. Thus, building minimal product versions to test and validate ideas has emerged as a way to avoid wasteful creation of complicated products which may be proven unsuccessful in the markets. Often, design of these early product versions needs to be done fast and with little advance information from end-users. In this paper we introduce the Minimum Viable User eXperience (MVUX) that aims at providing users a good enough user experience already in the early, minimal versions of the product. MVUX enables communication of the envisioned product value, gathering of meaningful feedback, and it can promote positive word of mouth. To understand what MVUX consists of, we conducted an interview study with 17 entrepreneurs from 12 small startups. The main elements of MVUX recognized are Attractiveness, Approachability, Professionalism, and Selling the Idea. We present the structured framework and elements' contributing qualities.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Department of Pervasive Computing, Research area: User experience

Contributors: Hokkanen, L., Kuusinen, K., Väänänen, K.

Number of pages: 13

Pages: 66-78

Publication date: 2016

Host publication information

Title of host publication: Agile Processes, in Software Engineering, and Extreme Programming : 17th International Conference, XP 2016, Edinburgh, UK, May 24-27, 2016, Proceedings

Publisher: Springer Verlag

ISBN (Print): 9783319335148

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 251

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering

Electronic versions:

Minimum Viable User eXperience_HokkanenEtAL_XP2016

DOIs:

10.1007/978-3-319-33515-5_6

URLs:

<http://urn.fi/URN:NBN:fi:tty-201903291365>

Bibliographical note

jufoid=71106

Source: Scopus

Source ID: 84971538959

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

On Confidences and Their Use in (Semi-)Automatic Multi-Image Taxa Identification

We analyzed classification confidences in biological multi-image taxa identification problems, where each specimen is represented by multiple images. We observed that confidences can be exploited to progress toward semi-automated identification process, where images are initially classified using a convolutional neural network and taxonomic experts manually inspect only the samples with a low confidence. We studied different ways to evaluate confidences and concluded that the difference of the largest and second largest values in unnormalized network outputs leads to best results. Furthermore, we compared different ways to use image-wise confidences when deciding on the final identification using all the input images of a specimen. The best results were obtained using a confidence-weighted sum rule over the unnormalized outputs. This approach also outperformed the evaluated supervised decision method.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Computing Sciences, Research group: Multimedia Research Group - MRG, Finnish Environment Institute

Contributors: Raitoharju, J., Meissner, K.

Number of pages: 6

Pages: 1338-1343

Publication date: 2019

Host publication information

Title of host publication: 2019 IEEE Symposium Series on Computational Intelligence, SSCI 2019

Publisher: IEEE

Article number: 9002975

ISBN (Print): 978-1-7281-2486-5

ISBN (Electronic): 9781728124858

ASJC Scopus subject areas: Artificial Intelligence, Computer Science Applications, Modelling and Simulation

Keywords: benthic macroinvertebrates, classification confidence, decision rules, taxa identification

DOIs:

10.1109/SSCI44817.2019.9002975

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

On prediction of DCT-based denoising efficiency under spatially correlated noise conditions

In this paper, results of image denoising efficiency prediction for filter based on discrete cosine transform (DCT) for the case of spatially correlated additive Gaussian Noise (SCGN) are given. The considered noise model is analyzed for different degrees of spatial correlation that produce varying non-homogeneous spectrum of the noise. PSNR metric is exploited to assess denoising efficiency. It is shown in this paper, that a prediction of denoising efficiency has high accuracy for data distorted by noise with different degrees of spatial correlation, and require low computational resources.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Department of Signal Processing, Research group: Computational Imaging-CI, Kharkiv National Aerospace University

Contributors: Rubel, O., Lukin, V., Egiazarian, K.

Number of pages: 5

Pages: 750-754

Publication date: 12 Apr 2016

Host publication information

Title of host publication: 2016 13th International Conference on Modern Problems of Radio Engineering, Telecommunications and Computer Science (TCSET)

Publisher: IEEE

ISBN (Print): 9786176078067

ASJC Scopus subject areas: Computer Networks and Communications, Electrical and Electronic Engineering, Instrumentation, Radiation, Computer Science (miscellaneous), Signal Processing, Modelling and Simulation

Keywords: Denoising, Efficiency Prediction, Fitting, Spatially Correlated Noise

DOIs:

10.1109/TCSET.2016.7452171

Source: Scopus

Source ID: 84969277857

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

OP2A: How to improve the quality of the web portal of open source software products

Open Source Software (OSS) communities do not often invest in marketing strategies to promote their products in a competitive way. Even the home pages of the web portals of well-known OSS products show technicalities and details that are not relevant for a fast and effective evaluation of the product's qualities. So, final users and even developers who are interested in evaluating and potentially adopting an OSS product are often negatively impressed by the quality perception they have from the web portal of the product and turn to proprietary software solutions or fail to adopt OSS that may be useful in their activities. In this paper, we define OP2A, an evaluation model and we derive a checklist that OSS developers and web masters can use to design (or improve) their web portals with all the contents that are expected to be of interest for OSS final users. We exemplify the use of the model by applying it to the Apache Tomcat web portal and we apply the model to 47 web sites of well-known OSS products to highlight the current deficiencies that characterize these web portals.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Università degli Studi Dell'Insubria
Contributors: Lavazza, L., Morasca, S., Taibi, D., Tosi, D.
Number of pages: 14
Pages: 149-162
Publication date: 2011

Host publication information

Title of host publication: Web Information Systems and Technologies - 7th International Conference, WEBIST 2011, Revised Selected Papers
Publisher: Springer Verlag
ISBN (Print): 9783642280818

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 101 LNBIP
ISSN (Print): 1865-1348
ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
Keywords: Open source software, Quality perception, Web portal quality model, Web portals quality assessment
DOIs:
10.1007/978-3-642-28082-5-11
Source: Scopus
Source ID: 84870372815
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Passive condition pre-enforcement for rights exporting

Condition pre-enforcement is one of the known methods for rights adaptation. Related to the integration of the rights exporting process, we identify issues introduced by condition pre-enforcement and potential risks of granting unexpected rights when exporting rights back and forth. We propose a solution to these problems in a form of a new algorithm called Passive Condition Pre-enforcement (PCP), and discuss the impact of PCP to the existing process of rights exporting.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Research Community on Data-to-Decision (D2D)
Contributors: Lu, W., Nummenmaa, J., Zhang, Z.
Number of pages: 14
Pages: 241-254
Publication date: 2015

Host publication information

Title of host publication: Perspectives in Business Informatics Research - 14th International Conference, BIR 2015, Proceedings
Volume: 229
Publisher: Springer Verlag
ISBN (Print): 9783319219141

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 229
ISSN (Print): 18651348

ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
Keywords: Condition pre-enforcement, Digital rights management, DRM interoperability, Rights exporting
DOIs:

10.1007/978-3-319-21915-8_16

URLs:

<http://www.scopus.com/inward/record.url?scp=84951287731&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84951287731

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Performance evaluation of a flow control algorithm for network-on-chip

Network-on-chip (NoC) has been proposed for SoC (System-on-Chip) as an alternative to on-chip bus-based interconnects to achieve better performance and lower energy consumption. Several approaches have been proposed to deal with NoCs design and can be classified into two main categories, design-time approaches and run-time approaches. Design-time approaches are generally tailored for an application domain or a specific application by providing a customized NoC. All parameters, such as routing and switching schemes, are defined at design time. Run-time approaches, however, provide techniques that allow a NoC to continuously adapt its structure and its behavior (i.e., at runtime). In this paper, performance evaluation of a flow control algorithm for congestion avoidance in NoCs is presented. This algorithm allows NoC elements to dynamically adjust their inflow by using a feedback control-based mechanism. Analytical and simulation results are reported to show the viability of this mechanism for congestion avoidance in NoCs.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: IRTES-M3M, Université de Technologie de Belfort-Montbéliard (UTBM), University of Valenciennes, Aalto Univ, Aalto University, Sch Engn, Dept Engn Design & Prod, Aalto University

Contributors: Bakhouya, M., Chariete, A., Gaber, J., Wack, M., Niar, S., Coatanea, E.

Number of pages: 7

Pages: 281-287

Publication date: 2012

Host publication information

Title of host publication: Proceedings of the 2012 International Conference on High Performance Computing and Simulation, HPCS 2012

Article number: 6266925

ISBN (Print): 9781467323598

ASJC Scopus subject areas: Modelling and Simulation

Keywords: Flow control and congestion, Modeling/simulation and evaluation, Network-on-chip

DOIs:

10.1109/HPCSim.2012.6266925

URLs:

<http://www.scopus.com/inward/record.url?scp=84866996348&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84866996348

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

PiMM: Parameterized and interfaced dataflow meta-model for MPSoCs runtime reconfiguration

Dataflow models of computation are widely used for the specification, analysis, and optimization of Digital Signal Processing (DSP) applications. In this paper a new meta-model called PiMM is introduced to address the important challenge of managing dynamics in DSP-oriented representations. PiMM extends a dataflow model by introducing an explicit parameter dependency tree and an interface-based hierarchical compositionality mechanism. PiMM favors the design of highly-efficient heterogeneous multicore systems, specifying algorithms with customizable trade-offs among predictability and exploitation of both static and adaptive task, data and pipeline parallelism. PiMM fosters design space exploration and reconfigurable resource allocation in a flexible dynamic dataflow context.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Signal Processing Research Community (SPRC), UBL, University of Maryland, Texas Instruments France S.A

Contributors: Desnos, K., Pelcat, M., Nezan, J. F., Bhattacharyya, S. S., Aridhi, S.

Number of pages: 8

Pages: 41-48

Publication date: 2013

Host publication information

Title of host publication: Proceedings - 2013 International Conference on Embedded Computer Systems: Architectures, Modeling and Simulation, IC-SAMOS 2013

Publisher: IEEE COMPUTER SOCIETY PRESS

Article number: 6621104

ISBN (Print): 9781479901036

ASJC Scopus subject areas: Hardware and Architecture, Electrical and Electronic Engineering, Modelling and Simulation
DOIs:

10.1109/SAMOS.2013.6621104

URLs:

<http://www.scopus.com/inward/record.url?scp=84888883761&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84888883761

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Prioritizing corrective maintenance activities for android applications: An industrial case study on android crash reports

Context: Unhandled code exceptions are often the cause of a drop in the number of users. In the highly competitive market of Android apps, users commonly stop using applications when they find some problem generated by unhandled exceptions. This is often reflected in a negative comment in the Google Play Store and developers are usually not able to reproduce the issue reported by the end users because of a lack of information. Objective: In this work, we present an industrial case study aimed at prioritizing the removal of bugs related to uncaught exceptions. Therefore, we (1) analyzed crash reports of an Android application developed by a public transportation company, (2) classified uncaught exceptions that caused the crashes; (3) prioritized the exceptions according to their impact on users. Results: The analysis of the exceptions showed that seven exceptions generated 70% of the overall errors and that it was possible to solve more than 50% of the exceptions-related issues by fixing just six Java classes. Moreover, as a side result, we discovered that the exceptions were highly correlated with two code smells, namely "Spaghetti Code" and "Swiss Army Knife". The results of this study helped the company understand how to better focus their limited maintenance effort. Additionally, the adopted process can be beneficial for any Android developer in understanding how to prioritize the maintenance effort.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Pervasive Computing, Free University of Bolzano-Bozen, SASAbus

Contributors: Lenarduzzi, V., Stan, A. C., Taibi, D., Venters, G., Windegger, M.

Number of pages: 11

Pages: 133-143

Publication date: Jan 2018

Host publication information

Title of host publication: Software Quality : Methods and Tools for Better Software and Systems - 10th International Conference, SWQD 2018, Proceedings

Publisher: Springer-Verlag Berlin Heidelberg

ISBN (Print): 9783319714394

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 302

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Management Information Systems, Control and Systems Engineering, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management

Keywords: Continuous monitoring, Software quality, Technical debt

DOIs:

10.1007/978-3-319-71440-0_8

Bibliographical note

EXT="Lenarduzzi, Valentina"

jufoid=71106

Source: Scopus

Source ID: 85041125663

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Reconfigurable computing for future vision-capable devices

Mobile devices have been identified as promising platforms for interactive vision-based applications. However, this type of applications still pose significant challenges in terms of latency, throughput and energy-efficiency. In this context, the integration of reconfigurable architectures on mobile devices allows dynamic reconfiguration to match the computation and data flow of interactive applications, demonstrating significant performance benefits compared to general purpose architectures. This paper presents concepts laying on platform level adaptability, exploring the acceleration of vision-based interactive applications through the utilization of three reconfigurable architectures: A low-power EnCore processor with a Configurable Flow Accelerator co-processor, a hybrid reconfigurable SIMD/MIMD platform and Transport-Triggered Architecture-based processors. The architectures are evaluated and compared with current processors, analyzing their advantages and weaknesses in terms of performance and energy-efficiency when implementing highly interactive vision-based applications. The results show that the inclusion of reconfigurable platforms on mobile devices can enable the computation of several computationally heavy tasks with high performance and small energy consumption while providing enough flexibility.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Signal Processing Research Community (SPRC), Univ of Oulu, University of Santiago de Compostela (USC)

Contributors: López, M. B., Nieto, A., Silvén, O., Bóutellier, J., Vilariño, D. L.

Number of pages: 8

Pages: 34-41

Publication date: 22 Dec 2015

Host publication information

Title of host publication: Proceedings - 2015 International Conference on Embedded Computer Systems: Architectures, Modeling and Simulation, SAMOS 2015

Publisher: Institute of Electrical and Electronics Engineers Inc.

Article number: 7363657

ISBN (Electronic): 9781467373111

ASJC Scopus subject areas: Computer Networks and Communications, Hardware and Architecture, Modelling and Simulation

DOIs:

10.1109/SAMOS.2015.7363657

URLs:

<http://www.scopus.com/inward/record.url?scp=84963704173&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84963704173

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Reconfigurable miniature sensor nodes for condition monitoring

The wireless sensor networks are being deployed at escalating rate for various application fields. The ever growing number of application areas requires a diverse set of algorithms with disparate processing needs. The wireless sensor networks also need to adapt to the prevailing energy conditions and processing requirements. The preceding reasons rule out the use of a single fixed design. Instead a general purpose design that can rapidly adapt to different conditions and requirements is desired. In lieu of the traditional inflexible wireless sensor node consisting of a micro-controller, radio transceiver, sensor array and energy storage, we propose a rapidly reconfigurable miniature sensor node, implemented with a transport triggered architecture processor on a low-power Flash FPGA. Also power consumption and silicon area usage comparison between 16-bit fixed and floating point and 32-bit floating point implementations is presented in this paper. The implemented processors and algorithms are intended for rolling bearing condition monitoring, but can be fully extended for other applications as well.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Signal Processing Research Community (SPRC), Univ of Oulu, Computer Science and Engineering Laboratory

Contributors: Nylanden, T., Boutellier, J., Nikunen, K., Hannuksela, J., Silven, O.

Number of pages: 7

Pages: 113-119

Publication date: 2012

Host publication information

Title of host publication: Proceedings - 2012 International Conference on Embedded Computer Systems: Architectures, Modeling and Simulation, IC-SAMOS 2012

Article number: 6404164

ISBN (Print): 9781467322973

ASJC Scopus subject areas: Hardware and Architecture, Electrical and Electronic Engineering, Modelling and Simulation

DOIs:

10.1109/SAMOS.2012.6404164

URLs:

<http://www.scopus.com/inward/record.url?scp=84873554935&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84873554935

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Revenue models of application developers in android market ecosystem

Mobile application ecosystems have grown rapidly in the past few years. Increasing number of startups and established developers are alike offering their products in different marketplaces such as Android Market and Apple App Store. In this paper, we are studying revenue models used in Android Market. For analysis, we gathered the data of 351,601 applications from their public pages at the marketplace. From these, a random sample of 100 applications was used in a qualitative study of revenue streams. The results indicate that a part of the marketplace can be explained with traditional models but free applications use complex revenue models. Basing on the qualitative analysis, we identified four general business strategy categories for further studies.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Managing digital industrial transformation (mDIT), Turku Centre for Computer Science, Business and Innovation Development (BID), University of Turku

Contributors: Hyrynsalmi, S., Suominen, A., Mäkilä, T., Järvi, A., Knuutila, T.

Number of pages: 14

Pages: 209-222

Publication date: 2012

Host publication information

Title of host publication: Software Business - Third International Conference, ICSOB 2012, Proceedings

Publisher: Springer Verlag

ISBN (Print): 9783642307454

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 114

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Business, Management and Accounting(all), Modelling and Simulation, Information Systems and Management, Information Systems, Management Information Systems, Business and International Management, Control and Systems Engineering

Keywords: Android Market, business model, Mobile ecosystem, revenue model

DOIs:

10.1007/978-3-642-30746-1_17

Source: Scopus

Source ID: 84864211787

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Safety at chimney-roof penetration: A numerical investigation

Chimneys convey exhaust gas produced in heat generators to the external ambient. To do this, they cross building elements such as floors and roofs, which can be made of flammable materials such as wood, wood fiber, cellulose, etc. This represents a dangerous condition that can lead to the overheating of the structure and, consequently, to possible fires. In recent years, numerous roof fires have occurred in Europe due to the presence of a chimney, and some of these have also involved certified chimneys. The aim of the certification procedure is the determination of the distance between chimney and flammable structures to avoid fires. This paper describes an investigation performed to understand the causes of the high number of fires and to propose solutions to the roof fires problem. The study was carried out numerically and experimentally, and consisted of three steps. Firstly, the chimney certification procedure was investigated to highlight possible weaknesses. Then, by means of a 2D and a 3D numerical models, the variables affecting heat transfer at chimney-roof penetration were identified. Finally, solutions and prescriptions to prevent roof fires are proposed. The solutions consist of a set of tables for checking chimney installations, and a universal device to be installed between chimney and roof to prevent the overheating of the latter, also in very critical conditions represented by soot fires, and installations in very thick and insulating roofs.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Civil Engineering, Università degli Studi di Brescia, FirePro Palokatko Oy

Contributors: Neri, M., Perttu, L., Alanen, M., Luscietti, D., Pilotelli, M.

Number of pages: 8

Pages: 123-130

Publication date: 2020

Host publication information

Title of host publication: Building Simulation Applications, BSA 2019 - 4th IBPSA-Italy Conference

Publisher: Free University of Bozen Bolzano

Editors: Pernigotto, G., Patuzzi, F., Prada, A., Corrado, V., Gasparella, A.

ISBN (Electronic): 9788860461766

Publication series

Name: Building Simulation Applications

Volume: 2020-June

ISSN (Electronic): 2531-6702

ASJC Scopus subject areas: Computer Science Applications, Building and Construction, Architecture, Modelling and Simulation

Electronic versions:

Safety at Chimney-Roof Penetration 2020

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202009237098>

URLs:

https://bsa.events.unibz.it/conference_proceedings/

Source: Scopus

Source ID: 85090850267

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Simulation of photon-photon resonance enhanced direct modulation bandwidth of DFB lasers

Simulations and experimental results of high-frequency photon-photon resonance are used to examine the possibilities to extend the direct modulation bandwidth in dual-mode distributed feedback lasers beyond the conventional limit set by the carrier-photon resonance.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Optoelectronics Research Centre, Research group: Semiconductor Technology and Applications,

Brighterwave Inc, Politecnico di Torino

Contributors: Dumitrescu, M., Uusitalo, T., Virtanen, H., Laakso, A., Bardella, P., Montrosset, I.

Number of pages: 2

Pages: 147-148

Publication date: 17 Aug 2016

Host publication information

Title of host publication: 16th International Conference on Numerical Simulation of Optoelectronic Devices, NUSOD 2016

Publisher: IEEE

ISBN (Electronic): 978-1-4673-8603-6

ASJC Scopus subject areas: Electrical and Electronic Engineering, Electronic, Optical and Magnetic Materials, Modelling and Simulation, Numerical Analysis

DOIs:

10.1109/NUSOD.2016.7547075

Bibliographical note

EXT="Laakso, A."

Source: Scopus

Source ID: 84987641496

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Simulation studies of DFB laser longitudinal structures for narrow linewidth emission

Simulation studies targeting high-power narrow-linewidth emission from DFB lasers are presented. The linewidth and output power calculations take into account the mirror losses, including the grating and the facets, as well as spontaneous emission noise, effective refractive index, power and carrier density variations inside the cavity. The longitudinal power

and carrier density distributions have been evaluated and their effects on longitudinal spatial hole burning and possible side mode lasing are discussed.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Optoelectronics Research Centre, Research group: Semiconductor Technology and Applications

Contributors: Virtanen, H., Uusitalo, T., Dumitrescu, M.

Number of pages: 2

Pages: 153-154

Publication date: 17 Aug 2016

Host publication information

Title of host publication: 16th International Conference on Numerical Simulation of Optoelectronic Devices, NUSOD 2016

Publisher: IEEE

ISBN (Electronic): 9781467386036

ASJC Scopus subject areas: Electrical and Electronic Engineering, Electronic, Optical and Magnetic Materials, Modelling and Simulation, Numerical Analysis

DOIs:

10.1109/NUSOD.2016.7547078

Source: Scopus

Source ID: 84987641768

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Sir analysis in square-shaped indoor premises

The increased wireless network densification has resulted in availability of wireless access points (AP) in almost each and every indoor location (room, office, etc.). To provide complete in-building coverage very often an AP is deployed per room. In this paper we analyze signal-to-interference (SIR) ratio for wireless systems operating in neighboring rooms separated by walls of different materials by explicitly taking into account the propagation and wall penetration losses. Both AP and direct device-to-device (D2D) configurations are addressed. Our numerical results indicate that the performance of such system is characterized by both the loss exponent describing the propagation environment of interest and wall materials. We provide the numerical results for typical wall widths/materials and analyze them in detail.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Department of Electronics and Communications Engineering, Research group: Emerging Technologies for Nano-Bio-Info-Cogno, Peoples' Friendship University of Russia, Russian Academy of Sciences, Peoples' Friendship University of Russia

Contributors: Samuylov, A., Moltchanov, D., Gaidamaka, Y., Begishev, V., Kovalchukov, R., Abaev, P., Shorgin, S.

Number of pages: 6

Pages: 692-697

Publication date: 2016

Host publication information

Title of host publication: Proceedings - 30th European Conference on Modelling and Simulation, ECMS 2016

Publisher: EUROPEAN COUNCIL FOR MODELLING AND SIMULATION

ISBN (Electronic): 9780993244025

ASJC Scopus subject areas: Modelling and Simulation

Keywords: Distributions, Indoor propagation, Signal-to-interference ratio, Square cells, Wall penetration, Wireless networks

DOIs:

10.7148/2016-0692

Bibliographical note

EXT="Kovalchukov, R."

Source: Scopus

Source ID: 84978745064

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Sir distribution in D2D environment with non-stationary mobility of users

Fifth generation (5G) cellular systems are expected to rely on the set of advanced networking techniques to further enhance the spatial frequency reuse. Device-to-device (D2D) communications is one of them allowing users to establish opportunistic direct connections. The use of direct communications is primarily determined by the signal-to-interference ratio (SIR). However, depending on the users movement, the SIR of an active connection is expected to drastically fluctuate. In this work we develop an analytical framework allowing to predict the channel quality between two moving

entities in a field of moving interfering stations. Assuming users movement driven by Fokker-Planck equation we obtain the empirical probability density function of SIR. The proposed methodology can be used to solve problems in the area of stochastic control of D2D communications in cellular networks.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Electronics and Communications Engineering, Keldysh Institute of Applied Mathematics, Peoples' Friendship University of Russia, Department of Applied Probability and Informatics, Russian Academy of Sciences

Contributors: Fedorov, S., Orlov, Y., Samuylov, A., Moltchanov, D., Gaidamaka, Y., Samouylov, K., Shorgin, S.

Number of pages: 6

Pages: 720-725

Publication date: 2017

Host publication information

Title of host publication: Proceedings - 31st European Conference on Modelling and Simulation, ECMS 2017

Publisher: EUROPEAN COUNCIL FOR MODELLING AND SIMULATION

ISBN (Electronic): 9780993244049

ASJC Scopus subject areas: Modelling and Simulation

Keywords: Cellular networks, D2D communications, Fokker-Planck equation, SIR distribution, Stochastic modeling

DOIs:

10.7148/2017-0720

Source: Scopus

Source ID: 85021835185

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Software evolution and time series volatility: An empirical exploration

The paper presents the first empirical study to examine econometric time series volatility modeling in the software evolution context. The econometric volatility concept is related to the conditional variance of a time series rather than the conditional mean targeted in conventional regression analysis. The software evolution context is motivated by relating these variance characteristics to the proximity of operating system releases, the theoretical hypothesis being that volatile characteristics increase nearby new milestone releases. The empirical experiment is done with a case study of FreeBSD. The analysis is carried out with 12 time series related to bug tracking, development activity, and communication. A historical period from 1995 to 2011 is covered under a daily sampling frequency. According to the results the time series dataset contains visible volatility characteristics, but these cannot be explained by the time windows around the six observed major FreeBSD releases. The paper consequently contributes to the software evolution research field with new methodological ideas, as well as with both positive and negative empirical results.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Managing digital industrial transformation (mDIT), University of Turku, Department of Information Technology

Contributors: Ruohonen, J., Hyrynsalmi, S., Leppänen, V.

Number of pages: 10

Pages: 56-65

Publication date: 30 Aug 2015

Host publication information

Title of host publication: 14th International Workshop on Principles of Software Evolution, IWPSE 2015 - Proceedings

Volume: 30-Aug-2015

Publisher: Institute of Electrical and Electronics Engineers Inc.

ISBN (Electronic): 9781450338165

ASJC Scopus subject areas: Software, Computational Theory and Mathematics, Modelling and Simulation, Theoretical Computer Science

Keywords: ARIMA, Code churn, Conditional variance, FreeBSD, GARCH, Software evolution, Time series analysis, Volatility

DOIs:

10.1145/2804360.2804367

Source: Scopus

Source ID: 84958599161

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Software vulnerability life cycles and the age of software products: An empirical assertion with operating system products

This empirical paper examines whether the age of software products can explain the turnaround between the release of security advisories and the publication vulnerability information. Building on the theoretical rationale of vulnerability life cycle modeling, this assertion is examined with an empirical sample that covers operating system releases from Microsoft and two Linux vendors. Estimation is carried out with a linear regression model. The results indicate that the age of the observed Microsoft products does not affect the turnaround times, and only feeble statistical relationships are present for the examined Linux releases. With this negative result, the paper contributes to the vulnerability life cycle modeling research by presenting and rejecting one theoretically motivated and previously unexplored question. The rejection is also a positive result; there is no reason for users to fear that the turnaround times would significantly lengthen as operating system releases age.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: University of Turku, Department of Information Technology

Contributors: Ruohonen, J., Hyrynsalmi, S., Leppänen, V.

Number of pages: 12

Pages: 207-218

Publication date: 2016

Host publication information

Title of host publication: Advanced Information Systems Engineering Workshops - CAiSE 2016 International Workshops, Proceedings

Publisher: Springer Verlag

ISBN (Print): 9783319395630

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 249

ISSN (Print): 18651348

ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering

Keywords: Linux, Microsoft, Negative result, Operating system, Security patching

DOIs:

10.1007/978-3-319-39564-7-20

Source: Scopus

Source ID: 84976644100

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Structural Similarity Index with Predictability of Image Blocks

Structural similarity index (SSIM) is a widely used full-reference metric for assessment of visual quality of images and remote sensing data. It is calculated in a block-wise manner and is based on multiplication of three components: similarity of means of image blocks, similarity of contrasts and a correlation factor. In this paper, two modifications of SSIM are proposed. First, a fourth multiplicative component is introduced to SSIM (thus obtaining SSIM4) that describes a similarity of predictability of image blocks. A predictability for a given block is calculated as a minimal value of mean square error between the considered block and the neighboring blocks. Second, a simple scheme for calculating the metrics SSIM and SSIM4 for color images is proposed and optimized. Effectiveness of the proposed modifications is confirmed for the specialized image databases TID2013, LIVE, and FLT. In particular, the Spearman rank order correlation coefficient (SROCC) for the recently introduced FLT Database, calculated between the proposed metric color SSIM4 and mean opinion scores (MOS), has reached the value 0.85 (the best result for all compared metrics) whilst for SSIM it is equal to 0.58.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Signal Processing, Research group: Computational Imaging-CI, Kharkiv National Aerospace University

Contributors: Ponomarenko, M., Egiazarian, K., Lukin, V., Abramova, V.

Number of pages: 4

Pages: 115-118

Publication date: 10 Sep 2018

Host publication information

Title of host publication: 2018 IEEE 17th International Conference on Mathematical Methods in Electromagnetic Theory, MMET 2018 - Proceedings

Volume: 2018-July

Publisher: IEEE COMPUTER SOCIETY PRESS

Article number: 8460285
ISBN (Print): 9781538654385
ASJC Scopus subject areas: Applied Mathematics, Mathematical Physics, Modelling and Simulation, Condensed Matter Physics
Keywords: image visual quality assessment, masking of unpredictable energy
DOIs:
10.1109/MMET.2018.8460285

Bibliographical note

JUFOID=72887
EXT="Lukin, Vladimir"
Source: Scopus
Source ID: 85054099331
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Technostress and social networking services: Uncovering strains and their underlying stressors

Numerous users of social networking sites and services (SNS) suffer from technostress and its various strains that hinder well-being. Despite a growing research interest on technostress, the extant studies have not explained what kinds of various strains can SNS use create and how can these strains be traced back to different stressors. To address this gap in research, we employed a qualitative approach by narrative interviews. As a contribution, our findings introduce four SNS strains (concentration problems, sleep problems, identity problems, and social relation problems) and explain how they link with different underlying SNS stressors. As practical implications, the findings of this study can help technostressed users to identify their SNS strains, understand how they are created, and increase their possibilities to avoid the strains in the future.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Industrial and Information Management, Jyväskylän yliopisto
Contributors: Salo, M., Pirkkalainen, H., Koskelainen, T.
Number of pages: 13
Pages: 41-53
Publication date: 2017

Host publication information

Title of host publication: Nordic Contributions in IS Research - 8th Scandinavian Conference on Information Systems, SCIS 2017, Proceedings
Publisher: Springer Verlag
ISBN (Print): 9783319646947

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 294
ISSN (Print): 1865-1348
ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management
Keywords: Social networking services, Social networking sites, Strains, Stressors, Technostress
DOIs:
10.1007/978-3-319-64695-4_4

Bibliographical note

jufoid=71106
Source: Scopus
Source ID: 85028352668
Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

The assessment of constructability: BIM cases

The constructability appraisal methods developed so far are based on evaluating and analyzing major design components and systems of an entire building, such as structural systems, materials and production techniques. There is still only a limited knowledge of the assessment methods of constructability using BIM as an intensifying technology. Forming constructability to a more explicit and measurable concept quantitative and qualitative assessment methods that can be applied systematically will be needed.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication
Organisations: Life Cycle Effectiveness of the Built Environment (LCE@BE), Aalto University
Contributors: Tauriainen, M., Puttonen, J., Saari, A., Laakso, P., Forsblom, K.
Number of pages: 7
Pages: 55-61
Publication date: 2015

Host publication information

Title of host publication: eWork and eBusiness in Architecture, Engineering and Construction - Proceedings of the 10th European Conference on Product and Process Modelling, ECPPM 2014
Publisher: CRC Press/Balkema
ISBN (Print): 9781138027107
ASJC Scopus subject areas: Modelling and Simulation
URLs:
<http://www.scopus.com/inward/record.url?scp=84907331486&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 84907331486
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

The development of constructability using BIM as an intensifying technology

According to the several international research and development articles, completed building plans that take care of constructability issues, contributes the achievement of construction objectives of time, cost and quality. A good constructability improves construction performance, productivity and quality. Building information modeling (BIM) has the similar effect to construction. BIM simulates the construction project in a virtual environment. It is possible to make constructability adjustments in the model, and practice construction before it is actualized.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Life Cycle Effectiveness of the Built Environment (LCE@BE), Aalto University
Contributors: Tauriainen, M., Mero, A. K., Lemström, A., Puttonen, J., Saari, A.
Number of pages: 4
Pages: 713-716
Publication date: 2012

Host publication information

Title of host publication: eWork and eBusiness in Architecture, Engineering and Construction - Proceedings of the European Conference on Product and Process Modelling 2012, ECPPM 2012
ISBN (Print): 9780415621281
ASJC Scopus subject areas: Hardware and Architecture, Modelling and Simulation
URLs:
<http://www.scopus.com/inward/record.url?scp=84863525009&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 84863525009
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Theory driven design and real proto typing of biomass pyrolytic stove

This article introduces a design approach integrating early design phase and model based engineering in order to develop innovative biomass gasifier system for rural communities in Africa. The need for such a systemic perspective is imposed by the imbrication of technical, ecological and cultural issues that cannot be ignored while designing new technology. The article proposes an integrated generic design theory approaches to discover and rank by order of importance system's variables and to single out most desired design parameters. A pre-design user requirement assessment was carried out to identify detailed stove's functions. Causal-ordering diagrams sketched for system's modelling. System functions were described graphically and synthesized through simple linear algebraic matrices. Contradictions in system functions were solved using Theory of Inventive Thinking (TRIZ 40). And system's optimization was done through simple Taguchi experimentation method. A two level L8 degree of freedom Taguchi table was used in the experimentation and optimization of the pyrolytic stove. The design approach was exemplified using the case of the "AKIBA" biomass stove.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Kenya Industrial Research and Development Institute (KIRDI), Aalto University School of Engineering, Department of Engineering Design and Production, Aalto University
Contributors: Ogeya, M. C., Coatanéa, E., Medyna, G.

Number of pages: 10
Pages: 69-78
Publication date: 2013

Host publication information

Title of host publication: Proceedings of the International Conference on Engineering Design, ICED
Volume: 9 DS75-09
ISBN (Print): 9781904670520
ASJC Scopus subject areas: Engineering (miscellaneous), Industrial and Manufacturing Engineering, Modelling and Simulation
Keywords: Design theory, Early design phase, Innovation, Optimisation, Systems engineering
URLs:
<http://www.scopus.com/inward/record.url?scp=84897650359&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 84897650359
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Time-dependent SIR modeling for D2D communications in indoor deployments

Device-to-device (D2D) communications is expected to become an integral part of the future 5G cellular systems. The connectivity performance of D2D sessions is heavily affected by the dynamic changes in the signal-to-interference ratio (SIR) caused by random movement of communicating pairs over a certain bounded area of interest. In this paper, taking into account the recent findings on the movement of users over a landscape, we characterize the probability density function (pdf) of SIR under stochastic motion of communicating D2D pairs on planar fractals. We demonstrate that the pdf of SIR depends on the fractal dimension and the spatial density of trajectories. The proposed model can be further used to investigate time-dependent user-centric performance metrics including the link data rate and the outage time.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Electronics and Communications Engineering, Research group: Emerging Technologies for Nano-Bio-Info-Cogno, Peoples' Friendship University of Russia, Keldysh Institute of Applied Mathematics, Department of Applied Probability and Informatics, Moscow City University
Contributors: Orlov, Y., Zenyuk, D., Samuylov, A., Moltchanov, D., Andreev, S., Romashkova, O., Gaidamaka, Y., Samouylov, K.
Number of pages: 6
Pages: 726-731
Publication date: 2017

Host publication information

Title of host publication: Proceedings - 31st European Conference on Modelling and Simulation, ECMS 2017
Publisher: EUROPEAN COUNCIL FOR MODELLING AND SIMULATION
ISBN (Electronic): 9780993244049
ASJC Scopus subject areas: Modelling and Simulation
Keywords: Cellular network, D2D communications, Fractal motion, SIR probability density function, Time-dependence
Source: Scopus
Source ID: 85021780590
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Timely report production from WWW data sources

In business intelligence, reporting is perceived by users as the most important area. Here, we present a case study of data integration for reporting within the World Health Organization (WHO). WHO produces Communicable Disease Epidemiological Profiles for emergency affected countries. Given the nature of emergencies, the production of these reports should be timely. In order to automate the production of the reports, we have introduced a method of integrating data from multiple sources by using the RDF (Resource Description Framework) format. The model of the data is described using an RDF ontology, making validation of the data from multiple sources possible. However, since RDF is highly technical, we have designed a graphical tool for the end user. The tool can be used to configure the data sources of a given report. After this, data for the report is generated from the sources. Finally, templates are used to generate the reports.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Research Community on Data-to-Decision (D2D), European Organization for Nuclear Research, Helsinki Institute of Physics, World Health Organization Avenue Appia 20
Contributors: Niinimäki, M., Niemi, T., Martin, S., Nummenmaa, J., Thanisch, P.

Number of pages: 12
Pages: 184-195
Publication date: 2012

Host publication information

Title of host publication: Workshops on Business Informatics Research, BIR 2011 International Workshops and Doctoral Consortium, Revised Selected Papers
Volume: 106 LNBIP
Publisher: Springer Verlag
ISBN (Print): 9783642292309

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 106 LNBIP
ISSN (Print): 18651348
ASJC Scopus subject areas: Business and International Management, Management Information Systems, Control and Systems Engineering, Information Systems and Management, Information Systems, Modelling and Simulation, Business, Management and Accounting(all)
Keywords: Data integration, OLAP, ontology, RDF, XML
DOIs:
10.1007/978-3-642-29231-6-15
URLs:
<http://www.scopus.com/inward/record.url?scp=84879722808&partnerID=8YFLogxK> (Link to publication in Scopus)
Source: Scopus
Source ID: 84879722808
Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

To network or not to network? Analysis of the Finnish software industry-A networking approach

The purpose of this paper is to study the role of networking in the development and present situation of Finnish software companies. Although the target of interest of this study is Finland, the conclusions can also to some extent be applied to other countries with mature software industries. In Finland there is uniquely wide longitudinal material on the software business available; the software industry survey is an annual study targeted for the branch, which has already been repeated for 18 consecutive years. The study shows that networking has been a key trend in the industry and also a driver for internationalization, but as it has not been identified very well in networking literature concerning the software industry, there is a clear need for further examination of software industry networks.

General information

Publication status: Published
MoE publication type: A4 Article in a conference publication
Organisations: Pori Department, Department of Information Management and Logistics, Research group: Novi, Research group: Software Engineering and Intelligent Systems
Contributors: Yrjönkoski, K., Helander, N., Jaakkola, H.
Number of pages: 11
Pages: 124-134
Publication date: 2016

Host publication information

Title of host publication: Software Business : 7th International Conference, ICSOB 2016, Ljubljana, Slovenia, June 13-14, 2016, Proceedings
Publisher: Springer Verlag
ISBN (Print): 9783319405148

Publication series

Name: Lecture Notes in Business Information Processing
Volume: 240
ISSN (Print): 1865-1348
ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering
Keywords: Networks, Software business
DOIs:
10.1007/978-3-319-40515-5_9

Bibliographical note

JUF0ID=71106
Source: Scopus

Source ID: 84976620429

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Towards a lean approach to reduce code smells injection: An empirical study

Software Quality Assurance is a complex and time-expensive task. In this study we want to observe how agile developers react to just-in-time metrics about the code smells they introduce, and how the metrics influence the quality of the output.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Free University of Bolzano-Bozen

Contributors: Taibi, D., Janes, A., Lenarduzzi, V.

Publication date: 2016

Host publication information

Title of host publication: Agile Processes in Software Engineering and Extreme Programming - 17th International Conference, XP 2016, Proceedings

Publisher: Springer Verlag

ISBN (Print): 9783319335148

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 251

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Control and Systems Engineering, Management Information Systems, Business and International Management, Information Systems, Modelling and Simulation, Information Systems and Management

DOIs:

10.1007/978-3-319-33515-5_30

Source: Scopus

Source ID: 84971570803

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

Towards an approach for evaluating the quality of requirements

In engineering design, the needs of stakeholders are often captured and expressed in natural language (NL). While this facilitates such tasks as sharing information with nonspecialists, there are several associated problems including ambiguity, incompleteness, understandability, and testability. Traditionally, these issues were managed through tedious procedures such as reading requirements documents and looking for errors, but new approaches are being developed to assist designers in collecting, analysing, and clarifying requirements. The quality of the end-product is strongly related to the clarity of requirements and, thus, requirements should be managed carefully. This paper proposes to combine diverse requirements quality measures found from literature. These metrics are coherently integrated in a single software tool. This paper also proposes a new metric for clustering requirements based on their similarity to increase the quality of requirement model. The proposed methodology is tested on a case study and results show that this tool provides designers with insight on the quality of individual requirements as well as with a holistic assessment of the entire set of requirements.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Intelligent dexterity for secure networked infrastructure and applications (IDSNIA), Aalto University

Contributors: Mokammel, F., Coatanea, E., Christophe, F., Ba Khouya, M., Medyna, G.

Publication date: 2013

Host publication information

Title of host publication: 33rd Computers and Information in Engineering Conference

Volume: 2 B

Publisher: American Society of Mechanical Engineers

Article number: V02BT02A024

ISBN (Print): 9780791855867

ASJC Scopus subject areas: Mechanical Engineering, Computer Graphics and Computer-Aided Design, Computer Science Applications, Modelling and Simulation

DOIs:

10.1115/DETC2013-13708

URLs:

<http://www.scopus.com/inward/record.url?scp=84896914578&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84896914578

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Towards usability heuristics for games utilizing speech recognition

Speech recognition technology has reached the maturity required by serious business applications, and the game industry is increasingly adopting the technology. Since usability is one of the key elements of enjoyability and, thus, the successfulness of games, a thorough analysis of the elements, properties and effects of this new user interface is needed. However, there seems to be no existing speech interface usability analysis methods for computer games. A pragmatic and rigorous framework, which the game industry could easily adopt, could help the utilization of speech recognition technology. In this paper, we discuss the usefulness of voice recognition in games and propose usability heuristics for games utilizing speech recognition.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Managing digital industrial transformation (mDIT), University of Turku, Turku Centre for Computer Science, Business and Innovation Development (BID), Free Lancer

Contributors: Halonen, A., Hyrynsalmi, S., Kimppa, K. K., Knuttila, T., Smed, J., Hakonen, H.

Number of pages: 5

Pages: 51-55

Publication date: 2012

Host publication information

Title of host publication: 4th Asian Conference on Intelligent Games and Simulation, GAME-ON ASIA 2012 - 4th Asian Simulation Technology Conference, ASTEC 2012

Publisher: EUROSIS

ISBN (Electronic): 9789077381687

ASJC Scopus subject areas: Artificial Intelligence, Human-Computer Interaction, Modelling and Simulation

Keywords: Games, Speech interface, Speech recognition, Usability heuristics, Voice interaction

URLs:

<http://www.scopus.com/inward/record.url?scp=84922463768&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 84922463768

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Transverse structure optimization of laterally-coupled ridge waveguide DFB lasers

A new figure of merit for single transverse mode operation and an accurate procedure for calculating the coupling coefficient in distributed feedback lasers with laterally-coupled ridge waveguide surface grating structures are introduced. Based on the difference in optical confinement between the pumped and un-pumped regions in the transverse plane, the single transverse mode figure of merit is effective and easy to calculate, while the improved coupling coefficient calculation procedure gives experimentally confirmed better results than the standard calculation approaches.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Optoelectronics Research Centre, Research group: Semiconductor Technology and Applications

Contributors: Uusitalo, T., Virtanen, H., Dumitrescu, M.

Number of pages: 2

Pages: 79-80

Publication date: 17 Aug 2016

Host publication information

Title of host publication: 16th International Conference on Numerical Simulation of Optoelectronic Devices, NUSOD 2016

Publisher: IEEE

Article number: 7547038

ISBN (Electronic): 9781467386036

ASJC Scopus subject areas: Electrical and Electronic Engineering, Electronic, Optical and Magnetic Materials, Modelling and Simulation, Numerical Analysis

DOIs:

10.1109/NUSOD.2016.7547038

Source: Scopus

Source ID: 84987653468

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Using the entity-attribute-value model for olap cube construction

When utilising multidimensional OLAP (On-Line Analytic Processing) analysis models in Business Intelligence analysis, it is common that the users need to add new, unanticipated dimensions to the OLAP cube. In a conventional implementation, this would imply frequent re-designs of the cube's dimensions. We present an alternative method for the addition of new dimensions. Interestingly, the same design method can also be used to import EAV (Entity-Attribute-Value) tables into a cube. EAV tables have earlier been used to represent extremely sparse data in applications such as biomedical databases. Though space-efficient, EAV-representation can be awkward to query. Our EAV-to-OLAP cube methodology has an advantage of managing many-to-many relationships in a natural manner. Simple theoretical analysis shows that the methodology is efficient in space consumption. We demonstrate the efficiency of our approach in terms of the speed of OLAP cube re-processing when importing EAV-style data, comparing the performance of our cube design method with the performance of the conventional cube design.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Research Community on Data-to-Decision (D2D), Helsinki Institute of Physics, European Organization for Nuclear Research

Contributors: Thanisch, P., Niemi, T., Niinimäki, M., Nummenmaa, J.

Number of pages: 14

Pages: 59-72

Publication date: 2011

Host publication information

Title of host publication: Perspectives in Business Informatics Research - 10th International Conference, BIR 2011, Proceedings

Volume: 90 LNBIP

Publisher: Springer Verlag

ISBN (Print): 9783642245107

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 90 LNBIP

ISSN (Print): 18651348

ASJC Scopus subject areas: Business, Management and Accounting(all), Information Systems and Management, Information Systems, Management Information Systems, Business and International Management, Control and Systems Engineering, Modelling and Simulation

Keywords: dimensions, EAV, OLAP

DOIs:

10.1007/978-3-642-24511-4_5

URLs:

<http://www.scopus.com/inward/record.url?scp=80054106590&partnerID=8YFLogxK> (Link to publication in Scopus)

Source: Scopus

Source ID: 80054106590

Research output: Chapter in Book/Report/Conference proceeding > Conference contribution > Scientific > peer-review

UX work in startups: Current practices and future needs

Startups are creating innovative new products and services while seeking fast growth with little resources. The capability to produce software products with good user experience (UX) can help the startup to gain positive attention and revenue. Practices and needs for UX design in startups are not well understood. Research can provide insight on how to design UX with little resources as well as to gaps about what kind of better practices should be developed. In this paper we describe the results of an interview study with eight startups operating in Finland. Current UX practices, challenges and needs for the future were investigated. The results show that personal networks have a significant role in helping startups gain professional UX advice as well as user feedback when designing for UX. When scaling up startups expect usage data and analytics to guide them towards better UX design.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Department of Pervasive Computing, Research area: User experience, Augmented Human Activities (AHA)

Contributors: Hokkanen, L., Väänänen-Vainio-Mattila, K.

Number of pages: 12

Pages: 81-92

Publication date: 2015

Host publication information

Title of host publication: Agile Processes in Software Engineering and Extreme Programming : 16th International Conference, XP 2015, Helsinki, Finland, May 25-29, 2015, Proceedings

Volume: 212

Publisher: Springer Verlag

ISBN (Print): 9783319186115

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 212

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering

Keywords: Lean, Startup, User experience

Electronic versions:

UX Work in Startups 2015

DOIs:

10.1007/978-3-319-18612-2_7

URLs:

<http://urn.fi/URN:NBN:fi:tuni-202004153264>

Source: Scopus

Source ID: 84942786975

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Wealthy, healthy and/or happy —what does 'ecosystem health' stand for?

The health of a software ecosystem is argued to be a key indicator of well-being, longevity and performance of a network of companies. In this paper, we address what scientific literature actually means with the concept of 'ecosystem health' by selecting relevant articles with systematic literature review. Based on the final set of 38 papers, we found that despite a common base, the term has been used to depict a wide range of hoped characteristics of a software ecosystem. However, the number of studies addressing the topic is shown to grow while empirical studies are still rare. Thus, further studies should aim to standardize the terminology and concepts in order to create a common base for future work. Further work is needed also to develop early indicators that warn and guides companies on problems with their ecosystems.

General information

Publication status: Published

MoE publication type: A4 Article in a conference publication

Organisations: Pori Department, Research group: Business Ecosystems, Networks and Innovations, Managing digital industrial transformation (mDIT), VTT Technical Research Centre of Finland, University of Turku, University of Turku, Turku School of Economics, Department of Management and Entrepreneurship, Innovation and Knowledge Economy, VTT Technical Research Centre of Finland

Contributors: Hyrynsalmi, S., Seppänen, M., Nokkala, T., Suominen, A., Järvi, A.

Number of pages: 16

Pages: 272-287

Publication date: 2015

Host publication information

Title of host publication: 6th International Conference on Software Business, ICSOB 2015; Braga; Portugal; 10 June 2015 through 12 June 2015

Volume: 210

Publisher: Springer Verlag

ISBN (Print): 9783319195926

Publication series

Name: Lecture Notes in Business Information Processing

Volume: 210

ISSN (Print): 1865-1348

ASJC Scopus subject areas: Business and International Management, Management Information Systems, Modelling and Simulation, Information Systems, Information Systems and Management, Control and Systems Engineering

Keywords: Business ecosystem, Ecosystem health, Software ecosystem, Systematic literature study

DOIs:

10.1007/978-3-319-19593-3_24

URLs:

<http://www.scopus.com/inward/record.url?scp=84937434086&partnerID=8YFLogxK> (Link to publication in Scopus)

Bibliographical note

EXT="Hyrnsalmi, Sami"

Source: Scopus

Source ID: 84937434086

Research output: Chapter in Book/Report/Conference proceeding › Conference contribution › Scientific › peer-review

Neural networks, cell cultures and some older work on data analysis.**General information**

Publication status: Published

Organisations: Faculty of Biomedical Sciences and Engineering

Contributors: Acimovic, J.

Publication date: 15 Jun 2009

Peer-reviewed: Unknown

Event: Paper presented at Okinawa Computational Neuroscience Course 2009, Japan.

ASJC Scopus subject areas: Cellular and Molecular Neuroscience, Neuroscience (miscellaneous), Modelling and Simulation, Signal Processing, Human-Computer Interaction

Keywords: computational neuroscience, spiking networks, complex networks, cortical networks, brain-machine interfaces

Research output: Other conference contribution › Paper, poster or abstract › Scientific